

## ÖLFLEX® ROBUST 210

Proven all-weather control cable – resistant to a wide range of chemical media

ÖLFLEX® ROBUST 210 - Control cable, weather, bio oil, detergent and hot water resistant for use in food & beverage industry and composting plants

### Info

Good weather resistance

Good chemical resistance please see Appendix T1

Reduced outer diameter



Suitable for outdoor use



Good chemical resistance



Halogen-free



Cold-resistant



UV-resistant



### Benefits

Outstanding weather, ozone and UV resistance together with the wide temperature range enable versatile use for indoor and outdoor applications

Resistant to contact with organic oils and the related emulsions as well as a multitude of plant, animal or synthetic-based greases and waxes

Good resistance to ammonia compounds and bio-gases

Last Update (24.11.2021)

©2021 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## ÖLFLEX® ROBUST 210

Good resistance to cold and hot water as well as water-soluble cleaning and cooling agents  
Well-suited to steam cleaning

### Application range

Machine tool building, medical technology, laundries, car washing equipment, chemical industry, composting plants, sewage works  
Food and beverage industry, especially for production and processing equipment of milk and meat products  
Agricultural equipment  
For indoor and outdoor use

### Product features

Good chemical resistance to ester-based hydraulic fluids  
Ozone, UV and weather-resistant according to EN 50396 and HD 605 S2  
Flexible down to -40 °C  
Low-capacitance design  
Number-coded cores

### Norm references / Approvals

Based on VDE 0250 / 0285  
Certified resistance to disinfection and cleaning solutions used in food and beverage industry  
Suitable for use in fresh water down to 10 m depth at max. water temperature of +40 °C according to EN 50565-2

### Product Make-up

Fine-wire, bare copper conductor  
Core insulation made of modified PP  
Cores twisted in layers  
Outer sheath made of special TPE  
Sheath colour: black

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000104 ETIM 6.0 Class-Description: Control cable
Core identification code:	Black with white numbers acc. to VDE 0293-334
Conductor stranding:	Fine wire according to VDE 0295, class 5/IEC 60228 class 5
Minimum bending radius:	Occasional flexing: 15 x outer diameter Fixed installation: 4 x outer diameter
Nominal voltage:	U0/U: 300/500 V
Test voltage:	4000 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Temperature range:	Occasional flexing: -40 °C to +80 °C Fixed installation: -50 °C to +80 °C

### Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Last Update (24.11.2021)

©2021 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## ÖLFLEX® ROBUST 210

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)

Packaging size: coil  $\leq$  30 kg or  $\leq$  250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Single lengths for sizes:  $\geq$  4G16 max. 600 m;  $\geq$  4G25 max. 300 m;  $\geq$  4G50 max. 250 m

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

The final resistance of the cable to the effects of chemicals and their compounds can only be assessed in real-life conditions, taking into account the totality of factors affecting the cable. Relevant factors can affect the performance and lifespan of the cable.

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter [mm]	Copper index (kg/km)
ÖLFLEX® ROBUST 210			
0021880	2 X 0.5	4.9	10
0021881	3 G 0.5	5.2	15
0021882	3 X 0.5	5.2	15
0021883	4 G 0.5	5.8	19.2
0021884	4 X 0.5	5.8	19.2
0021885	5 G 0.5	6.3	24
0021886	5 X 0.5	6.3	24
0021888	7 G 0.5	6.9	33.6
0021889	7 X 0.5	6.9	33.6
0021890	10 G 0.5	8.8	48
0021891	12 G 0.5	9.1	58
0021892	18 G 0.5	10.8	86.4
0021893	25 G 0.5	12.7	120
0021897	2 X 0.75	5.5	14.4
0021898	3 G 0.75	5.8	21.6
0021899	3 X 0.75	5.8	21.6
0021900	4 G 0.75	6.3	28.8
0021901	4 X 0.75	6.3	28.8
0021902	5 G 0.75	6.9	36
0021903	5 X 0.75	6.9	36
0021904	7 G 0.75	7.5	50
0021905	7 X 0.75	7.5	50
0021907	12 G 0.75	10.1	86
0021908	18 G 0.75	12	130
0021909	25 G 0.75	14.1	180
0021910	34 G 0.75	16.3	245
0021911	41 G 0.75	17.8	296
0021912	50 G 0.75	19.6	360
0021913	2 X 1.0	5.8	19.2
0021914	3 G 1.0	6.1	28.8
0021915	3 X 1.0	6.1	28.8
0021916	4 G 1.0	6.6	38.4
0021917	4 X 1.0	6.6	38.4

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter [mm]	Copper index (kg/km)
0021918	5 G 1.0	7.3	48
0021919	5 X 1.0	7.3	48
0021920	7 G 1.0	8.1	67
0021921	10 G 1.0	10.4	96
0021922	12 G 1.0	10.7	115
0021923	18 G 1.0	12.9	173
0021924	25 G 1.0	15	240
0021925	34 G 1.0	17.5	326
0021926	41 G 1.0	19.2	394
0021927	50 G 1.0	21	480
0021928	2 X 1.5	6.4	29
0021929	3 G 1.5	6.8	43
0021930	3 X 1.5	6.8	43
0021931	4 G 1.5	7.4	58
0021932	4 X 1.5	7.4	58
0021933	5 G 1.5	8.3	72
0021934	5 X 1.5	8.3	72
0021936	7 G 1.5	9	101
0021937	7 X 1.5	9	101
0021938	10 G 1.5	11.8	143
0021940	12 G 1.5	12.2	173
0021941	18 G 1.5	14.6	259
0021942	25 G 1.5	17.2	360
0021943	34 G 1.5	19.8	490
0021945	50 G 1.5	24	720
0021946	2 X 2.5	7.6	48
0021947	3 G 2.5	8.3	72
0021949	4 G 2.5	9	96
0021951	5 G 2.5	10.1	120
0021953	7 G 2.5	11.2	168
0021954	12 G 2.5	15.1	288
0021963	3 G 4.0	10.1	115
0021964	4 G 4.0	11.1	157
0021965	5 G 4.0	12.4	192

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter [mm]	Copper index (kg/km)
0021966	7 G 4.0	13.6	269
0021967	4 G 6.0	13.3	230
0021968	5 G 6.0	14.8	288
0021969	4 G 10.0	16.5	384
0021970	5 G 10.0	18.4	480
0021971	4 G 16.0	18.8	614.4
0021972	4 G 25.0	23.5	960
0021973	4 G 35.0	26.4	1344

Last Update (24.11.2021)  
©2021 Lapp Group - Technical changes reserved  
Product Management [www.lappkabel.de](http://www.lappkabel.de)  
You can find the current technical data in the corresponding data sheet.  
PN 0456 / 02\_03\_16

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Ribbon Cables / IDC Cables](#) category:*

*Click to view products by [Lapp Kabel](#) manufacturer:*

Other Similar products are found below :

[FSK-12A](#) [AWG28-10G](#) [EHJ3C](#) [EHJ4C](#) [FSP-25A](#) [cab-LVDV-DAT-34-15](#) [49635-C62-S2](#) [1-3636-600-5204](#) [92315-1408](#) [426171120-3](#) [2-1589735-3](#) [JSM015PP2DCC23N](#) [92301-0283](#) [ACL-eSSI-2](#) [92301-0718](#) [MMSDT-06-20-S-05.5-D-K-LDX](#) [IDD-04-G](#) [IDD-25-G](#) [NM-2J2-051-PS1-JJAB](#) [1700/26SF \(100FT\)](#) [1700/34SF \(100FT\)](#) [3801/09 \(100FT\)](#) [S30109](#) [96053-0000-00-0](#) [NM-2J2-065-SS1-JJ00-272](#) [7940098862](#) [IDMD-13-D-07.87](#) [166466](#) [TCMD-07-01](#) [HQCD-030-40.00-TTL-SBL-1-N](#) [HDR-201768-01-PCIEC](#) [DS1052-082B2NA201501](#) [DS1052-102B2NA201501](#) [DS1052-122B2MA201501](#) [DS1052-122B2NA201501](#) [DS1052-262B2NA201501](#) [DS1052-302B2MA201501](#) [DS1052-302B2MA203001](#) [DS1052-302B2MA206001](#) [DS1052-302B2NA201501](#) [DS1052-302B2NA203001](#) [DS1052-302B2NA206001](#) [DS1052-342B2MA201501](#) [DS1052-342B2MA203001](#) [DS1052-342B2NA201501](#) [DS1052-342B2NA203001](#) [DS1052-342B2NA206001](#) [DS1052-402B2MA201501](#) [DS1052-402B2MA203001](#) [DS1052-402B2MA206001](#)