

UNITRONIC® LiYY A

Data transmission cable with colour code acc. to DIN 47100 - UL/CSA recognized

UNITRONIC® LiYY A: Low-frequency PVC data cable, DIN 47100 color coded, UL CSA AWM, Flexible (0.34² Maxi TERMINAL®), Flame retardant, Instrumentation Control

Info

A for Advanced
here: UL and CSA certifications
Further dimensions/colours on request



Benefits

For various applications

Application range

Wiring of devices, machines and plants intended for export to the North American market or countries where UL-/CSA certified cables are used.

For the North American market

Product features

Flame-retardant acc. to IEC 60332-1-2,
UL VW-1 & CSA FT 1

Norm references / Approvals

UL AWM Style 2464
CSA AWM I/II A
UL File No. E63634

Product Make-up

Multi-wire strand made of tinned copper wires
Core insulation made of PVC
Outer sheath made of special PVC compound
Outer sheath colour: Dark grey

Last Update (30.09.2021)

©2021 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

UNITRONIC® LiYY A

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000104 ETIM 6.0 Class-Description: Control cable
Core identification code:	DIN 47100 without colour repetition, refer to Appendix T9
Conductor stranding:	AWG conductor sizes, 7 or 19 wires
Minimum bending radius:	Occasional flexing: 15 x outer diameter Fixed installation: 4 x Outer diameter
Nominal voltage:	UL/CSA: 300 V
Test voltage:	1500 V
Temperature range:	Occasional flexing: -5°C up to +70°C (UL: +80 °C) Fixed installation (IEC): -40°C bis +80°C UL: max. +80°C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: Coil 152 m; Drum 305 m

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Number of cores and AWG per conductor	Outer diameter [mm]	Copper index [kg/km]
UNITRONIC® LiYY A			
0022403	3 x AWG26/7	3.8	4.2
0022404	4 x AWG26/7	4	5.6
0022405	5 x AWG26/7	4.3	7
0022408	8 x AWG26/7	5.1	11.2
0022412	12 x AWG26/7	5.8	16.8
0022416	16 x AWG26/7	6.3	22.4
0022421	21 x AWG26/7	7	29.4
0022502	2 x AWG24/7	4	4.6
0022505	5 x AWG24/7	4.8	11.5
0022508	8 x AWG24/7	5.7	18.4
0022512	12 x AWG24/7	6.6	27.6
0022602	2 x AWG22/7	4.8	6.8
0022603	3 x AWG22/7	5	10.2
0022604	4 x AWG22/7	5.4	13.6
0022605	5 x AWG22/7	5.9	17
0022607	7 x AWG22/7	6.4	23.3
0022608	8 x AWG22/7	6.9	27.2
0022612	12 x AWG22/7	8.2	40.8
0022616	16 x AWG22/7	9.1	54.4
0022624	24 x AWG22/7	11.6	81.6
0022632	2 x AWG20/7	5.3	11.2
0022642	2 x AWG19/19	5.6	15

Last Update (30.09.2021)
 ©2021 Lapp Group - Technical changes reserved
 Product Management www.lappkabel.de
 You can find the current technical data in the corresponding data sheet.
 PN 0456 / 02_03_16

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ribbon Cables / IDC Cables](#) category:

Click to view products by [Lapp Kabel](#) manufacturer:

Other Similar products are found below :

[FSK-12A](#) [AWG28-10G](#) [EHJ3C](#) [EHJ4C](#) [FSP-25A](#) [cab-LVDV-DAT-34-15](#) [49635-C62-S2](#) [1-3636-600-5204](#) [92315-1408](#) [426171120-3](#) [2-1589735-3](#) [JSM015PP2DCC23N](#) [92301-0283](#) [ACL-eSSI-2](#) [92301-0718](#) [MMSDT-06-20-S-05.5-D-K-LDX](#) [IDD-04-G](#) [NM-2J2-051-PS1-JJAB](#) [1700/26SF \(100FT\)](#) [1700/34SF \(100FT\)](#) [3801/09 \(100FT\)](#) [DS1057-09A282R-76.5](#) [DS1057-10A282R-76.5](#) [DS1057-20A282R-76.5](#) [DS1057-24A282R-76.5](#) [DS1057-26A282R-76.5](#) [DS1057-30A282R-76.5](#) [DS1057-34A282R-76.5](#) [DS1057-40A282R-76.5](#) [DS1057-60A282R-76.5](#) [DS1057-64A282R-76.5](#) [DS1058-08M28-30.5](#) [DS1058-30M28-30.5](#) [0015712](#) [0015905](#) [S30109](#) [11203](#) [11223](#) [11243](#) [11262](#) [0037147](#) [0022512](#) [0022412](#) [0022416](#) [0022421](#) [0022632](#) [0022602](#) [0022502](#) [0022603](#) [0022403](#)