

## ÖLFLEX® SERVO FD 796 CP

Screened servo cable with PUR outer sheath for highly dynamic power chain application - certified

ÖLFLEX® SERVO FD 796 CP - Screened servo cable for high dynamic power chain application in harsh conditions with UL/CSA AWM and VDE certification

### Info

Extended Line Performance - Long travel lengths or high acceleration  
Product range extension



Halogen-free



Mechanical resistance



Oil-resistant



Power chain



Interference signals



UV-resistant

### Benefits

Allows much faster speed and accelerations which increases the economic efficiency of the machines

Suitable for use with servomotor product lines from leading drive manufacturers

Low capacitance design enables longer cable connection between frequency converter and motor

Resistant to contact with many mineral oil-based lubricants, diluted acids, aqueous alkaline solutions and other chemical media

Wide temperature range for applications in harsh climatic environments

Copper braiding screens the cable against

Last Update (29.09.2021)

©2021 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## ÖLFLEX® SERVO FD 796 CP

electromagnetic interference

### Application range

Connecting cable between servo controller and motor  
In power chains or moving machine parts  
For use in assembling & pick-and-place machinery  
Particularly in wet areas of machine tools and transfer lines  
Assembly lines, production lines, in all kinds of machines  
For indoor and outdoor use

### Product features

Flammability:  
UL/CSA: VW-1, FT1  
IEC/EN: 60332-1-2  
Halogen-free materials  
Abrasion and notch-resistant  
Oil-resistant

### Norm references / Approvals

VDE - Reg. - No. 8591  
(0027925,..926,..927,..930 pending)  
UL AWM Style 20234  
cULus AWM I/II A/B, 1000V 80° FT1  
CSA AWM I/II A, 1000V 80° FT1  
UL File No. E63634  
For use in power chains: Please comply with assembly guideline Appendix T3

### Product Make-up

Extra-fine wire strand made of bare copper wires (class 6)  
Core insulation: polypropylene (PP)  
Individual design depending on the item:  
Power cores without or with one or two individually shielded control core pairs twisted together in short lay lengths;  
Power cores with control core triplet twisted together in short lay lengths  
Non-woven wrapping  
Tinned-copper braiding  
PUR outer sheath, orange (RAL 2003)

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000104 ETIM 6.0 Class-Description: Control cable
Core identification code:	Power cores: black with marking U/L1/C/L+; V/L2; W/L3/D /L-; GN/YE protective conductor Single-paired versions: individual design depending on the item black; white or brown; white Double-paired versions: black with white numbers 5; 6; 7; 8 0.34 mm <sup>2</sup> pairs: WH/BN/GN/YE Triplet: black with white numbers 1; 2; 3
Conductor stranding:	Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6

Last Update (29.09.2021)

©2021 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## ÖLFLEX® SERVO FD 796 CP

Minimum bending radius:	Flexing: up from 7.5 x outer diameter (up to 16mm <sup>2</sup> ) up from 10 x outer diameter (from 25mm <sup>2</sup> ) Fixed installation: 4 x outer diameter
Nominal voltage:	Power cores and control cores: IEC U0/U: 600/1000 V UL & CSA: 1000 V
Test voltage:	Core/Core: 4 kV Core/Screen: 2 kV
Protective conductor:	G = with GN-YE protective conductor
Temperature range:	Flexing: -40 °C to +90 °C (UL/CSA: +80 °C) Fixed installation: -50 °C to +90 °C (UL/CSA: +80 °C)
Bending cycles & operation parameters:	See Selection Table A2-1 in the appendix of our online catalogue

### Note

Unless specified otherwise, the shown product values are nominal values at room temperature. Detailed values (e.g. tolerances) are available upon request.

Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm) approx.	Copper index (kg/km)
ÖLFLEX® SERVO FD 796 CP			
0027950	4 G 1,5	9.1	79
0027951	4 G 2,5	10.6	129
0027952	4 G 4	11.9	186
0027953	4 G 6	14.5	296
0027954	4 G 10	17.5	449
0027955	4 G 16	21.6	716
0027956	4 G 25	25.2	1073
0027957	4 G 35	28.6	1480
0027958	4 G 50	33.4	2115
0027930	4 G 0,75 + (2 x 0,5)	11.0	85.5
0027925	4 G 1 + (2 x 0,5)	11.5	97.4
0027931	4 G 1 + (2 x 1,0)	11.7	106.7
0027926	4 G 1,5 + (2 x 0,5)	12.0	117.2
0027948	4 G 1,5 + (2 x 1,0)	12.2	129.9
0027932	4 G 1,5 + (3 x 1,0)	12.0	143.8
0027959	4 G 1,5 + (2 x 1,5)	11.6	135
0027927	4 G 2,5 + (2 x 0,5)	12.6	161.2
0027978	4 G 2,5 + (2 x 1,0)	13.5	169.2
0027933	4 G 2,5 + (3 x 1,0)	13.5	204.3
0027960	4 G 2,5 + (2 x 1,5)	13.4	188
0027981	4 G 4 + (2 x 1,0)	14.8	238.9
0027934	4 G 4 + (3 x 1,0)	14.7	250
0027961	4 G 4 + (2 x 1,5)	14.8	235
0027982	4 G 6 + (2 x 1,0)	16.8	339.5
0027962	4 G 6 + (2 x 1,5)	16.8	329
0027935	4 G 6 + (3 x 1,5)	16.5	381.4
0027983	4 G 10 + (2 x 1,0)	18.8	530.1
0027963	4 G 10 + (2 x 1,5)	19.4	515
0027936	4 G 10 + (3 x 1,5)	19.7	568.9
0027984	4 G 16 + (2 x 1,0)	22.8	786.7
0027964	4 G 16 + (2 x 1,5)	23.1	757
0027937	4 G 16 + (3 x 1,5)	23.3	824.6
0027965	4 G 25 + (2 x 1,5)	26.6	1147

Last Update (29.09.2021)  
 ©2021 Lapp Group - Technical changes reserved  
 Product Management www.lappkabel.de  
 You can find the current technical data in the corresponding data sheet.  
 PN 0456 / 02\_03.16

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm) approx.	Copper index (kg/km)
0027966	4 G 35 + (2 x 1,5)	30.9	1538
0027967	4 G 50 + (2 x 1,5)	34.0	2181
0027968	4 G 1,0 + 2 x (2 x 0,75)	11.6	138.4
0027969	4 G 1,5 + 2 x (2 x 0,75)	12.2	159
0027970	4 G 2,5 + 2 x (2 x 1,0)	14.6	207
0027980	4 G 4 + 2 x (2 x 1,0)	16.1	274
0027971	4 G 4 + (2 x 1,0) + (2 x 1,5)	16.3	344
0027972	4 G 6 + (2 x 1,0) + (2 x 1,5)	18.1	436
0027973	4 G 10 + (2 x 1,0) + (2 x 1,5)	21.8	610
0027974	4 G 16 + 2 x (2 x 1,5)	25.5	801
0027975	4 G 25 + 2 x (2 x 1,5)	28.8	1187
0027976	4 G 35 + 2 x (2 x 1,5)	30.9	1588
0027977	4 G 50 + 2 x (2 x 2,5)	36.3	2557

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Ethernet Cables / Networking Cables](#) category:*

*Click to view products by [Lapp Kabel](#) manufacturer:*

Other Similar products are found below :

[73-7797-25](#) [MCJB2-10P6Q7-120](#) [84909-0204](#) [1200700174](#) [1200860368](#) [1410147](#) [E16A06002M030](#) [E200102-009-S1](#) [AX105346-EW](#)  
[MT14-187L](#) [17-103530](#) [190-038045-01](#) [NK5EPC18RDY](#) [NK5EPC18VLY](#) [NK5EPC18YLY](#) [NK5EPC1GRY](#) [NK5EPC4Y](#) [NK5EPC6YLY](#)  
[NK5EPC8BLY](#) [NK5EPC9YLY](#) [1969343-6](#) [C501100010](#) [C501106002](#) [C501106007](#) [C501106015](#) [C501106025](#) [C601102010](#) [C601104010](#)  
[C601106007](#) [C601106015](#) [2142758-2](#) [2168427-2](#) [CAT1106007](#) [21949-1](#) [2J1866A](#) [RJF SFTP 5E 0500](#) [AX100351](#) [MN14CEC/ST](#)  
[C501100015](#) [C501106004](#) [C501106010](#) [C5F1108007](#) [C601104004](#) [C601106004](#) [CA21106004](#) [CA21106010](#) [CA21109007](#) [CA21109010](#)  
[UTPCH14GY](#) [45-5684](#)