

JE-Y(ST)Y...BD

Static screened installation cable for industrial electronics

JE-Y(ST)Y...BD installation cable for industrial electronics, VDE 0815, PVC, solid conductor, pairs, bundle laying, screened/ static foil, stationary use

Info

In accordance with DIN VDE 0815



Interference signals

Benefits

Perfect for cost-effective installation, e.g. connections with insulation displacement technology (IDC).

Aluminium-laminated plastic foil static screen with tin-plated drain wire minimises the interference of high frequency, electromagnetic fields

Decoupling of circuits by means of twisted-pair (TP) design (crosstalk effects)

Application range

Connection cable for fixed installation in industrial control systems, as required in measurement, control, signalling and data applications

Industrial electronics

For fixed installation on and under plaster, in dry and damp rooms

Product features

The 2-pair version (2x2x0.8) is twisted into a star quad

Flame-retardant according IEC 60332-1-2

JE-Y(ST)Y...BD EB:

For intrinsically safe circuits (type of protection i - intrinsic safety) according to IEC 60079-14:2013 / EN 60079-14:2014 / VDE 0165-1:2014, section 16.2.2

Norm references / Approvals

Last Update (23.02.2021)

©2021 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

JE-Y(ST)Y...BD

In accordance with DIN VDE 0815
type JE-Y(ST)Y...BD

Product Make-up

Solid bare copper conductor
Core insulation made of PVC
2 cores twisted into a pair, and 4 pairs into units (for 2 x 2 x 0.8 as star quad cable)
Foil wrapping,
static screening made of aluminium-laminated plastic film with copper drain wire
Outer sheath made of PVC
Outer sheath colour: grey (similar to pebble grey/ RAL 7032)

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000829 ETIM 5.0 Class-Description: Signal-/telecommunications cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000829 ETIM 6.0 Class-Description: Signal-/telecommunications cable
Core identification code:	according to VDE 0815, refer to Appendix T10
Mutual capacitance:	max. 100 nF/km
Coupling:	approx. 200 pF/100 m
Inductivity:	approx. 0.65 mH/km
Conductor stranding:	Single-wire (solid conductor) 0.8 mm: 0.50 mm ²
Minimum bending radius:	Fixed installation: 6 x outer diameter
Test voltage:	Core/core: 500 V Core/screen: 2000 V
Loop resistance:	max. 73.2 Ohm/km
Temperature range:	Occasional flexing: -5°C to +50°C Fixed installation: -30°C to +70°C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 100/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Number of cores and cable diameter (mm)	Outer diameter [mm]	Copper index (kg/km)
JE-Y(ST)Y...BD			
0034190	2 x 2 x 0.8	6	25
0034191	4 x 2 x 0.8	8.5	45
0034192	8 x 2 x 0.8	11	85
0034193	12 x 2 x 0.8	13	126
0034194	16 x 2 x 0.8	14.5	166
0034195	20 x 2 x 0.8	16	206
0034197	40 x 2 x 0.8	22	407

Last Update (23.02.2021)
 ©2021 Lapp Group - Technical changes reserved
 Product Management www.lappkabel.de
 You can find the current technical data in the corresponding data sheet.
 PN 0456 / 02_03_16

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ribbon Cables / IDC Cables](#) category:

Click to view products by [Lapp Kabel](#) manufacturer:

Other Similar products are found below :

[FSK-12A](#) [AWG28-10G](#) [EHJ3C](#) [EHJ4C](#) [FSP-25A](#) [cab-LVDV-DAT-34-15](#) [49635-C62-S2](#) [1-3636-600-5204](#) [92315-1408](#) [426171120-3](#) [2-1589735-3](#) [JSM015PP2DCC23N](#) [92301-0283](#) [ACL-eSSI-2](#) [92301-0718](#) [MMSDT-06-20-S-05.5-D-K-LDX](#) [IDD-04-G](#) [NM-2J2-051-PS1-JJAB](#) [1700/26SF \(100FT\)](#) [1700/34SF \(100FT\)](#) [3801/09 \(100FT\)](#) [DS1058-08M28-30.5](#) [DS1058-30M28-30.5](#) [0015712](#) [0015905](#) [S30109](#)
[11203](#) [11223](#) [11243](#) [11262](#) [0037147](#) [0022512](#) [0022412](#) [0022416](#) [0022421](#) [0022632](#) [0022602](#) [0022502](#) [0022603](#) [0022403](#) [0022604](#)
[0022404](#) [0022605](#) [0022505](#) [0022405](#) [0022607](#) [0022608](#) [0022508](#) [0022408](#) [0011022](#)