

UNITRONIC® LiHCH (TP)

Screened halogen-free data transmission cable with colour code acc. to DIN 47100 and twisted pairs

UNITRONIC® LiHCH (TP): Low-frequency halogen-free data cable flexible (0.34 mm² multi-wire Maxi TERMI-POINT®) 47100 low capacitance, low smoke density, screened

Info

TP = twisted pair

CPR: Article number choice under www.lappkabel.com/cpr



Halogen-free



Interference signals

Benefits

Halogen-free: to protect human life and valuable assets in the event of a fire, through low smoke density and low amount of corrosive gases

Low capacitance due to polyolefin-based insulation

Overall braid minimises electrical interference

Decoupling of circuits by means of twisted-pair (TP) design (crosstalk effects)

Application range

Suitable for areas with a high density of people as well as high-value property that must be protected in the event of a fire
For use within public buildings, transport systems and industrial plants

For data processing, measurement and control engineering, safety related systems and as electronics cable

For use in computer systems, instrumentation systems, office equipment, balances -
wherever screened, halogen-free, small-diameter cables are needed.

Product features

Flame-retardant according IEC 60332-1-2

Last Update (02.04.2021)

©2021 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

UNITRONIC® LIHCH (TP)

Low smoke zero halogen (LSZH)

Halogen-free as per IEC 60754-1, Low corrosivity/ acidity of combustion gases per IEC 60754-2, Low toxicity of comb. gases per EN 50305

Low smoke density according to IEC 61034-2

Norm references / Approvals

Based on VDE 0812

Product Make-up

Fine-wire strand made of bare copper wires

Core insulation made of special halogen-free compound

TP structure

Tinned-copper braiding

Outer sheath made of special halogen-free compound

Outer sheath colour: pebble grey (RAL 7032)

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000104 ETIM 6.0 Class-Description: Control cable
Core identification code:	DIN 47100 without colour repetition, refer to Appendix T9
Mutual capacitance:	C/C approx. 80 nF/km C/S approx. 120 nF/km
Coupling:	At 1 kHz: approx. 300 pF/100 m
Inductivity:	approx. 0.65 mH/km
Conductor stranding:	Fine copper wire strands
Minimum bending radius:	Occasional flexing: 15 x outer diameter Fixed installation: 6 x outer diameter
Test voltage:	1200 V
Temperature range:	Occasional flexing: -5°C to +70°C Fixed installation: -30°C to +80°C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil \leq 30 kg or \leq 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)
UNITRONIC® LIHCH (TP)			
0038302	2 x 2 x 0.14	5.5	18.5
0038303	3 x 2 x 0.14	6	23
0038304	4 x 2 x 0.14	6.4	26.6
0038308	8 x 2 x 0.14	8.4	53.7
0038312	12 x 2 x 0.14	9.1	66
0038316	16 x 2 x 0.14	10.4	79
0038325	25 x 2 x 0.14	12.7	113
0038402	2 x 2 x 0.25	6.5	28
0038403	3 x 2 x 0.25	7.3	39.6
0038404	4 x 2 x 0.25	7.8	44.9
0038406	6 x 2 x 0.25	8.7	69.5
0038408	8 x 2 x 0.25	10.5	76.9
0038412	12 x 2 x 0.25	11.5	120
0038416	16 x 2 x 0.25	12.7	146.5
0038602	2 x 2 x 0.5	8.1	48.1
0038603	3 x 2 x 0.5	8.9	73.7
0038604	4 x 2 x 0.5	9.6	82
0038606	6 x 2 x 0.5	11.3	110
0038608	8 x 2 x 0.5	13.3	139
0038612	12 x 2 x 0.5	15.1	198.3
0038616	16 x 2 x 0.5	16.7	240
0038702	2 x 2 x 0.75	8.7	58
0038704	4 x 2 x 0.75	10.9	108
0038708	8 x 2 x 0.75	14.9	180
0038802	2 x 2 x 1.0	9.2	84
0038803	3 x 2 x 1.0	10.6	96
0038804	4 x 2 x 1.0	11.5	121

Last Update (02.04.2021)
 ©2021 Lapp Group - Technical changes reserved
 Product Management www.lappkabel.de
 You can find the current technical data in the corresponding data sheet.
 PN 0456 / 02_03.16

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ribbon Cables / IDC Cables](#) category:

Click to view products by [Lapp Kabel](#) manufacturer:

Other Similar products are found below :

[FSK-12A](#) [AWG28-10G](#) [EHJ3C](#) [EHJ4C](#) [FSP-25A](#) [cab-LVDV-DAT-34-15](#) [49635-C62-S2](#) [1-3636-600-5204](#) [92315-1408](#) [426171120-3](#) [2-1589735-3](#) [JSM015PP2DCC23N](#) [92301-0283](#) [ACL-eSSI-2](#) [92301-0718](#) [MMSDT-06-20-S-05.5-D-K-LDX](#) [IDD-04-G](#) [IDD-25-G](#) [NM-2J2-051-PS1-JJAB](#) [1700/26SF \(100FT\)](#) [1700/34SF \(100FT\)](#) [3801/09 \(100FT\)](#) [S30109](#) [96053-0000-00-0](#) [NM-2J2-065-SS1-JJ00-272](#) [7940098862](#) [IDMD-13-D-07.87](#) [166466](#) [HQCD-030-40.00-TTL-SBL-1-N](#) [HDR-201768-01-PCIEC](#) [DS1052-082B2NA201501](#) [DS1052-102B2NA201501](#) [DS1052-122B2MA201501](#) [DS1052-122B2NA201501](#) [DS1052-262B2NA201501](#) [DS1052-302B2MA201501](#) [DS1052-302B2MA203001](#) [DS1052-302B2MA206001](#) [DS1052-302B2NA201501](#) [DS1052-302B2NA203001](#) [DS1052-302B2NA206001](#) [DS1052-342B2MA201501](#) [DS1052-342B2MA203001](#) [DS1052-342B2NA201501](#) [DS1052-342B2NA203001](#) [DS1052-342B2NA206001](#) [DS1052-402B2MA201501](#) [DS1052-402B2MA203001](#) [DS1052-402B2MA206001](#) [DS1052-402B2NA201501](#)