

## H1Z2Z2-K, optimized version

Crosslinked H1Z2Z2-K solar/PV cable per EN 50618, UL Impact-/Crushing-Resistance, AD8, Dca


H1Z2Z2-K - cross-linked solar photovoltaic (PV) cable per EN 50618, UV/ Ozone resistant, burial-related UL 854 Crushing- & Impact-Resistance Test, CPR Dca, AD8

### Info

AD8 - Permanent Submersion

Burial-related UL 854 Impact- and Crushing-Resistance

Dca classified per CPR



Mechanical and plant engineering



Solar Energy



Suitable for outdoor use



Good chemical resistance



Flame-retardant



Halogen-free



Heat-resistant



Cold-resistant

Last Update (08.02.2022)

©2022 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## H1Z2Z2-K, optimized version



Corrosion-resistant



Mechanical resistance



Low weight



Robust



Acid-resistant



Voltage



Temperature-resistant



UV-resistant



Waterproof



Variety of approval certifications



### Benefits

Reduction of flame propagation and of toxic combustion gases in the event of fire

Robust against mechanical impacts

For outdoor applications

Inside the EU, and particularly on site, applicable for many building types as per local, legal implementation of EU CPR - Construction Product Regulation (EU) No. 305/2011, thanks to Dca Classification

25 years in expectable lifespan under normal use conditions as defined in EN 50618

### Application range

For free and stationary or for freely suspended outdoor and indoor cabling between the solar modules, or between the module strings and the DC/AC inverter, for example in line with HD 60364-7-712 on PV systems, and EN 50618 on H1Z2Z2-K cable type, etc....; Short circuit and earth fault protected per EN 50618, Annex A, and per HD 60364-5-52

Photovoltaic systems with DC system voltage up to 1800 V to ground

As per EN 50618, Annex A, inside electrical installation pipe/ duct/ channel, plaster, and appliance, as well as inside or connected to double insulated/ protected appliance or system of protection class II

AD8: Permanent water contact and submersion down to 1 metre in water depth

Last Update (08.02.2022)

©2022 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## H1Z2Z2-K, optimized version

Increased, mechanical robustness, for instance in the event of impact, with regard to assessed, burial based Impact-Resistance Test and Crushing-Resistance Test per UL 854

### Product features

Weather/ UV resistant per EN 50618, Annex E, as well as ozone resistant per EN 50396;  
 Transversely watertight "AD8" per IEC 60364-5-51/ HD 60364-5-51, IEC 62440, and EN 50525-2-21 down to 1 metre in water depth  
 Flame retardant per IEC 60332-1-2, and Dca classified per EU CPR - Construction Product Regulation (EU) No. 305/2011  
 Halogen-free according to IEC 60754-1 (amount of halogen acid gas),  
 Low Corrosiveness of combustion gases according to IEC 60754-2 (degree of acidity)  
 Good notch and abrasion resistance  
 Tested against burial-related, mechanical UL 854 Tests Impact-Resistance and Crushing-Resistance

### Norm references / Approvals

H1Z2Z2-K type certified according to EN 50618  
 Items with other cross-sections on request

### Product Make-up

Fine-wire, tinned-copper conductor  
 Coreinsulation made of cross-linked copolymer  
 Outer sheath made of cross-linked copolymer  
 Outer sheath colour: black, red or blue  
 Further single colours for the outer sheath on request

### Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC001578 ETIM 6.0 Class-Description: Flexible cable
Conductor stranding:	Fine wire according to VDE 0295, class 5/IEC 60228 class 5
Minimum bending radius:	4 x OD
Nominal voltage:	AC $U_0/U$ : 1.0/1.0 kV DC $U_0/U$ : 1.5/1.5 kV Max. permissible DC operating voltage: 1.8 kV
Test voltage:	AC 6500 V DC 15000 V
Current rating:	Im compliance with EN 50618, Table A.3 Acc. to EN 50618, reduction factors for clustered wiring per... HD 60364-5-52
Temperature range:	>Conductor..., max., per EN 60216-1: 120 °C; >Conductor..., max., short-circuit/ earth fault (period of max. 5 s): 250 °C; >Ambient..., min., stationary use: -40 °C; >Ambient..., min., flexible use or during installation: -25 °C; >Ambient..., max., in conjunction with EN 60216-1: 90 °C; >Ambient..., constant, in conjunction with HD 60364-7-712: 70 °C to 90 °C; >Ambient..., ambient temp. related reduction factor 1.00: 60 °C; >Ambient..., max., storage: 40 °C

## H1Z2Z2-K, optimized version

### Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)

\* Trade product, no Lapp product

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter [mm]	Copper index (kg/km)
Color of the outer jacket: Black			
1023759	1 X 4	5.5	38.4
1023760	1 X 6	6	57.6
1023761	1 X 10	7.1	96
Color of the outer jacket: Red			
1023774	1 X 4	5.5	38.4
1023775	1 X 6	6	57.6
1023776	1 X 10	7.1	96
Color of the outer jacket: Blue			
1023789	1 X 4	5.5	38.4
1023790	1 X 6	6	57.6
1023791	1 X 10	7.1	96

Last Update (08.02.2022)


©2022 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03\_16

## H1Z2Z2-K, optimized version



Last Update (08.02.2022)

©2022 Lapp Group - Technical changes reserved

Product Management [www.lappkabel.de](http://www.lappkabel.de)

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16

## H1Z2Z2-K, optimized version



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Hook-up Wire](#) category:*

*Click to view products by [Lapp Kabel](#) manufacturer:*

Other Similar products are found below :

[8918-BRN-1000](#) [8920-DK-BLU-1000](#) [CR6328-000](#) [01776.38.01](#) [M22759/16-14-5-500FT](#) [7053-RED-1000](#) [7053-SLATE-1000](#) [F25935-000](#)  
[F60898-000](#) [8055](#) [81044/12-18-9CS3209](#) [82A0811-4-9-G110](#) [83004-ORG-1000](#) [83005-LT-BLU-1000](#) [83025-VIO-1000](#) [8523-RED-100](#)  
[8524-WHT-100](#) [8525-ORG-1000](#) [8530-BLK-1000](#) [8530-LT-BLU-100](#) [8538-009-1000](#) [8597-LT-BLU-100](#) [8898-BLK-100](#) [138498-000](#)  
[E76065-000](#) [EPD50886A-20-9](#) [BFWUL3239-24-PINK](#) [C2015A.12.05](#) [C2015A.12.08](#) [C2015A.12.10](#) [C2015A.12.19](#) [C2016A.12.05](#)  
[C2016A.12.07](#) [C2065A.12.02](#) [C77653-000](#) [220368-001](#) [8916-GRY-500](#) [8918-RED-100](#) [8919-DK-BLU-1000](#) [8919-YEL-100](#) [8920-YEL-100](#)  
[9242833001](#) [933205-000](#) [2841/7-YELLOW-1000](#) [2842/7-ORANGE-100](#) [2842/7-RED-1000](#) [2843/19-BLUE-100](#) [2843/1-YELLOW-100](#)  
[2844/7-BLACK-1000](#) [2845/7-RED-100](#)