

UNITRONIC® BUS PB

Fixed installation

These bus cables can be used for PROFIBUS-DP, PROFIBUS-FMS and FIP. Available with Fast Connect and halogen-free.

Info

Lapp Kabel is a member of the PROFIBUS user organisation (PNO)

A for Advanced

here: UL and CSA certifications



UV-resistant



Halogen-free



Industrial machinery and plant engineering



Automation & fältinstallation

Application range

For fixed installation

Maximum electromagnetic screening

Dry or damp rooms

Article no. 2170233, 2170333, 2170820, 2170824, 2170826 are all UV-resistant

UNITRONIC® BUS PB

Product features

These bus cables can be used for PROFIBUS-DP as well as for PROFIBUS-FMS and FIP

Based on the bit rates listed, in accordance with PNO specifications the following maximum cable lengths for a bus segment apply

(cable type A, PROFIBUS-DP):

93.75 kbit/s = 1200 m

187.5 kbit/s = 1000 m

500 kbit/s = 400 m

1.5 Mbit/s = 200 m

12.0 Mbit/s = 100 m

Norm references / approvals

In accordance with DIN 19245 and EN 50170, e.g. for SIEMENS SIMATIC NET, also suitable for FIP (Factory Instrumentation Protocol)

See below for UL certification type

Design

FC: "Fast Connect" cable design

P: Polyurethane

H: Halogen-free

PE: Polyethylene, sheath colour, black. E.g. for the food and beverage industry.

7-W: 7-wire, e.g. for applications where vibrations occur

COMBI: Data transmission and power supply in one cable

Technical Data

Classification:	ETIM 5.0 Class-ID: EC000830 ETIM 5.0 Class-Description: Data cable
Operating capacitance:	(800 Hz): max. 30 nF/km
Peak operating voltage:	(not for power applications) 250 V
Conductor resistance:	(loop): max. 186 ohm/km. See data sheet
Minimum bending radius:	Fixed installation: see data sheet
Test voltage:	Core/Core: 1500 V eff.
Characteristic impedance:	150 ±15 ohm

UNITRONIC® BUS PB

Note

Unless otherwise specified, the product values shown are nominal values. You can receive further values, such as tolerances, upon request if they are available and have been released for publication.

Copper price basis: EUR 150/100 kg; see catalogue appendix T17 for the application and definition of "Metal price basis" and "Metal index"

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging: Ring \leq 30 kg or \leq 250 m, otherwise drum

Please specify the preferred packaging (e.g. 1 x 500 m drum or 5 x 100 m rings)

SIMATIC NET® is a registered trademark of Siemens AG

Lapp Kabel is a member of the PROFIBUS user organisation (PNO)

Photographs are not to scale and do not represent detailed images of the respective products.

* Prices are net prices without VAT and surcharges. Sale to business customers only.

Article number	Article designation	Number of pairs and conductor diameter (mm)	Outer diameter (mm)	Copper index (kg/km)
For fixed installation - conventional cable assembly				
2170220	UNITRONIC® BUS PB	1 x 2 x 0.64	8	30.1
2170233	UNITRONIC® PB PE	1 x 2 x 0.64	8	30.1
2170226	UNITRONIC® BUS PB H 7-W	1 x 2 x 0.64	8	30.1
2170225	UNITRONIC® BUS PB COMBI 7-W	1 x 2 x 0,64 Ø + 3 x 1,0 mm ²	9.8	59
For fixed installation - UL/CSA CMX certification				
2170219	UNITRONIC® BUS PB A	1 x 2 x 0.64	8	30.1
For fixed installation - UL/CSA CMG certification				
2170824	UNITRONIC® BUS PB 7-W A	1 x 2 x 0.64	8	30.1
For fixed installation - "Fast Connect" cable assembly				
2170333	UNITRONIC® BUS PB PE FC	1 x 2 x 0.64	8	26
For fixed installation - UL/CSA CMX certification				
2170330	UNITRONIC® BUS PB P FC	1 x 2 x 0.64	8	26
For fixed installation - "Fast Connect" cable assembly - UL/CSA CMG certification				
2170820	UNITRONIC® BUS PB FC	1 x 2 x 0.64	8	26
2170826	UNITRONIC® BUS PB 7-W FC	1 x 2 x 0.64	8	26
2170326	UNITRONIC® BUS PB-H FC	1 x 2 x 0.64	8	26

UNITRONIC® BUS PB



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ethernet Cables / Networking Cables](#) category:

Click to view products by [Lapp Kabel](#) manufacturer:

Other Similar products are found below :

[0152660053](#) [603020002](#) [73-7797-25](#) [73-8890-10](#) [73-8890-14](#) [73-8891-14](#) [73-8891-25](#) [73-8892-50](#) [73-8894-10](#) [73-8894-3](#) [73-8895-14](#) [73-8896-7](#) [MCJB2-10P6Q7-120](#) [84909-0204](#) [9QA0-111-12-3.00](#) [1200650742](#) [1200700174](#) [1200860368](#) [1200650013](#) [1201080008](#) [1-21919-1](#) [1300500373](#) [1300101844](#) [1300101845](#) [130050-0004](#) [1300500014](#) [1410147](#) [E16A06002M030](#) [E200102-009-S1](#) [MT14-187L](#) [17-103530](#) [NK5EPC18RDY](#) [NK5EPC18VLY](#) [NK5EPC18YLY](#) [NK5EPC1GRY](#) [NK5EPC30BLY](#) [NK5EPC30VLY](#) [NK5EPC30YLY](#) [NK5EPC4Y](#) [NK5EPC6YLY](#) [NK5EPC8BLY](#) [NK5EPC9YLY](#) [NK6PC30BUY](#) [NK6PC30GRY](#) [NK6PC30RDY](#) [NK6PC30Y](#) [NK6PC30YLY](#) [1969343-6](#) [C501100010](#) [C501106002](#)