

MOBILITY DOCK

ITEM NO.: 5555925000 | MODE 2 CHARGER, 10 A, 1-PHASE,
FOR CHARGING ELECTRIC AND HYBRID CARS



>> THE MOBILITY DOCK, 10 A, 1-PHASE MODE 2 CHARGER FROM LAPP is a mobile charging device specially designed for charging on the move. Connected to a standard household socket (Schuko), it enables electric and plug-in hybrid cars to be charged easily and safely anywhere. The existing mode 3 charging cable is effortlessly connected between the car and the MOBILITY DOCK, which is then connected to the mains power. As well as the actual charging process, the MOBILITY DOCK has a range of protection functions, including essential overcurrent and excess temperature monitoring and protection for the user.

ADVANTAGES AT A GLANCE

- Mobile charging device for use with a standard domestic power socket
- 100% user friendly and intuitive
- Compact design and ergonomic, easy handling
- Space saving storage in boot
- Charging process starts automatically when requested by the car
- Meets all relevant requirements of the product standard IEC62752
- Protection rating IP55

TECHNICAL INFORMATION

- Mode 2 charging mode in compliance with IEC 61851
- In-cable control and protection device in compliance with IEC 62752
- CE-compliant - meets all stipulations of the applicable standards
- Type E/F power connector (charging current 10A 1-phase)
- Socket for mode 3 charging cable (IEC 62196)
- Protection rating IP55 (connected IP44)
- Charging capacity up to 2.3kW, automatically adjusting
- Weight 730 g
- Dimensions (H x W x D): 255 mm x 138 mm x 106 mm
- Ambient temperature -25 °C to +45 °C

INCLUDED IN DELIVERY

- Charger with type 2 coupling and type E/F power connector (Schuko) including cap
- Operating instructions

KEY FEATURES

- Support on housing extendable using push button for support on the wall
- Easy disconnection of charging cable after completion of charging using release lever
- Use with the mode 3 charging cable already available in the car
- Gyro sensor in housing for position monitoring
- LED display in housing

SAFETY FUNCTIONS

- Self-test on start
- Residual current detection (DC) - provides effective protection against DC faults, so that upstream type A RCDs do not become blind
- Residual current detection (AC) - immediately disconnects in the event of potentially fatal AC faults
- Charge monitoring to vehicle
- Continuous protective earth
- Relay monitoring
- Overcurrent detection
- Over and undervoltage detection
- IC-CPD and power connector - Safe charging thanks to disconnection and regulation of charging capacity in case of overheating.
- Protection rating IP55 (charger), IP44 (connector/coupling)
- Halogen-free
- Flame-retardant
- Oil-resistant

ELECTRICAL DATA

- Charging capacity up to 2.3 kW
- Nominal voltage 230 V
- Nominal current 10 A, 1-phase
- Frequency 50 Hz
- Residual current device (RCD) ≤ 30 mA AC, ≤ 6 mA DC



Lapp Mobility GmbH
Stuttgart Headquarters
Oskar-Lapp-Str. 2 · D-70565 Stuttgart
Phone: +49 711 7838 - 04
Fax: +49 711 7838 - 3520
www.lappmobility.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Specialised Cables](#) category:

Click to view products by [Lapp Kabel](#) manufacturer:

Other Similar products are found below :

[706000D02F200](#) [910640](#) [96CB-L2020PIB2](#) [AC172](#) [ACL-SSI-4](#) [1300150047](#) [1300660036](#) [1302260080](#) [1300150079](#) [1300220119](#)
[1301240492](#) [1365323-1](#) [1589946-2](#) [1971465-2](#) [20240400003](#) [20886510030](#) [2-22733-8](#) [3011-03](#) [SSM005PC0DY012Q](#) [CCS-FCB-5](#)
[CCSFCBF2](#) [426122200-3](#) [VMMP6R](#) [427492400-3](#) [05AD05X](#) [10075358-F0200YYLF](#) [1052015-1-10](#) [540012](#) [RTPADPTR02](#) [636083-1](#)
[83010-0157](#) [VMMP2BK](#) [VMMP1BK](#) [ENP2205M030](#) [5-1589943-0](#) [N12601](#) [1300660038](#) [1300300020](#) [1300150101](#) [1300140041](#)
[1300660049](#) [1300300014](#) [1300150058](#) [1300150050](#) [1300150031](#) [1300140064](#) [1200900023](#) [00-4951](#) [XW2Z100JF1](#) [1200900047](#)