


64400010	<b>DATA SHEET</b>	
Valid from: 03.07.2018	<b>SILVYN® AS-P</b>	

The protection conduit SILVYN® AS-P, is a strip-wound metal conduit with hooked profile – acc. to DIN 49012, structural shape I – with PVC sheathing for the protection against environmental influences. Due to its properties the conduit SILVYN® AS-P can be used in the machine and plant construction, in electrical installations and in the automotive segment.



**Material:** Protection Conduit – Stahl-Cold strip DC 03 acc. to EN 10139, galvanized  
Conduit-Sheathing – PVC

**Feature:** Weatherproof  
Watertight  
High flexibility  
Stretch-resistant  
Compression-resistant  
Structural shape I acc. to DIN 49012, approved to DIN EN IEC 61386-23  
Free of cadmium and silicon  
Non flame propagating acc. to DIN EN IEC 61386-23

**Resistance:** Widely seawater-, acids and oil resistant

**Temperature range:** -25°C up to +80°C


**Colour:** Grey

**Norm Reference:**



**Protection class:** IP 68 acc. to EN 60529

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB64400010EN Version: 02	Page 1 of 2
---	---------------------------------------	-------------

64400010	<b>DATA SHEET</b>	
Valid from: 03.07.2018	<b>SILVYN® AS-P</b>	

**Dimension table:**

Part No.	Part name	Nominal size	Diameter mm		Bending radius mm	Weight kg/m
			Inner	Outer		
<b>SILVYN® AS-P</b>						
6440 0010	SILVYN AS-P 10 / 7x10 GY	10	7,0	10,0	95	0,085
6440 0020	SILVYN AS-P 14 / 10x14 GY	14	10,0	14,0	105	0,135
6440 0030	SILVYN AS-P 17 / 13x17 GY	17	13,0	17,0	115	0,17
6440 0040	SILVYN AS-P 19 / 15x19 GY	19	15,0	19,0	120	0,2
6440 0050	SILVYN AS-P 21 / 17x21 GY	21	17,0	21,0	110	0,22
6440 0060	SILVYN AS-P 27 / 22x27 GY	27	22,0	27,0	135	0,34
6440 0070	SILVYN AS-P 36 / 29x36 GY	36	29,0	36,0	145	0,62
6440 0080	SILVYN AS-P 45 / 38x45 GY	45	38,0	45,0	215	0,82
6440 0090	SILVYN AS-P 56 / 49x56 GY	56	49,0	56,0	205	0,97
<b>SILVYN® AS-P 10M</b>						
6440 0100	SILVYN AS-P 10 / 7x10 GY	10	7,0	10,0	95	0,085
6440 0110	SILVYN AS-P 14 / 10x14 GY	14	10,0	14,0	105	0,135
6440 0120	SILVYN AS-P 17 / 13x17 GY	17	13,0	17,0	115	0,17
6440 0130	SILVYN AS-P 19 / 15x19 GY	19	15,0	19,0	120	0,2
6440 0140	SILVYN AS-P 21 / 17x21 GY	21	17,0	21,0	110	0,22
6440 0150	SILVYN AS-P 27 / 22x27 GY	27	22,0	27,0	135	0,34
6440 0160	SILVYN AS-P 36 / 29x36 GY	36	29,0	36,0	145	0,62
6440 0170	SILVYN AS-P 45 / 38x45 GY	45	38,0	45,0	215	0,82
6440 0180	SILVYN AS-P 56 / 49x56 GY	56	49,0	56,0	205	0,97

**Suitable accessories:**

- SILVYN® MSK-M US
- SILVYN® US-M
- SILVYN® US
- SILVYN® US-AS
- SILVYN® US-EDU-AS

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB64400010EN Version: 02	Page 2 of 2
---	---------------------------------------	-------------

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Spiral Wraps, Sleeves, Tubing & Conduit](#) category:*

*Click to view products by [Lapp Kabel](#) manufacturer:*

Other Similar products are found below :

[CTA-0053](#) [8423-6](#) [8426-11](#) [8429-9](#) [25](#) [202C302-13-0](#) [RAY-103-10.0\(100\)](#) [RAY-103-4.0\(100\)](#) [4627-S](#) [5026790001](#) [100-003A1000](#) [102-060-008](#) [103-013-012](#) [5356510001](#) [8445-2.5](#) [24028-1](#) [100-001A203](#) [121-103-1-1-09BFTTH](#) [T25R-M](#) [SAS-090-1-1048-1X](#) [SAS-160-1-1030-0](#) [RAY-101-3.0\(100\)](#) [8428-18](#) [8429-12](#) [8659](#) [100-003A750](#) [100-003A109](#) [102-072-008](#) [HC1B-7008-0312-0](#) [22A00010-0DH16](#) [100-003A078](#) [OSPU 10](#) [CS-A900T](#) [THP6B](#) [121-100-1-1-20BETE](#) [330.012.2](#) [330.012.3](#) [330.016.2](#) [330.020.3](#) [373.016.2](#) [CYLG-29B](#) [61747000](#) [61806130](#) [61806140](#) [166-30730](#) [162-20100](#) [348.016.1](#) [3110000817](#) [3110014011](#) [SP-15100KN8](#)