

Bulk Cable Specification

TFSC2004 Category 5e Cable

<p>Cross-sectional View</p> <p>JACKET, BRAIDED SHIELD, ALUMINIZED POLYESTER SHIELD, POLYESTER SHIELD, TWISTED PAIR, DRAIN WIRE</p>		<p>Color Code</p> <p>P1. Blue & White / Blue P2. Orange & White / Orange P3. Green & White / Green P4. Brown & White / Brown</p>
ITEM		DESCRIPTION
Conductor	No. of Conductors	4 Pairs
	Material	Bare Copper
	Construction	24 AWG solid
Insulation	Material	Polyethylene
	Nominal Thickness	.010"
	Nominal Diameter	.040"
Shielding	Material	Aluminized Polyester Tape (insulation on inside surface)
	Coverage	100%
	Material	Polyester Tape
	Coverage	100%
Braiding	Material	Tinned Copper
	Coverage	60%
	Drain Wire	24 AWG
Jacket	Material	PVC
	Nominal Diameter	.256"
	Color	Gray (RAL7044)
Marking:		
ELECTRICAL PROPERTIES		
Conductor Resistance		Max 9.38 Ω / 100 meters @ 20°C
Insulation Resistance		500M Ω / km @ 20°C
Dielectric test		1 kVdc / 1 min

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Coaxial Cables](#) category:

Click to view products by [L-Com](#) manufacturer:

Other Similar products are found below :

[89880-003-1000](#) [9116-010-U500](#) [1322R-010-1000](#) [1807A-B59-U1000](#) [2020K8421-9X-CS3417](#) [9251-010-1000](#) [9275-010-U1000](#) [275604-000](#) [935240-000](#) [9659-010-1000](#) [980704-001](#) [CF2823-000](#) [33312-010-500](#) [CZ1589-000](#) [5022W0809-0CS3263](#) [10610-4-4](#) [EF8108-000](#) [1673B TIN100](#) [672525-001](#) [735A1-008-1000](#) [CBA-SMAM-NM1](#) [8212-010-U500](#) [8263 010U500](#) [480414-000](#) [5024A1311-0](#) [1530A 010U1000](#) [9248 010U1000](#) [1694A 0081000](#) [8241F J5C1000](#) [1674A TIN50](#) [9116SB 0101000](#) [9271 0061000](#) [1807A B591000](#) [5339Q5 009U500](#) [89207 010100](#) [C6424](#) [1369R 004500](#) [7915R 0101000](#) [M17/17600002/500](#) [132CX-06](#) [833101-000](#) [1152A-A8R-500](#) [9907-E4X-U1000](#) [3092A-X7E-500](#) [4505R-010-1000](#) [5021K1011-0](#) [LMR-500](#) [LMR-600-FR](#) [LMR-600](#) [LMR-600-DB](#)