

L-com's TRD628
Series Cables
provide high speed
connectivity for
confined space
patching
applications



Product Overview

L-com's new slim-line Ethernet patch cables are the ideal solution for high density patching applications. Our new patent pending spline-free design provides a reduced diameter profile which offers a perfect solution for applications that require a smaller and more flexible cable. Available in performance ratings of Category 6 (TRD628BL-series) and Category 6A (TRD628ABL- series), these cables support data rates up to 10Gbps for demanding high-speed voice, video and data applications.

Features

- > A 38% smaller cross sectional area and a 33% reduction in weight
- L-com's high performance RJ45 plugs with molded boots
- > 50u gold plated contacts
- Lengths: 1ft, 3ft, 5ft, 7ft, 10ft, 14ft available off-the-shelf

Applications


- High-speed Ethernet transmission
- Tight space enclosure connectivity

Challenges

- High-density patching
- Confined space patching

Solution

L-com's slim-line high performance category 6/6A cable assemblies offer a 38% smaller cross-sectional area and a tighter bend radius than standard patch cables. This improves airflow in high-density patching applications and saves space in confined areas.



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for 1-com manufacturer:

Other Similar products are found below:

FOA-550A SDRA15AG UMC-201 CSMN50MF-5 CSMNB15MF-15 TRD815RA2BL-5 CA3N050 CA3A-90DA-1M U3A00003-03M CTLF3VGAMM-20 HDCAMM-3 U3A000014-03M ECF-SK-25 CSMT15MF-10 CSMT15MM-15 CSMT15MM-25 CSPL15MF-50 CSPL25MF-25 CSPL9MF-10 CSPL9MF-5 CSPL25MF-5 CSPL25MF-2.5 AL-IPEPS NB201611-10F-1 TDG1026KC5-MNL NB121005-10F TRD855SRA6DBL-05M TRD855SRA6DBL-10M TRD855SRA7DBL-1M TRD855SRA7DBL-10M PR175SCDLCQ24 TRG508-T4T-3M TRA5261-15F TRA5261S-1F TRA6261-1F TRA6261-10F USBBFT DGB25M CASATAL-18 CSM25MM-10 CSM37MF-10 CSUSB-100 CA3A-90RA-1M CA3A-90RMICB-1M U2A00003-3M U3A00003-05M U2A00008-12I U3A00056-03M U3A00007-075M U3A00007-1M