

STRADA

The most versatile modular product family especially designed for street lighting, but also suitable for wide range of other applications

STRADA is LEDiL's most comprehensive product family with a wide variety of different beams suitable for both outdoor and indoor lighting. The standardized modules are available in 2X2 and 2X6 layouts as well as in two different single formats. 2X2MX features a standardized 90 x 90 mm footprint. The latest addition to the product family includes silicone versions for increased durability and thermal resistance. Being especially designed for street lighting they provide highly efficient and uniform lighting.


STRADA-2X2

50 x 50 mm 2X2 arrays for up to 5050 size LED packages



PRODUCTS:


C17485_STRADA-2X2-FS3-PC



Dimensions: 50.0 mm x 50.0 mm
Height: 12.00 mm

Forward throw beam optimized for European tunnels, resulting in extremely efficient lighting with counter-beam method. Variant made from PC.


C12419_STRADA-2X2-A-T



Dimensions: 50.0 mm x 50.0 mm
Height: 7.30 mm

Short IESNA Type II beam for narrow roads or high poles with extremely low glare

C13936_STRADA-2X2-B2-STP




Dimensions: 50.0 mm x 50.0 mm
Height: 5.18 mm

Beam for area lighting and applications demanding a wide oval beam pattern

PRODUCTS:


C14731_STRADA-2X2-FN-PC



Dimensions: 50.0 mm x 50.0 mm
Height: 10.00 mm

Narrow forward throw beam for area lighting. Excellent for lighting stadiums and airports from high masts. Variant made from PC.


C15540_STRADA-2X2-T3-PC



Dimensions: 50.0 mm x 50.0 mm
Height: 7.10 mm

IESNA Type III (medium) beam for roads that are equal to or wider than mounting height. Variant made from PC.


C16504_STRADA-2X2-T2-M



Dimensions: 50.0 mm x 50.0 mm
Height: 11.85 mm

IESNA Type II (medium) beam with excellent backlight control, illuminance uniformity and cutoff


C17446_STRADA-2X2-LN1



Dimensions: 50.0 mm x 50.0 mm
Height: 7.10 mm

Beam for EN13201 M-class requirements with high poles or where road width is equal or less the pole height.


C12362_STRADA-2X2-DWC



Dimensions: 50.0 mm x 50.0 mm
Height: 6.00 mm

Universal road lighting beam with excellent mixed illuminance and luminance uniformity. Typically IESNA Type III (medium).

C13858_STRADA-2X2-XW




Dimensions: 50.0 mm x 50.0 mm
Height: 7.10 mm

Extra wide beam for wide area security lighting

PRODUCTS:


C14680_STRADA-2X2-VSM



Dimensions: 50.0 mm x 50.0 mm
Height: 6.14 mm

IESNA Type V (square) beam for wide areas lighting such as car parks


C15413_STRADA-2X2-T2-PC



Dimensions: 50.0 mm x 50.0 mm
Height: 7.70 mm

IESNA Type II (medium) beam applicable for European P-class standard pedestrian lighting and M-class roads. Variant made from PC.


C16473_STRADA-2X2-SCL-PC



Dimensions: 50.0 mm x 50.0 mm
Height: 7.80 mm

Type II/III (long) beam for very wide pole to pole distances. Ideal for pedestrian paths and residential roads. EN13201 P-classes. Variant made from PC.


C17118_STRADA-2X2-T1-M



Dimensions: 50.0 mm x 50.0 mm
Height: 6.47 mm

IESNA Type I (medium) beam applicable for European P-class standard for pedestrian lighting and bicycle paths. Compatible with up to 3535 size LED packages.


C12360_STRADA-2X2-DNW



Dimensions: 50.0 mm x 50.0 mm
Height: 11.27 mm

Soft wide beam with good illuminance uniformity

C13805_STRADA-2X2-T4




Dimensions: 50.0 mm x 50.0 mm
Height: 7.70 mm

IESNA Type IV beam for wider roads and large outdoor area

PRODUCTS:


C14556_STRADA-2X2-TF



Dimensions: 50.0 mm x 50.0 mm
Height: 8.73 mm

Narrow forward throw beam optimized for European tunnels


C15292_STRADA-2X2-T2-C



Dimensions: 50.0 mm x 50.0 mm
Height: 7.34 mm

IESNA Type II (medium) beam with added house side backlight. Designed for tilted and long armatures.


C16395_STRADA-2X2-T1-PC



Dimensions: 50.0 mm x 50.0 mm
Height: 7.78 mm

Symmetric IESNA Type I (medium) beam for narrow roads and paths with long pole distance and tilted armature. Variant made from PC.


C17027_STRADA-2X2-VSM-PC



Dimensions: 50.0 mm x 50.0 mm
Height: 6.14 mm

IESNA Type V beam for wide areas such as car parks. Variant made from PC.


C13699_STRADA-2X2-DN



Dimensions: 50.0 mm x 50.0 mm
Height: 8.05 mm

Beam for area lighting with shorter illumination distances

C14517_STRADA-2X2-DWC-PC




Dimensions: 50.0 mm x 50.0 mm
Height: 6.00 mm

Universal road lighting beam with excellent mixed illuminance and luminance uniformity. Typically IESNA Type III Medium. Variant made from PC.

PRODUCTS:


C15217_STRADA-2X2-CAT-B



Dimensions: 50.0 mm x 50.0 mm
Height: 7.73 mm

Narrow catenary street light beam,
optimized for EN13201 M-classes and
tilted poles


C16378_STRADA-2X2-FR



Dimensions: 50.0 mm x 50.0 mm
Height: 11.80 mm

Asymmetric spotlight beam for
floodlighting railway tracks according to
Russian normative


C16996_STRADA-2X2-PX-PC



Dimensions: 50.0 mm x 50.0 mm
Height: 8.00 mm

Double asymmetric beam designed to
highlight pedestrian crossings for right
side traffic. Variant made from PC.


C13604_STRADA-2X2-FN



Dimensions: 50.0 mm x 50.0 mm
Height: 10.00 mm

Narrow forward throw beam for area
lighting. Excellent for lighting stadiums
and airports from high masts.


C14165_STRADA-2X2-ME-WIDE2



Dimensions: 50.0 mm x 50.0 mm
Height: 7.00 mm

Beam with excellent longitudinal
luminance uniformity for staggered pole
setups fulfilling EN13201 M-class
requirements where road width is equal
to or less than the pole height

C15135_STRADA-2X2-T1




Dimensions: 50.0 mm x 50.0 mm
Height: 7.78 mm

Symmetric IESNA Type I (medium) beam
for narrow roads and paths with long pole
distance and tilted armature

PRODUCTS:


C16181_STRADA-2X2-ME-N



Dimensions: 50.0 mm x 50.0 mm
Height: 9.70 mm

Beam designed for high poles and fulfilling EN13201 M-class requirements where road width is less than the pole height


C16927_STRADA-2X2-LW1



Dimensions: 50.0 mm x 50.0 mm
Height: 7.20 mm

Excellent longitudinal luminance uniformity for EN13201 M-class where road width is wider than the pole height.


C13499_STRADA-2X2-CY



Dimensions: 50.0 mm x 50.0 mm
Height: 5.95 mm

Beam for canopy lighting with batwing light distribution. Suitable for symmetrical tunnel lighting.


C14164_STRADA-2X2-ME-WIDE1



Dimensions: 50.0 mm x 50.0 mm
Height: 8.90 mm

Beam with excellent longitudinal luminance uniformity fulfilling EN13201 M-class requirements where road width is equal to or less than the pole height. Added house-side backlight.


C15021_STRADA-2X2-SCL



Dimensions: 50.0 mm x 50.0 mm
Height: 7.80 mm

Type II/III (long) beam for very wide pole to pole distances. Ideal for pedestrian paths and residential roads. EN13201 P-classes.

C16097_STRADA-2X2-CY-PC




Dimensions: 50.0 mm x 50.0 mm
Height: 5.95 mm

Beam for canopy lighting with batwing light distribution. Suitable for symmetrical tunnel lighting. Variant made from PC.

PRODUCTS:


C16926_STRADA-2X2-LM1



Dimensions: 50.0 mm x 50.0 mm
Height: 7.09 mm

Excellent longitudinal luminance uniformity for EN13201 M-class where road width is yhtsuur the pole height.


C13301_STRADA-2X2-T3



Dimensions: 50.0 mm x 50.0 mm
Height: 7.10 mm

IESNA Type III (medium) beam for roads that are equal to or wider than mounting height


C14116_STRADA-2X2-PX



Dimensions: 50.0 mm x 50.0 mm
Height: 8.00 mm

Fully asymmetric beam designed to highlight pedestrian crossings for right side traffic


C15014_STRADA-2X2-T4-B



Dimensions: 50.0 mm x 50.0 mm
Height: 9.02 mm

Wide IESNA Type IV forward-throw beam for wide area lighting like car parks


C15962_STRADA-2X2-FS3



Dimensions: 50.0 mm x 50.0 mm
Height: 12.00 mm

Forward throw beam optimized for European tunnels, resulting in extremely efficient lighting with counter-beam method.

C16795_STRADA-2X2-T2-M-PC




Dimensions: 50.0 mm x 50.0 mm
Height: 11.85 mm

IESNA Type II (medium) beam with excellent backlight control, illuminance uniformity and cutoff. Variant made from PC.

PRODUCTS:


C17634_STRADA-2X2-LM2



Dimensions: 50.0 mm x 50.0 mm
Height: 6.60 mm

Excellent longitudinal luminance uniformity for EN13201 M-class where road width is equal or less the pole height.


C13300_STRADA-2X2-T2



Dimensions: 50.0 mm x 50.0 mm
Height: 7.70 mm

IESNA Type II (medium) beam applicable for European P-class standard pedestrian lighting and M-class roads


C14109_STRADA-2X2-NHS



Dimensions: 50.0 mm x 50.0 mm
Height: 10.13 mm

Narrow beam with minimal house side backlight


C14896_STRADA-2X2-PXL



Dimensions: 50.0 mm x 50.0 mm
Height: 8.00 mm

Fully asymmetric beam designed to highlight pedestrian crossings for left side traffic


C15687_STRADA-2X2-FW



Dimensions: 50.0 mm x 50.0 mm
Height: 10.90 mm

Beam with wide light distribution and good illuminance uniformity for residential street lighting and staggered pole setups

C16702_STRADA-2X2-CAT-B-PC




Dimensions: 50.0 mm x 50.0 mm
Height: 7.73 mm

Narrow catenary street light beam, optimized for EN13201 M-classes and tilted poles. Variant made from PC.

PRODUCTS:


C17633_STRADA-2X2-DB



Dimensions: 50.0 mm x 50.0 mm
Height: 8.10 mm

Asymmetric beam for floodlighting the area between the railway tracks according to DB requirements.


C13299_STRADA-2X2-ME



Dimensions: 50.0 mm x 50.0 mm
Height: 7.10 mm

Beam with excellent longitudinal luminance uniformity fulfilling EN13201 M-class requirements where road width is equal to or less the pole height


C13937_STRADA-2X2-C-STP



Dimensions: 50.0 mm x 50.0 mm
Height: 5.30 mm

Beam for area and street lighting such as parks and pedestrian walkways


C14750_STRADA-2X2-CAT



Dimensions: 50.0 mm x 50.0 mm
Height: 6.20 mm

Catenary street light beam optimized for EN13201 M-classes


C15594_STRADA-2X2-MEW



Dimensions: 50.0 mm x 50.0 mm
Height: 10.16 mm

Beam with extremely low glare fulfilling EN13201 M-class requirements for wet road surfaces in North Europe

C16505_STRADA-2X2-T3-M



Dimensions: 50.0 mm x 50.0 mm
Height: 9.73 mm

IESNA Type III (medium) beam with excellent backlight control, illuminance uniformity and cutoff

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LED Lighting Lenses](#) category:

Click to view products by [Ledil](#) manufacturer:

Other Similar products are found below :

[LL01ED-AK40L06](#) [LL01ZZ-EX25L06-M2](#) [180182-0000](#) [LL01ED-ALI55R49](#) [C14707_IDA16-O](#) [C12231_LENA-FRESNEL-LENS](#)
[LL01ED-AKY24R49](#) [LL01CR-AYG15R49](#) [LL01CR-OT32L06-M2](#) [LL01ZZ-AAA24L49](#) [LL01CR-CEN38L02](#) [LL01ZZ-AAA55L49](#)
[LL01CR-AYG24R49](#) [LL01A00CZMB2-M2](#) [LL01ED-AKY38R49](#) [LL01CR-CNE2545L06-M2](#) [LL01ZZ-AAA38L49](#) [LL01ED-AKV36R49](#)
[LL01ED-ALI24R49](#) [LL01CR-AYG38R49](#) [C17171_DAISSY-8X1-SHD-MATT](#) [F16859_LINDA-ZT25](#) [C17295_ILONA-ZOOM](#)
[F16636_LINDA-W60](#) [C17362_DAISSY-7X1-W-D](#) [C17361_DAISSY-7X1-WW-D](#) [10003](#) [10003/15](#) [10048](#) [10049](#) [10108](#) [10510](#)
[F14487_FLORENCE-1R-MAXI-WG](#) [12667](#) [C14165_STRADA-2X2-ME-WIDE2](#) [C14605_HB-2X2-RW](#) [C14642_FLORENCE-1R-UP](#)
[CAY033](#) [CAY046/55](#) [FCX11157_RES-O-90](#) [OS-LRI2015X45S](#) [OSOLRA2015M](#) [PG1C-NX36](#) [PG1C-SX17](#) [PM2A-SXV1](#) [PM2B-NX55-](#)
[AW](#) [PM6A-FN25](#) [FC2231-0000-0050-L](#) [FC2231-0000-0100-L](#) [C14116_STRADA-2X2-PX](#)