

AMY-70-ZOOM-B

Infinitely adjustable beam from 20 to 50 degrees. Assembly with holder B compatible with Ø35 mm BJB and B+W connectors. Black version

SPECIFICATION:

Dimensions Ø 70.0 mm
Height 29.5 mm
ROHS compliant yes ①



MATERIALS:

ComponentTypeMaterialColourFinishC18618_AMY-70-ZOOM-SUBSingle lensPMMAclearmattCP18620_AMY-70-ZOOM-BAssembly

ORDERING INFORMATION:

Quantities for one set:

Single lens 1
Assembly 1

Published: 27/03/2023




PRODUCT DATASHEET AMY-70-ZOOM-B

Component		Qty in box	MOQ	MPQ	Box weight (kg)
C18618_AMY-70-ZOOM-SUB » Box size: 400 x 300 x 160 mm	Single lens	165		15	4.1
CP18620_AMY-70-ZOOM-B » Box size: 480 x 280 x 300 mm	Assembly	165		15	9.0



PRODUCT DATASHEET AMY-70-ZOOM-B



See also our general installation guide: www.ledil.com/installation_guide

3/4





GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405, Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Lighting Lenses category:

Click to view products by Ledil manufacturer:

Other Similar products are found below:

LL01ZZ-EX25L06-M2 C12231_LENA-FRESNEL-LENS LL01CR-OT32L06-M2 LL01CR-CEN38L02 C17295_ILONA-ZOOM

2200001315 2200001328 10003 10003/15 10048 10049 10108 10510 12667 C14165_STRADA-2X2-ME-WIDE2 C14642_FLORENCE
1R-UP CAY046/55 OS-LR12015X45S OSOLRA2015M PG1C-NX36 PM2A-SXV1 FC2231-0000-0050-L FC2231-0000-0100-L 2328823
1 C14116_STRADA-2X2-PX OPC11WIDE OPAA-1-WSL OPK2-1-003 C11916_SATU-S C15427_FLORENTINA-1-SHD-60

C15800_MOLLY-S C15802_MOLLY-W F15176_ANGELETTE-LENS F15523_LINNEA-90 C16503_STRADELLA-16-T3

F15524_LINNEA-60 10758 10192 10193 10194 10195 10196 10197 10198 10208 10209 10398 10403 10412 10414