

## EMILY-RS

~8° spot beam. 14.74 mm high lens.

### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 26.0 mm
Height	14.7 mm
Fastening	tape
ROHS compliant	yes ⓘ

### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
EMILY-RS	Single lens	PMMA	clear	
SPUTNIK-TAPE	Tape	Acrylic foam	black	

### ORDERING INFORMATION:









Component		Qty in box	MOQ	MPQ	Box weight (kg)
CA13546_EMILY-RS	Single lens	1690	260	130	10.3
» Box size: 480 x 280 x 300 mm					





See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)


#### PHOTOMETRIC DATA (MEASURED):

<p><b>CREE → LED</b></p> <p>LED XB-H            FWHM / FWTM 9.0° / 17.0°            Efficiency 88 %            Peak intensity 24.7 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>CREE → LED</b></p> <p>LED XP-G3            FWHM / FWTM 10.0° / 18.0°            Efficiency 94 %            Peak intensity 18 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>CREE → LED</b></p> <p>LED XP-L HD            FWHM / FWTM 13.0° / 23.0°            Efficiency 89 %            Peak intensity 13.1 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>CREE → LED</b></p> <p>LED XP-L HI            FWHM / FWTM 8.0° / 15.0°            Efficiency 88 %            Peak intensity 28 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		

#### PHOTOMETRIC DATA (MEASURED):


##### CREE LED

LED XP-L2  
 FWHM / FWTM 13.0° / 25.0°  
 Efficiency 93 %  
 Peak intensity 10 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





##### CREE LED

LED XQ-E HI  
 FWHM / FWTM 4.0° / 9.0°  
 Efficiency 94 %  
 Peak intensity 71.1 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




##### CREE LED

LED XT-E  
 FWHM / FWTM 8.0° / 16.0°  
 Efficiency 91 %  
 Peak intensity 23.9 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:







##### LUMILEDS


LED LUXEON Z ES  
 FWHM / FWTM 5.0° / 11.0°  
 Efficiency 91 %  
 Peak intensity 52 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### PHOTOMETRIC DATA (MEASURED):

<p><b>NICHIA</b></p> <p>LED NVSW219D            FWHM / FWTM 10.0° / 18.0°            Efficiency 94 %            Peak intensity 20.1 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSLOM Square EC            FWHM / FWTM 8.0° / 15.0°            Efficiency 90 %            Peak intensity 29.1 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED PLPVEC2 850A            FWHM / FWTM 4.0° / 11.0°            Efficiency %            LEDs/each optic 1            Light colour IR            Required components:</p>		
<p><b>SEOUL SEMICONDUCTOR</b></p> <p>LED nPola            FWHM / FWTM 5.0°            Efficiency 94 %            Peak intensity 81.2 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		


### PHOTOMETRIC DATA (MEASURED):




### PHOTOMETRIC DATA (SIMULATED):




LED XHP35 HI  
 FWHM / FWTM 10.0° / 18.0°  
 Efficiency 96 %  
 Peak intensity 22 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




LED XP-E2  
 FWHM / FWTM 6.0° / 14.0°  
 Efficiency 94 %  
 Peak intensity 51.8 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED XP-G2  
 FWHM / FWTM 8.0° / 16.0°  
 Efficiency 94 %  
 Peak intensity 30.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED XP-G2 HE  
 FWHM / FWTM 10.0° / 20.0°  
 Efficiency 95 %  
 Peak intensity 19.1 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### PHOTOMETRIC DATA (SIMULATED):

<p><b>CREE</b> LED</p> <p>LED: XP-P            FWHM / FWTM: 6.0° / 12.0°            Efficiency: 96 %            Peak intensity: 63.8 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	
<p><b>LUMILEDS</b></p> <p>LED: LUXEON C            FWHM / FWTM: 7.0° / 16.0°            Efficiency: 94 %            Peak intensity: 37.3 cd/lm            LEDs/each optic: 1            Light colour: Royal Blue            Required components:</p>	
<p><b>LUMILEDS</b></p> <p>LED: LUXEON MZ            FWHM / FWTM: 14.0° / 26.0°            Efficiency: 95 %            Peak intensity: 10.7 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	
<p><b>LUMILEDS</b></p> <p>LED: LUXEON Rebel            FWHM / FWTM: 6.0° / 14.0°            Efficiency: 94 %            Peak intensity: 41.5 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	



#### PHOTOMETRIC DATA (SIMULATED):

<p><b>LUMILEDS</b></p> <p>LED: LUXEON Rebel Plus</p> <p>FWHM / FWTM: 6.0° / 14.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 42.1 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p><b>LUMILEDS</b></p> <p>LED: LUXEON Rubix (white)</p> <p>FWHM / FWTM: 6.0° / 12.0°</p> <p>Efficiency: 96 %</p> <p>Peak intensity: 62.6 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p><b>LUMILEDS</b></p> <p>LED: LUXEON Z</p> <p>FWHM / FWTM: 5.9° / 12.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 65.3 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p><b>NICHIA</b></p> <p>LED: NCSxE17A</p> <p>FWHM / FWTM: 6.0° / 16.0°</p> <p>Efficiency: 93 %</p> <p>Peak intensity: 35.5 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	

#### PHOTOMETRIC DATA (SIMULATED):

<p><b>NICHIA</b></p> <p>LED: NCSxE17A            FWHM / FWTM: 8.0° / 16.0°            Efficiency: 92 %            Peak intensity: 32.5 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	
<p><b>NICHIA</b></p> <p>LED: NCSxE17A            FWHM / FWTM: 18.0° / 35.0°            Efficiency: 91 %            Peak intensity: 5.8 cd/lm            LEDs/each optic: 3            Light colour: White            Required components:</p>	
<p><b>NICHIA</b></p> <p>LED: NVSW3x9A            FWHM / FWTM: 12.0° / 22.0°            Efficiency: 95 %            Peak intensity: 16.3 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	
<p><b>NICHIA</b></p> <p>LED: NVSxE21A            FWHM / FWTM: 8.0° / 18.0°            Efficiency: 94 %            Peak intensity: 27.8 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	

#### PHOTOMETRIC DATA (SIMULATED):

<p><b>NICHIA</b></p> <p>LED NVSxE21A            FWHM / FWTM 8.0° / 18.0°            Efficiency 93 %            Peak intensity 26.2 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED Duris S5 (Single chip)            FWHM / FWTM 9.0° / 18.0°            Efficiency 89 %            Peak intensity 23.2 cd/lm            LEDs/each optic 1            Light colour Purple            Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED Duris S5 (Single chip)            FWHM / FWTM 8.0° / 18.0°            Efficiency 96 %            Peak intensity 25.4 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSCONIQ C 2424            FWHM / FWTM 8.0° / 16.0°            Efficiency 96 %            Peak intensity 36.2 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	





#### PHOTOMETRIC DATA (SIMULATED):

<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSCONIQ P 3030</p> <p>FWHM / FWTM 10.0° / 20.0°</p> <p>Efficiency 96 %</p> <p>Peak intensity 20.8 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSLOK Black</p> <p>FWHM / FWTM 11.0° / 20.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 19.7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSLOK Black Flat</p> <p>FWHM / FWTM 6.3° / 14.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 50.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSLOK PURE 1010 (GW VJLPE1)</p> <p>FWHM / FWTM 8.0° / 16.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 29.8 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	

#### PHOTOMETRIC DATA (SIMULATED):

<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSLOM Square CSSRM2/CSSRM3</p> <p>FWHM / FWTM 11.0° / 21.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 19.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSLOM SSL 120</p> <p>FWHM / FWTM 7.0° / 14.0°</p> <p>Efficiency 96 %</p> <p>Peak intensity 45.5 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour Amber</p> <p>Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSLOM SSL 150</p> <p>FWHM / FWTM 7.0° / 14.0°</p> <p>Efficiency 96 %</p> <p>Peak intensity 44.5 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour Amber</p> <p>Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSLOM SSL 150</p> <p>FWHM / FWTM 6.0° / 14.0°</p> <p>Efficiency 96 %</p> <p>Peak intensity 47.7 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	


### PHOTOMETRIC DATA (SIMULATED):

<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED: OSLOM SSL 80</p> <p>FWHM / FWTM: 7.0° / 14.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 38 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED: SFH 4170S</p> <p>FWHM / FWTM: 6.0° / 11.0°</p> <p>Efficiency: 87 %</p> <p>LEDs/each optic: 1</p> <p>Light colour: IR</p> <p>Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED: SFH 4716AS</p> <p>FWHM / FWTM: 8.0° / 14.0°</p> <p>Efficiency: 96 %</p> <p>LEDs/each optic: 1</p> <p>Light colour: IR</p> <p>Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED: SFH 4725AS</p> <p>FWHM / FWTM: 8.0° / 18.0°</p> <p>Efficiency: 95 %</p> <p>LEDs/each optic: 1</p> <p>Light colour: IR</p> <p>Required components:</p>	

### PHOTOMETRIC DATA (SIMULATED):

#### SAMSUNG

LED	LM301B
FWHM / FWTM	9.0° / 18.0°
Efficiency	94 %
Peak intensity	28.5 cd/lm
LEDs/each optic	1
Light colour	White
Required components:	



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Lighting Lenses Assemblies](#) category:*

*Click to view products by [Ledil](#) manufacturer:*

Other Similar products are found below :

[FCN12592\\_LE1-D-COP](#) [CA16129\\_OLGA-W](#) [CA16370\\_HB-SQ-W](#) [FN15972\\_RONDA-ZT45-C](#) [CS15759\\_HB-2X2MX-8-W](#)  
[CA16435\\_LXP2-SS-WAS](#) [CN16210\\_GABRIELLA-MIDI-W](#) [CP17137\\_CARMEN-M2-C](#) [CA16015\\_STRADA-SQ-SCL](#) [CP17594\\_TINA-SC-](#)  
[RS](#) [CS15767\\_HB-2X2MX-8-M](#) [CP10960\\_RGBX-SS](#) [CP12395\\_LXP3-W](#) [CP12939\\_LARISA-RS-CLIP16](#) [C14636\\_XTM-PF-ADAPTER](#)  
[CA11819\\_STRADA-SQ-T-DW](#) [CA14508\\_G2-LXP2-D](#) [CA14601\\_VERONICA-SQ-MINI-RS](#) [FCP13895\\_SEANNA-A](#) [CP12943\\_LARISA-](#)  
[O-CLIP16](#) [FP11124\\_LISA2-O-PIN](#) [CS14597\\_HB-IP-2X6-O](#) [CP14995\\_FLORENTINA-HLD-O](#) [CS15158\\_STRADA-IP-2X6-T4-B](#)  
[CS16323\\_STRADELLA-IP-28-HB-M](#) [FN14976\\_STELLA-DWC2](#) [FN15264\\_STELLA-HB-WWW](#) [CA15584\\_ZORYA-MINI-TAPE](#)  
[FA15229\\_ROSE-MRK-S](#) [FA15232\\_ROSE-MRK-M](#) [FA15233\\_ROSE-MRK-W](#) [FCN13552\\_CRYSTAL-RS](#) [FN15552\\_RONDA-W](#)  
[FS15626\\_FLORENCE-3R-IP-Z90](#) [FS15786\\_FLORENCE-3R-IP-Z60](#) [FS15847\\_FLORENCE-3R-IP-O](#) [CA14505\\_G2-LXP2-RS2-P](#)  
[FCN12775\\_IRIS-O](#) [CP15304\\_LARISA-RS-PIN](#) [FN15679\\_RONDA-S](#) [CA15519\\_VERONICA-SQ-MINI-D](#) [FP14414\\_LISA2-O-PIN](#)  
[LL01CR-DF60L06-M2](#) [FN15993\\_RONDA-O](#) [FN15977\\_RONDA-WAS2](#) [CA14366\\_FLARE-MAXI-TAPE](#) [CA14442\\_VERONICA-SQ-W](#)  
[CA14509\\_G2-LXP2-M-P](#) [CA15231\\_VERONICA-SQ-MINI-W](#) [FP11002\\_LISA2-W-PIN](#)