

### **HB-SQ-W**

~60° beam. Assembly with installation tape.

#### **TECHNICAL SPECIFICATIONS:**

Dimensions 25.0 mm
Height 10 mm
Fastening tape, pin
ROHS compliant yes 1

#### **MATERIAL SPECIFICATIONS:**

ComponentTypeHB-SQ-WSingle lensROSE-TAPETape



MaterialColourPMMAclearPU tapeblack

### **ORDERING INFORMATION:**


Component Qty in box MOQ MPQ Box weight (kg)

CA16370\_HB-SQ-W Single lens 2058 294 98 8.6

» Box size: 480 x 280 x 300 mm


**Finish** 







### PHOTOMETRIC DATA (MEASURED):




### PHOTOMETRIC DATA (SIMULATED):

# CREE \$

LED XHP50.2 FWHM 55.0° Efficiency 95 %

Peak intensity 0.9 cd/lm LEDs/each optic 1
Light colour White

Required components:




## CREE 💠

LED XHP70 FWHM 54.0°

Efficiency 92 %
Peak intensity 1.1 cd/lm

LEDs/each optic 1
Light colour White


Required components:



## CREE 🕏

LED XHP70.2 FWHM 61.0° Efficiency 91 % Peak intensity 0.9 cd/lm

LEDs/each optic 1
Light colour White
Required components:




### **DESCRIPTION** LUMILEDS

Required components:

LED LUXEON 5050 Round LES

FWHM 49.0°
Efficiency 94 %
Peak intensity 1.3 cd/lm
LEDs/each optic 1
Light colour White




### PHOTOMETRIC DATA (SIMULATED):



LED LUXEON M/MX

**FWHM** 51.0° Efficiency 93 % Peak intensity 1.1 cd/lm LEDs/each optic Light colour White




#### **MUMILEDS**

Required components:

LED LUXEON MZ

**FWHM** 46.0° 96 % Efficiency Peak intensity 1.3 cd/lm LEDs/each optic 1


White Light colour Required components:



#### **WNICHIA**

LED NV4x144A **FWHM** 57.0° Efficiency 93 % Peak intensity 0.9 cd/lm


LEDs/each optic Light colour White Required components:



## OSRAM Opto Semiconductors

LED Duris S10 **FWHM** 45.0° Efficiency 96 % Peak intensity 1.4 cd/lm LEDs/each optic White

Light colour Required components:






## PHOTOMETRIC DATA (SIMULATED):

OSRAM Opto Semiconductors

LED OSCONIQ P 7070

FWHM 52.0°
Efficiency 93 %
Peak intensity 1.2 cd/lm
LEDs/each optic 1

Light colour White Required components:





#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

www.ledil.com/ where\_to\_buy

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Lighting Lenses Assemblies category:

Click to view products by Ledil manufacturer:

Other Similar products are found below:

FCN12592\_LEI-D-COP\_CA11362\_IRIS\_CA16127\_OLGA-S\_CP16107\_CARMEN-50-S-C\_CS15763\_STRADA-2X2MX-8-VSM
C17171\_DAISY-8X1-SHD-MATT\_C17172\_DAISY-8X1-SHD-MATT-WHT\_C17173\_DAISY-4X1-WW-US\_C17341\_DAISY-4X1-WW-US\_D\_CS15759\_HB-2X2MX-8-W\_CS15769\_STRADA-2X2MX-8-T2-S\_CA16435\_LXP2-SS-WAS\_CS13756\_STRADA-IP-2X6-DWC-PC\_CN16210\_GABRIELLA-MIDI-W\_CP17138\_CARMEN-M2-C-WHT\_CP17137\_CARMEN-M2-C\_CA16015\_STRADA-SQ-SCL\_C16989\_DAISY-7X1-W2\_C17225\_DAISY-7X1-SHD-WHT-MATT\_C17296\_ILONA-ZOOM-SUB\_FP15752\_STRADA-2X2MXS-T3\_C16590\_DAISY-4X1-SHD\_FP16562\_LISA3-WWW-PIN\_CX15819\_GABRIELLA-45-W\_C16870\_DAISY-7X1-WW\_CP12939\_LARISA-RS-CLIP16\_C14636\_XTM-PF-ADAPTER\_CA14506\_G2-LXP2-RS2\_CA14508\_G2-LXP2-D\_FCP13895\_SEANNA-A\_FN14637\_OLIVIA-S\_CP12943\_LARISA-O-CLIP16\_FP11124\_LISA2-O-PIN\_CP10444\_LISA-SS\_CS14597\_HB-IP-2X6-O\_CP14995\_FLORENTINA-HLD-O\_CA16128\_OLGA-M\_CP14994\_FLORENTINA-HLD-M\_CP15775\_CARMEN-M-C\_CS15158\_STRADA-IP-2X6-T4-B\_CS15363\_STRADA-IP-2X6-T2-B\_CS15751\_STRADA-2X2MX-8-DWC\_CS15886\_STRADA-IP-2X6-T2-B-90\_CS16323\_STRADELLA-IP-28-HB-M\_FN14976\_STELLA-DWC2\_FN15264\_STELLA-HB-WWW\_FN15966\_RONDA-WWW-C\_FN15971\_RONDA-WAS-C\_FP15073\_ZORYA-SC-B\_CA15584\_ZORYA-MINI-TAPE