

### **HB-SQ-WWW**

~90° beam. Assembly with installation tape.

#### **TECHNICAL SPECIFICATIONS:**

Dimensions 25.0 mm
Height 10 mm
Fastening tape, pin
ROHS compliant yes 1

#### **MATERIAL SPECIFICATIONS:**

ComponentTypeMaterialColourHB-SQ-WWWSingle lensPMMAclearROSE-TAPETapePU tapeblack

### **ORDERING INFORMATION:**


Component Qty in box MOQ MPQ Box weight (kg)

**LEDiL**<sup>®</sup>

CA16372\_HB-SQ-WWW Single lens 2058 294 98 8.9 » Box size: 480 x 280 x 300 mm


**Finish** 







### PHOTOMETRIC DATA (MEASURED):






### PHOTOMETRIC DATA (SIMULATED):

bridgelux


LED Bridgelux SMD 5050

FWHM 77.0°
Efficiency 93 %
Peak intensity 0.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:



### CREE 🕏

LED MHD-E/G
FWHM 85.5°
Efficiency 91 %
Peak intensity 0.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:




## CREE 🕏

LED XHP50.2
FWHM 86.0°
Efficiency 93 %
Peak intensity 0.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:



LED XHP70
FWHM 83.0°
Efficiency 89 %
Peak intensity 0.5 cd/lm
LEDs/each optic 1
Light colour White
Required components:



### PHOTOMETRIC DATA (SIMULATED):

## CREE 💠

LED XHP70.2
FWHM 85.0°
Efficiency 86 %
Peak intensity 0.4 cd/lm
LEDs/each optic 1
Light colour White


### **MUMILEDS**

Required components:

LED LUXEON M/MX

FWHM 80.0°
Efficiency 90 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1

Light colour White Required components:




### **MUMILEDS**

LED LUXEON M/MX

FWHM 88.0°
Efficiency 86 %
Peak intensity 0.4 cd/lm
LEDs/each optic 1
Light colour White

Transparent protective cover




### **DESCRIPTION** LUMILEDS

Required components:


LED LUXEON MZ FWHM 77.0°

Efficiency 94 %
Peak intensity 0.6 cd/lm
LEDs/each optic 1

Light colour White Required components:



### PHOTOMETRIC DATA (SIMULATED):





#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

www.ledil.com/ where\_to\_buy

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Lighting Lenses Assemblies category:

Click to view products by Ledil manufacturer:

Other Similar products are found below:

FCN12592\_LEI-D-COP\_CA11362\_IRIS\_CA16127\_OLGA-S\_CP16107\_CARMEN-50-S-C\_CS15763\_STRADA-2X2MX-8-VSM
C17171\_DAISY-8X1-SHD-MATT\_C17172\_DAISY-8X1-SHD-MATT-WHT\_C17173\_DAISY-4X1-WW-US\_C17341\_DAISY-4X1-WW-US\_D\_CS15759\_HB-2X2MX-8-W\_CS15769\_STRADA-2X2MX-8-T2-S\_CA16435\_LXP2-SS-WAS\_CS13756\_STRADA-IP-2X6-DWC-PC\_CN16210\_GABRIELLA-MIDI-W\_CP17138\_CARMEN-M2-C-WHT\_CP17137\_CARMEN-M2-C\_CA16015\_STRADA-SQ-SCL\_C16989\_DAISY-7X1-W2\_C17225\_DAISY-7X1-SHD-WHT-MATT\_C17296\_ILONA-ZOOM-SUB\_FP15752\_STRADA-2X2MXS-T3\_C16590\_DAISY-4X1-SHD\_FP16562\_LISA3-WWW-PIN\_CX15819\_GABRIELLA-45-W\_C16870\_DAISY-7X1-WW\_CP12939\_LARISA-RS-CLIP16\_C14636\_XTM-PF-ADAPTER\_CA14506\_G2-LXP2-RS2\_CA14508\_G2-LXP2-D\_FCP13895\_SEANNA-A\_FN14637\_OLIVIA-S\_CP12943\_LARISA-O-CLIP16\_FP11124\_LISA2-O-PIN\_CP10444\_LISA-SS\_CS14597\_HB-IP-2X6-O\_CP14995\_FLORENTINA-HLD-O\_CA16128\_OLGA-M\_CP14994\_FLORENTINA-HLD-M\_CP15775\_CARMEN-M-C\_CS15158\_STRADA-IP-2X6-T4-B\_CS15363\_STRADA-IP-2X6-T2-B\_CS15751\_STRADA-2X2MX-8-DWC\_CS15886\_STRADA-IP-2X6-T2-B-90\_CS16323\_STRADELLA-IP-28-HB-M\_FN14976\_STELLA-DWC2\_FN15264\_STELLA-HB-WWW\_FN15966\_RONDA-WWW-C\_FN15971\_RONDA-WAS-C\_FP15073\_ZORYA-SC-B\_CA15584\_ZORYA-MINI-TAPE