

## HB-IP-2X6-WWW

~100° wide beam

### TECHNICAL SPECIFICATIONS:

Dimensions	71.4 x 173.0 mm
Height	11.4 mm
Fastening	screw
Ingress protection classes	IP67
ROHS compliant	yes ⓘ


### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
HB-IP-2X6-WWW	Multi-lens	PMMA	clear	
2X6-SEAL25	Seal	Silicone	white	











### ORDERING INFORMATION:

Component	Type	Qty in box	MOQ	MPQ	Box weight (kg)
CS14263_HB-IP-2X6-WWW » Box size: 476 x 273 x 247 mm	Multi-lens	120	40	40	8.3











See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)









### PHOTOMETRIC DATA (MEASURED):

<p><b>COMET ELECTRONICS</b></p> <p>LED QUICK FLUX 2x6 LED XG xxx G7+</p> <p>FWHM / FWTM 100.0° / 133.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 0.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>COMET ELECTRONICS</b></p> <p>LED QUICK FLUX 2x6 LED XT xxx G5</p> <p>FWHM / FWTM 96.0° / 128.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 0.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>CREE LED</b></p> <p>LED XM-L2</p> <p>FWHM / FWTM 97.0° / 132.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 0.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>CREE LED</b></p> <p>LED XP-G2</p> <p>FWHM / FWTM 95.0° / 132.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 0.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		

#### PHOTOMETRIC DATA (MEASURED):

<p><b>CREE</b> ⇄ <b>LED</b></p> <p>LED            XP-L HD            FWHM / FWTM    103.0° / 138.0°            Efficiency        92 %            Peak intensity    0.4 cd/lm            LEDs/each optic    1            Light colour        White            Required components:</p>		
<p><b>CREE</b> ⇄ <b>LED</b></p> <p>LED            XP-L2            FWHM / FWTM    96.0° / 134.0°            Efficiency        94 %            Peak intensity    0.4 cd/lm            LEDs/each optic    1            Light colour        White            Required components:</p>		
<p><b>CREE</b> ⇄ <b>LED</b></p> <p>LED            XT-E            FWHM / FWTM    98.0° / 130.0°            Efficiency        94 %            Peak intensity    0.4 cd/lm            LEDs/each optic    1            Light colour        White            Required components:</p>		
<p><b>CREE</b> ⇄ <b>LED</b></p> <p>LED            XT-E HE            FWHM / FWTM    95.0° / 129.0°            Efficiency        94 %            Peak intensity    0.4 cd/lm            LEDs/each optic    1            Light colour        White            Required components:</p>		



#### PHOTOMETRIC DATA (MEASURED):

<p><b>LUMILEDS</b></p> <p>LED LUXEON T</p> <p>FWHM / FWTM 91.0° / 129.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 0.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>LUMILEDS</b></p> <p>LED LUXEON TX</p> <p>FWHM / FWTM 95.0° / 133.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 0.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>LUMILEDS</b></p> <p>LED LUXEON V</p> <p>FWHM / FWTM 94.0° / 130.0°</p> <p>Efficiency 92 %</p> <p>Peak intensity 0.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>LUMILEDS</b></p> <p>LED LUXEON V2</p> <p>FWHM / FWTM 91.0° / 129.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 0.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		

#### PHOTOMETRIC DATA (MEASURED):



##### LUMILEDS

LED LUXEON XR-TX (L2T0-xyyy012M)  
 FWHM / FWTM 97.0° / 135.0°  
 Efficiency 93 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




##### LUMILEDS

LED LUXEON Z ES  
 FWHM / FWTM 85.0° / 124.0°  
 Efficiency 93 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





##### LUMINUS

LED SST-10-B130  
 FWHM / FWTM 96.0° / 124.0°  
 Efficiency 95 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour Deep Red  
 Required components:



##### *Your solutions*



LED RecLED 146x45mm 2900lm 730 STRADA-IP-2x6 G1  
 FWHM / FWTM 91.5° / 129.0°  
 Efficiency 93 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### PHOTOMETRIC DATA (MEASURED):





LED NVSW219D  
 FWHM / FWTM 98.0° / 132.0°  
 Efficiency 93 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





LED NVSW319B  
 FWHM / FWTM 103.0° / 136.0°  
 Efficiency 94 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED NVSW3x9A  
 FWHM / FWTM 97.0° / 133.0°  
 Efficiency 93 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





LED NVSW519A  
 FWHM / FWTM 100.0° / 126.0°  
 Efficiency 95 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### PHOTOMETRIC DATA (MEASURED):





LED NVSx21A  
 FWHM / FWTM 84.0° / 120.0°  
 Efficiency 94 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





LED NVSxx19B/NVSxx19C  
 FWHM / FWTM 90.0° / 129.0°  
 Efficiency 94 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED Duris S8  
 FWHM / FWTM 90.0° / 124.0°  
 Efficiency 94 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED OSLON Square CSSRM2/CSSRM3  
 FWHM / FWTM 97.0° / 135.0°  
 Efficiency 94 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:






### PHOTOMETRIC DATA (MEASURED):

#### OSRAM

Opto Semiconductors



LED OSLON Square PC  
 FWHM / FWTM 95.0° / 130.0°  
 Efficiency 92 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### OSRAM



Opto Semiconductors

LED OSLON SSL 80  
 FWHM / FWTM 76.0° / 123.0°  
 Efficiency 94 %  
 Peak intensity 0.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





#### PHILIPS

LED Fortimo FastFlex LED 2x6 DP G4  
 FWHM / FWTM 95.0° / 132.0°  
 Efficiency 93 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHILIPS



LED Fortimo FastFlex LED 2x6 DP G5  
 FWHM / FWTM 96.0° / 125.0°  
 Efficiency 95 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### PHOTOMETRIC DATA (MEASURED):


#### PHILIPS

LED Fortimo FastFlex LED 2x6 DP HE  
 FWHM / FWTM 93.0° / 122.0°  
 Efficiency 97 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





#### SAMSUNG

LED HiLOM RH12 (LH351C)  
 FWHM / FWTM 94.0° / 130.0°  
 Efficiency 93 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### SAMSUNG

LED HiLOM RM12 ZP (LH502C)  
 FWHM / FWTM 92.0° / 122.0°  
 Efficiency 96 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:











#### SCIOLUX









LED XLE-S22C4XTEHE (XT-E HE)  
 FWHM / FWTM 95.0° / 129.0°  
 Efficiency 94 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (MEASURED):

<p><b>SCIOLUX</b></p> <p>LED XLE-S26XHP35 (XHP35 HD)</p> <p>FWHM / FWTM 104.0° / 139.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 0.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>SEOUL SEMICONDUCTOR</b></p> <p>LED 2x6 5050 module - SMJD-3625012F-XX</p> <p>FWHM / FWTM 88.0° / 125.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 0.5 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>SEOUL SEMICONDUCTOR</b></p> <p>LED SMJQ-D36W12Mx</p> <p>FWHM / FWTM 79.0° / 123.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 0.5 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>SEOUL SEMICONDUCTOR</b></p> <p>LED SMJQ-D36W12Px</p> <p>FWHM / FWTM 96.0° / 131.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 0.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		

#### PHOTOMETRIC DATA (MEASURED):


<p><b>SEOUL SEMICONDUCTOR</b></p> <p>LED Z5M1/Z5M2</p> <p>FWHM / FWTM 97.0° / 135.0°</p> <p>Efficiency 92 %</p> <p>Peak intensity 0.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>SEOUL SEMICONDUCTOR</b></p> <p>LED Z5M3</p> <p>FWHM / FWTM 93.0° / 128.0°</p> <p>Efficiency 95 %</p> <p>Peak intensity 0.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>SEOUL SEMICONDUCTOR</b></p> <p>LED Z8Y22</p> <p>FWHM / FWTM 79.0° / 123.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 0.5 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p><b>SEOUL SEMICONDUCTOR</b></p> <p>LED Z8Y22P</p> <p>FWHM / FWTM 92.0° / 128.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 0.4 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		

### PHOTOMETRIC DATA (MEASURED):

#### TOSHIBA


Leading Innovation >>>

LED TL1L4  
FWHM / FWTM 95.0° / 131.0°  
Efficiency 94 %  
Peak intensity 0.4 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:



#### TRIDONIC


LED RLE 2x6 3000lm HP EXC2 OTD  
FWHM / FWTM 94.0° / 130.0°  
Efficiency 94 %  
Peak intensity 0.4 cd/lm  
LEDs/each optic 1  
Light colour White  
Required components:




#### PHOTOMETRIC DATA (SIMULATED):




LED J Series 5050 Round LES  
 FWHM / FWTM 98.0° / 130.0°  
 Efficiency 94 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




LED J Series 5050 Square LES  
 FWHM / FWTM 94.0° / 123.0°  
 Efficiency 96 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED MHB-A/B  
 FWHM / FWTM 106.0° / 131.0°  
 Efficiency 87 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



LED XHP35 HD  
 FWHM / FWTM 101.0° / 129.0°  
 Efficiency 91 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (SIMULATED):


<p><b>CREE</b> LED</p> <p>LED: XP-E            FWHM / FWTM: 99.0° / 129.0°            Efficiency: 94 %            Peak intensity: 0.4 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	
<p><b>CREE</b> LED</p> <p>LED: XP-G2 HE            FWHM / FWTM: 108.0° / 140.0°            Efficiency: 93 %            Peak intensity: 0.3 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	
<p><b>CREE</b> LED</p> <p>LED: XP-G3            FWHM / FWTM: 95.0° / 145.0°            Efficiency: 91 %            Peak intensity: 0.4 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	
<p><b>LUMILEDS</b></p> <p>LED: LUXEON 5050 Round LES            FWHM / FWTM: 92.0° / 125.0°            Efficiency: 93 %            Peak intensity: 0.4 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	

### PHOTOMETRIC DATA (SIMULATED):

#### LUMILEDS

LED LUXEON 5050 Round LES  
 FWHM / FWTM 98.0° / 130.0°  
 Efficiency 90 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:

Protective plate, glass




#### LUMILEDS

LED LUXEON 5050 Square LES  
 FWHM / FWTM 90.0° / 122.0°  
 Efficiency 96 %  
 Peak intensity 0.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:


#### NICHIA

LED NV4WB35AM  
 FWHM / FWTM 98.0° / 123.0°  
 Efficiency 96 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:







#### NICHIA

LED NVSW219F  
 FWHM / FWTM 110.0° / 132.0°  
 Efficiency 92 %  
 Peak intensity 0.3 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





#### PHOTOMETRIC DATA (SIMULATED):


<p><b>NICHIA</b></p> <p>LED: NVSxE21A            FWHM / FWTM: 94.0° / 122.0°            Efficiency: 95 %            Peak intensity: 0.4 cd/lm            LEDs/each optic: 4            Light colour: White            Required components:</p>	
<p><b>OSRAM</b></p> <p>LED: PrevaLED Brick HP IP 2x6            FWHM / FWTM: 98.0° / 124.0°            Efficiency: 96 %            Peak intensity: 0.4 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	
<p><b>OSRAM</b>  <small>Opto Semiconductors</small></p> <p>LED: OSCONIQ P 3030            FWHM / FWTM: 94.0° / 126.0°            Efficiency: 96 %            Peak intensity: 0.4 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	
<p><b>OSRAM</b>  <small>Opto Semiconductors</small></p> <p>LED: OSCONIQ P 3737 (2W version)            FWHM / FWTM: 95.0° / 127.0°            Efficiency: 94 %            Peak intensity: 0.4 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	

### PHOTOMETRIC DATA (SIMULATED):

#### OSRAM

Opto Semiconductors


LED OSCONIQ P 3737 (3W version)  
 FWHM / FWTM 98.0° / 127.0°  
 Efficiency 94 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### OSRAM


Opto Semiconductors

LED OSCONIQ P 3737 Flat  
 FWHM / FWTM 94.0° / 126.0°  
 Efficiency 96 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### PHILIPS

LED Fortimo FastFlex LED 2x6 DPX G4  
 FWHM / FWTM 105.0° / 92.0°  
 Efficiency 94 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### SAMSUNG


LED LH181B  
 FWHM / FWTM 90.0° / 124.0°  
 Efficiency 96 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### PHOTOMETRIC DATA (SIMULATED):


#### SAMSUNG

LED LH351B  
 FWHM / FWTM 100.0° / 130.0°  
 Efficiency 94 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### SAMSUNG

LED LH351D  
 FWHM / FWTM 107.0° / 145.0°  
 Efficiency 92 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### SAMSUNG

LED LH502C  
 FWHM / FWTM 96.0° / 124.0°  
 Efficiency 96 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:







SEOUL SEMICONDUCTOR

LED Z5M4  
 FWHM / FWTM 94.0° / 125.0°  
 Efficiency 96 %  
 Peak intensity 0.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



**PHOTOMETRIC DATA (SIMULATED):**

<p> <b>SEOUL SEMICONDUCTOR</b></p> <p>LED: Z8Y22T            FWHM / FWTM: 93.0° / 131.0°            Efficiency: 94 %            Peak intensity: 0.5 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	
<p><b>TOSHIBA</b> Leading Innovation &gt;&gt;&gt;</p> <p>LED: TL1L2            FWHM / FWTM: 100.0° / 125.0°            Efficiency: 91 %            Peak intensity: 0.4 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	
<p><b>TOSHIBA</b> Leading Innovation &gt;&gt;&gt;</p> <p>LED: TL1L3            FWHM / FWTM: Asymmetric            Efficiency: 84 %            Peak intensity: 0.5 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>	

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Lighting Lenses Assemblies](#) category:*

*Click to view products by [Ledil](#) manufacturer:*

Other Similar products are found below :

[FCN12592\\_LE1-D-COP](#) [CA16129\\_OLGA-W](#) [CA16370\\_HB-SQ-W](#) [FN15972\\_RONDA-ZT45-C](#) [CS15759\\_HB-2X2MX-8-W](#)  
[CA16435\\_LXP2-SS-WAS](#) [CN16210\\_GABRIELLA-MIDI-W](#) [CP17137\\_CARMEN-M2-C](#) [CA16015\\_STRADA-SQ-SCL](#) [CP17594\\_TINA-SC-](#)  
[RS](#) [CS15767\\_HB-2X2MX-8-M](#) [CP10960\\_RGBX-SS](#) [CP12395\\_LXP3-W](#) [CP12939\\_LARISA-RS-CLIP16](#) [C14636\\_XTM-PF-ADAPTER](#)  
[CA11819\\_STRADA-SQ-T-DW](#) [CA14508\\_G2-LXP2-D](#) [CA14601\\_VERONICA-SQ-MINI-RS](#) [FCP13895\\_SEANNA-A](#) [CP12943\\_LARISA-](#)  
[O-CLIP16](#) [FP11124\\_LISA2-O-PIN](#) [CS14597\\_HB-IP-2X6-O](#) [CP14995\\_FLORENTINA-HLD-O](#) [CS15158\\_STRADA-IP-2X6-T4-B](#)  
[CS16323\\_STRADELLA-IP-28-HB-M](#) [FN14976\\_STELLA-DWC2](#) [FN15264\\_STELLA-HB-WWW](#) [CA15584\\_ZORYA-MINI-TAPE](#)  
[FA15229\\_ROSE-MRK-S](#) [FA15232\\_ROSE-MRK-M](#) [FA15233\\_ROSE-MRK-W](#) [FCN13552\\_CRYSTAL-RS](#) [FN15552\\_RONDA-W](#)  
[FS15626\\_FLORENCE-3R-IP-Z90](#) [FS15786\\_FLORENCE-3R-IP-Z60](#) [FS15847\\_FLORENCE-3R-IP-O](#) [CA14505\\_G2-LXP2-RS2-P](#)  
[FCN12775\\_IRIS-O](#) [CP15304\\_LARISA-RS-PIN](#) [FN15679\\_RONDA-S](#) [CA15519\\_VERONICA-SQ-MINI-D](#) [FP14414\\_LISA2-O-PIN](#)  
[LL01CR-DF60L06-M2](#) [FN15993\\_RONDA-O](#) [FN15977\\_RONDA-WAS2](#) [CA14366\\_FLARE-MAXI-TAPE](#) [CA14442\\_VERONICA-SQ-W](#)  
[CA14509\\_G2-LXP2-M-P](#) [CA15231\\_VERONICA-SQ-MINI-W](#) [FP11002\\_LISA2-W-PIN](#)