

TINA-RS

~13° spot beam optimized for Osram Golden Dragon+. Assembly with holder and installation tape.

TECHNICAL SPECIFICATIONS:

Ø 16.1 mm
10.1 mm
tape
yes 🛈



MATERIAL SPECIFICATIONS:


Component	Туре	Material	Colour	Finish
TINA-O-PLUS-RS	Single lens	PMMA	clear	
TINA-O-PLUS-H-TAPE-WHT	Holder	PC	white	
TINA-TAPE3	Tape	Acrylic foam	black	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FA10886_TINA-RS	Single lens	2016	288	144	4.1
» Box size:					



PRODUCT DATASHEET FA10886_TINA-RS




See also our general installation guide: www.ledil.com/installation_guide



PHOTOMETRIC DATA (MEASURED):



LED Golden Dragon+
FWHM / FWTM 10.0° / 19.0°
Efficiency 93 %
Peak intensity 20.1 cd/lm
LEDs/each optic 1
Light colour White
Required components:






PHOTOMETRIC DATA (SIMULATED):



LED XP-E2 FWHM / FWTM 10.0° / 25.0° Efficiency 88 % Peak intensity 13.1 cd/lm LEDs/each optic

White


Light colour Required components:



CREE - LED


LED XP-G3 FWHM / FWTM 16.0° / 36.0° Efficiency 85 % Peak intensity 6.1 cd/lm LEDs/each optic 1 White Light colour

Required components:




CREE \$\(\preceq\) LED

LED XP-L HI FWHM / FWTM 12.0° / 32.0° Efficiency 89 % Peak intensity 8.6 cd/lm LEDs/each optic 1 Light colour White Required components:



CREE - LED

XT-E FWHM / FWTM 12.0° / 32.0° Efficiency 81 % Peak intensity 6.8 cd/lm LEDs/each optic White Light colour Required components:






PHOTOMETRIC DATA (SIMULATED):



LED LUXEON 5050 Square LES

FWHM / FWTM 22.0° / 56.0° Efficiency 84 % Peak intensity 2.6 cd/lm LEDs/each optic Light colour White


Required components:



WNICHIA

LED NV4WB35AM FWHM / FWTM 18.0° / 46.0° Efficiency 85 % Peak intensity 3.7 cd/lm LEDs/each optic 1 White Light colour


Required components:



OSRAM Opto Semiconductor

LED KW CULPM1.TG FWHM / FWTM 11.0° / 27.0° Efficiency 88 % Peak intensity 11.1 cd/lm LEDs/each optic 1 Light colour White

Required components:




SAMSUNG

LH351C FWHM / FWTM 16.0° / 37.0° 91 % Efficiency

Peak intensity 6.4 cd/lm LEDs/each optic White Light colour

Required components:





PRODUCT DATASHEET FA10886_TINA-RS

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDIL Oy

Joensuunkatu 13 FI-24240 SALO Finland

LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

Local sales and technical support

www.ledil.com/ where_to_buy

Shipping locations

Salo, Finland Hong Kong, China

Distribution Partners

www.ledil.com/ where_to_buy

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for LED Lighting Lenses Assemblies category:

Click to view products by Ledil manufacturer:

Other Similar products are found below:

FCN12592_LE1-D-COP CA16129_OLGA-W CA16370_HB-SQ-W FN15972_RONDA-ZT45-C CS15759_HB-2X2MX-8-W CA16435_LXP2-SS-WAS CN16210_GABRIELLA-MIDI-W CP17137_CARMEN-M2-C CA16015_STRADA-SQ-SCL CP17594_TINA-SC-RS CS15767_HB-2X2MX-8-M CP10960_RGBX-SS CP12395_LXP3-W CP12939_LARISA-RS-CLIP16 C14636_XTM-PF-ADAPTER CA11819_STRADA-SQ-T-DW CA14508_G2-LXP2-D CA14601_VERONICA-SQ-MINI-RS FCP13895_SEANNA-A CP12943_LARISA-O-CLIP16 FP11124_LISA2-O-PIN CS14597_HB-IP-2X6-O CP14995_FLORENTINA-HLD-O CS15158_STRADA-IP-2X6-T4-B CS16323_STRADELLA-IP-28-HB-M FN14976_STELLA-DWC2 FN15264_STELLA-HB-WWW CA15584_ZORYA-MINI-TAPE FA15229_ROSE-MRK-S FA15232_ROSE-MRK-M FA15233_ROSE-MRK-W FCN13552_CRYSTAL-RS FN15552_RONDA-W FS15626_FLORENCE-3R-IP-Z90 FS15786_FLORENCE-3R-IP-Z60 FS15847_FLORENCE-3R-IP-O CA14505_G2-LXP2-RS2-P FCN12775_IRIS-O CP15304_LARISA-RS-PIN FN15679_RONDA-S CA15519_VERONICA-SQ-MINI-D FP14414_LISA2-O-PIN LL01CR-DF60L06-M2 FN15993_RONDA-O FN15977_RONDA-WAS2 CA14366_FLARE-MAXI-TAPE CA14442_VERONICA-SQ-W CA14509_G2-LXP2-M-P CA15231_VERONICA-SQ-MINI-W FP11002_LISA2-W-PIN