


主要技术特性要求:

1. 使用温度范围:  
环境温度:  $-25 \sim +70^{\circ}\text{C}$   
相对湿度: 95%(40 $^{\circ}\text{C}$ )
2. 额定负荷: 2A 100V AC
3. 接触电阻:  $\leq 30\text{m}\Omega$
4. 绝缘电阻:  $\geq 100\text{M}\Omega$
5. 耐压: 500V AC (50Hz) 1min
6. 插拔力: 10~50N
7. 寿命:  $\geq 5000$ 次



				TOLERANCE UNLESS SPECIFIED							
				UP TO 5mm: $\pm 0.1$	ANGULAR	1					
				ABOVE 5mm: $\pm 0.2$	$\pm 1^{\circ}$	NO	DATE	REVISIONS		BY	APPD
4	CONTACT FOOT	BRASS	2	Ag-Plated	TITLE: DIN SOCKET			UNIT : MM	ROHS COMPLIANT	DWN	
3	CONTACT FOOT	BRASS	4	Ag-Plated	MODEL: DIN-449			SCALE: 1:1		CHK'D	
2	COVER	PBT	1	BLACK	东莞市六钧电子五金有限公司					APPD	
1	HOUSING	PBT	1	BLACK						PRO.AGL:	
NO.	PART NAME	MATERIAL	QTY	FINISHING							

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Circular DIN Connectors](#) category:*

*Click to view products by [Legion](#) manufacturer:*

Other Similar products are found below :

[D38999/20MJ37PB](#) [75-190222-09G](#) [75-190224-28S](#) [75-474014-07L](#) [FRCIR030FP-36-10P-F80](#) [88-559975-75P](#) [PT05A-14-18SW\(023\)](#)  
[PT05A-14-5SX](#) [PT05A1832SW](#) [PT05A2041SX](#) [PT05E-24-31PW](#) [PT05SE1832SWLC](#) [PT05SE1832SYLC](#) [GTC030-20-27PW-LC](#)  
[ACC06AF-20-23P\(003\)](#) [1210503216](#) [ACS00F-16-10S\(003\)](#) [ACS06AF-16-10P\(003\)](#) [D38999/46WE6SN](#) [MS3122E10-6PW](#) [MS3456W28-](#)  
[21PZ-LC](#) [MS3459W36-7PW](#) [C18213N21](#) [CA3100E16S-8PBF80](#) [CA3100E18-1SBF80A176](#) [CA3100E20-7SB-F80-A176](#) [CA3100E22-](#)  
[14SBF80](#) [CA3100E22-19PBF80](#) [CA3100E22-22SB](#) [CA3100E22-22SBF80](#) [CA3100E22-2SBF80](#) [CA3100E32-15SB](#) [CA3100F18-10SB](#)  
[CA3100F20A9SB](#) [CA3100R16S-1SBF80](#) [CA3101E18-10SBF80](#) [CA3101E18-12PBF80A176](#) [CA3101E20-15SB](#) [CA3101E32-15SB](#)  
[CA3101E32-1PB](#) [CA3101E32-5PB](#) [CA3101F10SL-3SB](#) [CA3101F20-19SB](#) [CA3101F20-29SBF80](#) [CA3101F20A9PB](#) [CA3102E12S-3P](#)  
[CA3102E14S-2P](#) [CA3102E14S-6P](#) [CA3102E14S-7P](#) [CA3102E18-10SXB](#)