



主要技术特性要求:

1.使用温度范围:

环境温度: -25~+70℃

相对湿度: 95%(40℃)

2.额定负荷: 2A 100V AC

3.接触电阻: ≤30nΩ

4.绝缘电阻: ≥100MΩ

5.耐 压: 500V AC (50Hz) 1min

6.插 拔 力: 10~50N

7.寿 命: ≥5000次

8	绝缘盖	PBT	1		TOLERANCE							
7	右长针	BRASS	1	Sn-PLATED	UNLESS SPECIFIED							
6	左长针	BRASS	1	Sn-PLATED	UP TO 5mm: ±0.1	ANGULAR	A1	2021.11.26	更新绝缘盖材质PCB为PBT	WM		
5	左短针	BRASS	1	Sn-PLATED	ABOVE 5mm: ±0.2	±1°	NO	DATE	REVISIONS	BY	APPD	
4	直针	BRASS	1	Sn-PLATED	TITLE: DIN JACK			UNIT : MM	ROHS	DWN		
3	右短针	BRASS	1	Sn-PLATED	MODEL: DIN-504B-M10			SCALE: 1:1	COMPLIANT	CHK'D		
2	接地针	PBS	1	Sn-PLATED	东莞市六钩电子五金有限公司					APPD		
1	基 座	PBT	1	BLACK								
NO.	PART NAME	MATERIAL	QTY	FINISHING				PRO.AGL:		REV :A1		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Circular DIN Connectors](#) category:

Click to view products by [Legion](#) manufacturer:

Other Similar products are found below :

[D38999/20MJ37PB](#) [75-190222-09G](#) [75-190224-28S](#) [75-474014-07L](#) [FRCIR030FP-36-10P-F80](#) [88-559975-75P](#) [PT05A-14-18SW\(023\)](#)
[PT05A-14-5SX](#) [PT05A1832SW](#) [PT05A2041SX](#) [PT05E-24-31PW](#) [PT05SE1832SWLC](#) [PT05SE1832SYLC](#) [GTC030-20-27PW-LC](#)
[ACC06AF-20-23P\(003\)](#) [1210503216](#) [ACS00F-16-10S\(003\)](#) [ACS06AF-16-10P\(003\)](#) [D38999/46WE6SN](#) [MS3122E10-6PW](#) [MS3456W28-](#)
[21PZ-LC](#) [MS3459W36-7PW](#) [C18213N21](#) [CA3100E16S-8PBF80](#) [CA3100E18-1SBF80A176](#) [CA3100E20-7SB-F80-A176](#) [CA3100E22-](#)
[14SBF80](#) [CA3100E22-19PBF80](#) [CA3100E22-22SB](#) [CA3100E22-22SBF80](#) [CA3100E22-2SBF80](#) [CA3100E32-15SB](#) [CA3100F18-10SB](#)
[CA3100F20A9SB](#) [CA3100R16S-1SBF80](#) [CA3101E18-10SBF80](#) [CA3101E18-12PBF80A176](#) [CA3101E20-15SB](#) [CA3101E32-15SB](#)
[CA3101E32-1PB](#) [CA3101E32-5PB](#) [CA3101F10SL-3SB](#) [CA3101F20-19SB](#) [CA3101F20-29SBF80](#) [CA3101F20A9PB](#) [CA3102E12S-3P](#)
[CA3102E14S-2P](#) [CA3102E14S-6P](#) [CA3102E14S-7P](#) [CA3102E18-10SXB](#)