



P.C.B. LAYOUT

SPECIFICATION

1. Rating: DC 12V 0.3A
  2. Function: 2P2T
  3. Contact Resistance: ≤70m MAX
  4. Operating Force: 180±80gf
  5. Life test: 10,000 cycles
  6. 功能: 自锁
- TEL:0769-82320511-867

				TOLERANCE UNLESS SPECIFIED										
				UP TO 5mm: ±0.1	ANGULAR	1	2015.9.10	初版		liu				
				ABOVE 5mm: ±0.2	±1°	NO	DATE	REVISIONS		BY APPD				
5	CAMSTICK	SUS	1	NATURAL	TITLE:VERTICAL PUSH SWITCH		UNIT : MM	ROHS COMPLIANT	DWN					
4	SPRING	SUS	1	NATURAL	MODEL:PB-22E60B-S-C T2.0		SCALE: 5:1	CHK'D						
3	CASE	PA66/0.3mm BRASS	1	GREY/Ag PLATED	东莞市六钧电子五金有限公司 LEGION ELECTRONIC&HARDWARE CO.,LTD							APPD		
2	COVER	PBT/PA66	1	BLACK								PRO.AGL:		REV : A
1	KNOB	POM/PA66/0.045mm PBS	1	WHITE/BLACK/Ag CLAD										
NO.	PART NAME	MATERIAL	QTY	FINISHING										

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [Legion](#) manufacturer:*

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [01-153.025](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE](#)  
[01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)  
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-](#)  
[7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#) [1211500044](#) [121194](#) [1212MRA](#)  
[1232A6NF](#) [121489](#) [1223A2ULCSA](#) [D5P-MT4](#) [13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#) [AH165-TGFY22](#) [AH165-](#)  
[TGL5Y11E3](#) [AH165-TGLR11AA3](#)