


- NOTES:
1. "□" DENOTES CRITICAL DIMENSIONS
 2. Part name: Outlet
 3. Power Rating: 15A 250VAC
 4. Life test: No Load condition: 5,000 cycles
 5. On Load test:
 - (a) Tested at Over Load condition 150% rated current: 500 cycles.
Check temp rise - not exceed 30°C
 - (b) Tested at On Load condition - rated current 15A: 500 cycles.
Check temp rise - not exceed 30°C
 6. Terminal pull force 10kg(min)
 7. Insertion Force: 9±4kg
 8. Withdrawal Force: 6±3kg

电话: 0769-82310511-867
 邮箱: hooya89@hooya.hk

Part name : Female 4-Poles Connector

2	BODY	PBT 4130(a) 94-V0 Gray Blue E304813	1
1	PIN 1#	C2680 4.8X0.8 Tin-plating 3~5µm	4
NO.	PART NAME	MATERIAL	Q'TY

5	→	10	→	DIMENSIONAL TOLERANCES		APPROVED	CHECKED	DESIGN	DRAWN	ALL SIZE ARE IN	MM	
4	→	9	→	RANGE	TOLERANCE					SCALE	NO	
3	→	8	→	X	±0.4					MAT'L	***	
2	→	7	→	X.X	±0.3					MATERIAL NO.	DRAWING NO.	
1	修改进胶口	6	→	X.XX	±0.2					RT-C05C-C	WIF111007	B
NO	DESCRIPTION	NO	DESCRIPTION	ANGLES	±0.5°	LEGION ELECTRONIC & HARDWARE CO., LTD						



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [AC Power Plugs & Receptacles](#) category:

Click to view products by [Legion](#) manufacturer:

Other Similar products are found below :

[85447L](#) [1301460003](#) [1301520008](#) [14W07](#) [15W07](#) [22806](#) [26W47](#) [929662-1](#) [27W75](#) [27W81](#) [26W](#) [26W76BLK](#) [2783](#) [27W47](#) [27W48](#)
[29W47MB](#) [HDR-E14FG1+](#) [43305](#) [85266](#) [5262DW](#) [22801](#) [25W47](#) [69W75](#) [701W-15/06](#) [26W75](#) [26W75BLK](#) [GM 207-3 NBR](#)
[BLASSBRAUN/LIGHT BROWN](#) [27T76](#) [8210GY](#) [29W48](#) [A52S22A](#) [26T49](#) [2707](#) [25W04MB](#) [2708G](#) [27W07MB](#) [2883](#) [27W74MB](#)
[28W75BLK](#) [27W81MB](#) [2983](#) [27W10MB](#) [29W83](#) [15W33GCM](#) [26W47-W](#) [63W65](#) [RECWALLBOXBA](#) [178125-2](#) [RT-C08-G2-BG](#) [RT-](#)
[C14-H08-AA-B\(HF\)](#)