

## Description


The SE2312 uses advanced trench technology to provide excellent  $R_{DS(ON)}$ , low gate charge and operation with gate voltages as low as 2.5V. This device is suitable for use as a Battery protection or in other Switching application.

## General Features


$V_{DS} = 20V$   $I_D = 6.8A$

$R_{DS(ON)} < 21m\Omega$  @  $V_{GS}=4.5V$

## Dimensions SOT-23



## Pin Configuration



## Application

- Lithium battery protection
- Wireless impact
- Mobile phone fast charging

## Package Marking and Ordering Information

Device	Device Marking	Device Package	Reel Size	Tape width	Quantity
SE2312	AE9T	SOT-23	Ø180mm	8 mm	3000 units

## Absolute Maximum Ratings (TC=25°C unless otherwise noted)

Symbol	Parameter	Rating	Units
$V_{DS}$	Drain-Source Voltage	20	V
$V_{GS}$	Gate-Source Voltage	$\pm 20$	V
$I_D@T_A=25^\circ C$	Continuous Drain Current	6.8	A
$I_D@T_A=70^\circ C$	Continuous Drain Current	6.0	A
$I_{DM}$	Pulsed Drain Current <sup>2</sup>	30	A
$P_D@T_A=25^\circ C$	Total Power Dissipation <sup>3</sup>	1.5	W
$T_{STG}$	Storage Temperature Range	-55 to 150	°C
$T_J$	Operating Junction Temperature Range	-55 to 150	°C
$R_{\theta JA}$	Thermal Resistance Junction-ambient <sup>1</sup>	83	°C/W

**Electrical Characteristics (T<sub>J</sub>=25°C, unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
BVDSS	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V, I <sub>D</sub> =250μA	20	22		V
VGS(th)	Gate Threshold Voltage	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> =250μA	0.50	0.65	1.0	V
RDS(ON)	Static Drain-Source On-Resistance	V <sub>GS</sub> =4.5V, I <sub>D</sub> =4A	16	21	mΩ	
RDS(ON)	Static Drain-Source On-Resistance					
IDSS	Zero Gate Voltage Drain Current	V <sub>DS</sub> =20V, V <sub>GS</sub> =0V			1	μA
IGSS	Gate-Body Leakage Current	V <sub>GS</sub> =±10V, V <sub>DS</sub> =0V			±100	nA
C <sub>iss</sub>	Input Capacitance	V <sub>DS</sub> =10V, V <sub>GS</sub> =0V, f=1MHZ	780		pF	
C <sub>oss</sub>	Output Capacitance			140		
C <sub>rss</sub>	Reverse Transfer Capacitance			80		
Q <sub>g</sub>	Total Gate Charge	V <sub>GS</sub> =4.5V, V <sub>DS</sub> =10V, I <sub>D</sub> =6.8A	11		nC	
Q <sub>gs</sub>	Gate-Source Charge			2.3		
Q <sub>gd</sub>	Gate-Drain Charge			2.9		
tD(on)	Turn-on Delay Time	V <sub>GS</sub> =4.5V, V <sub>DS</sub> =10V, I <sub>D</sub> =6.8A R <sub>GEN</sub> =3Ω	9		ns	
t <sub>r</sub>	Turn-on Rise Time			30		
tD(off)	Turn-off Delay Time			35		
t <sub>f</sub>	Turn-off fall Time			10		
V <sub>SD</sub>	Diode Forward Voltage	I <sub>S</sub> =6.8A, V <sub>GS</sub> =0V			1.2	V

**Note :**

- 1、The data tested by surface mounted on a 1 inch<sup>2</sup> FR-4 board with 2OZ copper.
- 2、The data tested by pulsed , pulse width ≦ 300us , duty cycle ≦ 2%
- 3、The power dissipation is limited by 150°C junction temperature
- 4、The data is theoretically the same as ID and IDM , in real applications , should be limited by total power dissipation

### Typical Characteristics




Figure 1: Output Characteristics




Figure 2: Typical Transfer Characteristics




Figure 3: On-resistance vs. Drain Current




Figure 4: Body Diode Characteristics




Figure 5: Gate Charge Characteristics







Figure 6: Capacitance Characteristics




**Figure 7: Normalized Breakdown Voltage vs. Junction Temperature**




**Figure 8: Normalized on Resistance vs Junction Temperature**




**Figure 9: Maximum Safe Operating Area vs. Case Temperature**



**Figure 10: Maximum Continuous Drain Current**



**Figure 11: Maximum Effective Transient Thermal Impedance, Junction-to-Case**

**Package Mechanical Data:SOT-23**


<b>Symbol</b>	<b>Dimensions in Millimeters</b>	
	<b>MIN.</b>	<b>MAX.</b>
A	0.900	1.150
A1	0.000	0.100
A2	0.900	1.050
b	0.300	0.500
c	0.080	0.150
D	2.800	3.000
E	1.200	1.400
E1	2.250	2.550
e	0.950TYP	
e1	1.800	2.000
L	0.550REF	
L1	0.300	0.500
θ	0°	8°

Shanghai Leiditech Electronic Co.,Ltd  
 Email: sale1@leiditech.com  
 Tel : +86- 021 50828806  
 Fax : +86- 021 50477059

# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for MOSFET category:***

***Click to view products by Leiditech manufacturer:***

Other Similar products are found below :

[614233C](#) [648584F](#) [IRFD120](#) [IRFF430](#) [JANTX2N5237](#) [2N7000](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [AOD464](#) [2SK2267\(Q\)](#) [2SK2545\(Q,T\)](#)  
[405094E](#) [423220D](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [SSM6J414TU,LF\(T\)](#) [751625C](#) [PSMN4R2-30MLD](#)  
[TK31J60W5,S1VQ\(O\)](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#)  
[NTE2384](#) [NTE2969](#) [NTE6400A](#) [DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [SSM6P54TU,LF](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#) [STU5N65M6](#) [C3M0021120D](#) [DMN13M9UCA6-7](#)  
[BSS340NWH6327XTSA1](#) [MCM3400A-TP](#) [DMTH10H4M6SPS-13](#) [IRF40SC240ARMA1](#) [IPS60R1K0PFD7SAKMA1](#)  
[IPS60R360PFD7SAKMA1](#) [IPS60R600PFD7SAKMA1](#)