



## www.lemo.com

## SUMMARY

#### # Wires



Image is for illustrative purpose only

**Series** 1M

Termination type No contacts / Accessory

IP rating 68

AWG wire size 0.00 - 0.00Cable Ø 0.00 - 0.00 mm

Status active

#### **Download**

Request a quote

Catalog

## **TECHNICAL DETAILS**

## **Mechanics**

Shell Style/Model BME\*: Blanking cap for fixed receptacle(knurled grip)

Keying

Aluminium (nickel plated [SAE AMS QQ N 290], anthracite color) shell and nut, other pieces **Housing Material** 

bronze/brass

Weight 4.51 g

#### **Performance**

Configuration

Insulator

**Rated Current** 

## **Specifications**

Contact LEMO for performance details.

### **Others**

Temp (min / max):  $-20^{\circ}$ C /  $+135^{\circ}$ C Humidity (max): 21 days at 95%

Gunfire vibration: 25 Hz - 2000 Hz, 3 axis (Apache helicopter)

Vibration-Sine: 30 g, 3 axes, 12 hr [10 Hz - 2000 Hz]

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Vibration-Random: 37.8 g rms - 3 axes, 4 hr amb [50 Hz - 2000 Hz]


Shock Resistance: 300 g [ 3 ms]

Lighting strike EIA 364-75: 10K amps - 6 times Thermal shock: 5 cycles: -65°C to +150°C

EMI Shielding EIA 364-66A: >= 80 dB (1 GHz), >= 70 dB (3 GHz), >= 58 dB (6 GHz), >= 40 dB (10 GHz)

Salt Spray Corrosion: max. 48 hr

# **DRAWINGS**





#### **Dimensions**

	A	С	L	N	Р	Х
mm.	14.6	14.2	23.4	85	3.9	6
in.	0,57	0,56	0,92	3,35	0,15	0,24

# **RECOMMENDED BY LEMO**

### **Tools**

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Standard Circular Connector category:

Click to view products by LEMO manufacturer:

Other Similar products are found below:

5M2530B10P 600259N006 600273N007 6134-336-13149 6134-337-11149 6134-337-2390 6134-341-17149 6280-4SG-516 6280-7SG-3DC 6290 6291A 66200A-10 680-SMG 681-PMG CXS3102A14S2P CXS3102A181S 7251-6SG-300 7271-6SG-300 7282-3PG-300-CH3 75-474014-05S 75-474618-01S 75-474618-04S 799539-000 MI8-SE 805-005-07NF11-19PC 805-005-07NF15-7PA 8280-4PG-516 8280-7PG-519 8282-5PG-519 836783-1 MP-4102-25P-C 862256-1 864019-2 866857-1 867865-1 PT01SP-14-18P PT08P-14-5S PTSF06SE-14-12S 120-1833-000 QCM019PC2DC012B 1-2069279-1 121583-0217 121667-0020 129591AU 1000B BULK RD10A16-19-P6CS051/1 RD10A20-31-P8CS051/1 RD16A14-12-S6CS051/2 1301240290 1301240347 1301860202