

EEG.2B.302.CLL

SUMMARY

Wires

Low voltage



Image is for illustrative purpose only

Series	2B	
Termination type	Female solder	
IP rating	50	
AWG wire size	22.00 - 14.00	
Cable Ø	0.00 - 0.00 mm	
Status	active	
Matching parts	FGG.2B.302.CLAD82	

2

Download

Request a quote Eplan Catalog

TECHNICAL DETAILS

Mechanics


Shell Style/Model	EE*: Fixed receptacle, nut fixing (back panel mounting)
Keying	1 key (alpha=0, plug: male contacts, receptacle: female contacts)
Housing Material	Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces
Weight	15.82 g
Performance	
Configuration	2B.302 : 2 Low Voltage
Insulator	L: PEEK (UL 94 / V-0/1.5)
Rated Current	25 Amps
Specifications	


Contact Type: Solder Contact Dia.: 2 mm (0.079in) Bucket Dia.: 1.8 mm (0.071in) Max. Solid Conductor: 1.5 mm^2 (AWG 14) Max. Stranded Conductor: 1.5 mm^2 (AWG 16) R (max): 3.3 mOhm Vtest (contact-shell): 1750 V (AC), 2500 V (DC) Vtest (contact-contact): 2100 V (AC), 2970 V (DC)

Others

Endurance (Shell): 5000 Temp (min / max): -55°C / +250°C Humidity (max): <=95% [at 60 deg C /140 F] Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms] Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz) Salt Spray Corrosion: >1000 hr

DRAWINGS







Dimensions

	А	В	E	L	Μ	N	Р	S1	S2	e
mm.	20	20	4.3	26.7	3.5	24.6	9	13.5	15	M15x1.0
in.	0,79	0,79	0,17	1,05	0,14	0,97	0,35	0,53	0,59	

RECOMMENDED BY LEMO

Tools

Cables

CMN.02.T14.072PGZE		Grey	
CMN.02.T14.072PNZE		Black	-
CMN.02.T14.072QGZE	TPR (medical)	Grey	-
CMN.02.T14.078PGZE		Grey	
CMN.02.T14.078PNZE			-
CMN.02.T18.064UNCU			
CMN.02.T20.047PGZE		Grey	
CMN.02.T20.047PNZE			-
CMN.02.T20.048QGZE	TPR (medical)	Grey	
CMN.02.T28.030PGCE	PVC	GREY	
CMN.02.T28.030PGZE		Grey	-
CMN.02.T28.030PNCE	PVC	Black	
CMN.02.T28.030PNZE			-
102080	PVC	Grey	
120184	PVC	Black	>
120240	PVC	Black	
120250	PVC	Grey	-
120500	PVC	Grey	-
120501	PVC	Grey	
120751	PVC	Grey	~
20140	PVC	Grey	
20140	PVC	Grey	
20141	PVC	Grey	
20142	PVC	Red	
20143	PVC	Green	
20144	PVC	Black	
20145	PVC	Yellow	
20146	PVC	Black	
20240	PTFE	White	**
20260	PVC	Black	
20264	PVC	Black	-
20266	PVC	Violet	
2050	PVC	Black	~
20550	PUR	Black	
20560	PUR	White	
	FUR	wince	

220151	PVC	Grey	
220750	PVC	Grey	
2221	PVC	Black	
2260	PTFE	White	<>
2280	PVC	Black	
320150	PVC	Grey	-
4082	PVC	Grey	
CMB.02.210.635	PUR	Black	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Push Pull Connectors category:

Click to view products by LEMO manufacturer:

Other Similar products are found below :

6407-249V-11273P 6408-201V-13273 6408-202V-13343 6408-202V-17343 EZG.0B.309.CLN FFA.2S.310.ZLA FGA.1B.307.CYCD72Z FGJ.1B.304.CLLD76 FGJ.1B.306.CWLD72 FGJ.3B.304.CYMD10Z FGJ.3B.304.CYMD82Z PCS.01.250.DLLE24 PHG.0K.305.CYMC40Z PHG.1K.308.CLLK85 PKG.M0.6BL.LZ PLC.M1.0SL.LA GMA.10.290.DN GMA.3B.090.DA PRG.M0.6GL.LC52GZ PSA.1S.275.CTLC66 ABF.1S.250.NTA 133020F 1331ER193MZ 1332M107MZ DTS26Z19-32JA-LC DTS26Z19-32SA DTS26Z19-32SA-LC DTS26Z23-55HA DTS26Z23-55HA-LC DTS26Z23-55JA-LC EAJ.1B.306.CWA ECG.XB.312.CLL 1589430-2 EEA.0B.305.CLN EEA.0B.309.CLL ELF.00.250.NTL ERA.01.250.DLL BRR.2S.200.PZVG HR10A-P CAH.M34.SLL.C72GZ CAJ.M34.SLL.C72GZ 300500 ESB.00.303.NLL EXG.0B.309.HLN FFB.1S.250.CLAC27 FGA.2B.306.CYCD92 FGA.2B.306.CYCD92Z FGA.XB.312.CLAD72 FGJ.1B.302.CYMD62 FGJ.3B.308.CLLD72Z