

# EGJ.1B.305.CYC

### SUMMARY

#### # Wires

Low voltage

5



Image is for illustrative purpose only

| Series           | 1B                |  |  |  |
|------------------|-------------------|--|--|--|
| Termination type | Male crimp        |  |  |  |
| IP rating        | 50                |  |  |  |
| AWG wire size    | 24.00 - 20.00     |  |  |  |
| Cable Ø          | 0.00 - 0.00 mm    |  |  |  |
| Status           | active            |  |  |  |
| Matching parts   | FGJ.1B.305.CYMD42 |  |  |  |

#### Download

Request a quote Catalog

## **TECHNICAL DETAILS**

#### **Mechanics**

| Shell Style/Model                                   | EG*: Fixed receptacle, nut fixing   |
|---|---|
| Keying  | 2 keys (gamma=45, plug: female contacts, receptacle: male contacts)   |
| Housing Material                                    | Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces |
| Weight  | 9.26 g  |
| Performance   |   |
| Configuration                                       | 1B.305 : 5 Low Voltage  |
| Insulator   | Y: PEEK for crimp contacts  |
| Rated Current                                       | 9 Amps  |
|   |   |
| Weight<br>Performance<br>Configuration<br>Insulator | brass latch sleeve and mid pieces<br>9.26 g<br>1B.305 : 5 Low Voltage<br>Y: PEEK for crimp contacts                           |

#### **Specifications**

Contact Type: Crimp Contact Retention: 30 N Contact Dia.: 0.9 mm (0.035in) Bucket Dia.: 1.1 mm (0.043in) Min. Conductor: 0.25 mm^2 (AWG 24) Max. Conductor: 0.5 mm^2 (AWG 20) R (max): 4.8 mOhm Vtest (contact-shell): 1550 V (AC), 2200 V (DC)


LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

#### Others

Endurance (Shell): 5000 Temp (min / max): -55°C / +250°C Humidity (max): <=95% [at 60 deg C /140 F] Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [ 6 ms] Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz) Salt Spray Corrosion: >1000 hr

### DRAWINGS







#### Dimensions

|     | А    | В    | E    | L    | м    | N    | S1   | \$3  | e       |
|-----|------|------|------|------|------|------|------|------|---------|
| mm. | 14   | 16   | 7.5  | 23   | 1.5  | 21.1 | 10.5 | 14   | M12x1.0 |
| in. | 0,55 | 0,63 | 0,30 | 0,91 | 0,06 | 0,83 | 0,41 | 0,55 |         |

### **RECOMMENDED BY LEMO**

#### Tools

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

| Crimp Tool:          | DPC.91.701.V                  |
|----------------------|-------------------------------|
| Crimp settings:      | AWG/Selector = 20-22-24/6-5-5 |
| Positionner:         | DCE.91.091.BVC                |
| Extractor:           | DCF.91.090.2LT                |
| Replacement contact: | FGG.1B.560.ZZC                |

#### Cables

| CMN.05.T20.057PGZE |               | Grey  | >€ |
|--------------------|---------------|-------|----|
| CMN.05.T20.057PNZE |               |       | €  |
| CMN.05.T20.057QGZE | TPR (medical) | Grey  | €  |
| CMN.05.T22.051QGZE | TPR (medical) | Grey  | €  |
| CMN.05.T28.029PGCE | PVC           | GREY  |    |
| CMN.05.T28.029PGZE |               | Grey  | €  |
| CMN.05.T28.029PNCE | PVC           | Black |    |
| CMN.05.T28.029PNZE |               |       |    |
| 150250             | PVC           | Grey  |    |
| 250500             | PVC           | Grey  |    |
| 50090              | PVC           | Black |    |
| 50140              | PVC           | Grey  |    |
| 5050               | PVC           | Black |    |

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Push Pull Connectors category:

Click to view products by LEMO manufacturer:

Other Similar products are found below :

6407-249V-11273P 6408-201V-13273 6408-202V-13343 6408-202V-17343 EZG.0B.309.CLN FFA.2S.310.ZLA FGA.1B.307.CYCD72Z FGJ.1B.304.CLLD76 FGJ.1B.306.CWLD72 FGJ.3B.304.CYMD10Z FGJ.3B.304.CYMD82Z PCS.01.250.DLLE24 PHG.0K.305.CYMC40Z PHG.1K.308.CLLK85 PKG.M0.6BL.LZ PLC.M1.0SL.LA GMA.10.290.DN GMA.3B.090.DA PRG.M0.6GL.LC52GZ PSA.1S.275.CTLC66 ABF.1S.250.NTA 133020F 1331ER193MZ 1332M107MZ DTS26Z19-32JA-LC DTS26Z19-32SA DTS26Z19-32SA-LC DTS26Z23-55HA DTS26Z23-55HA-LC DTS26Z23-55JA-LC EAJ.1B.306.CWA ECG.XB.312.CLL 1589430-2 EEA.0B.305.CLN EEA.0B.309.CLL ELF.00.250.NTL ERA.01.250.DLL BRR.2S.200.PZVG HR10A-P CAH.M34.SLL.C72GZ CAJ.M34.SLL.C72GZ 300500 ESB.00.303.NLL EXG.0B.309.HLN FFB.1S.250.CLAC27 FGA.2B.306.CYCD92 FGA.2B.306.CYCD92Z FGA.XB.312.CLAD72 FGJ.1B.302.CYMD62 FGJ.3B.308.CLLD72Z