



www.lemo.com

SUMMARY

Wires

Coax 1



Image is for illustrative purpose only

00 **Series**

Female solder Termination type

IP rating 50

AWG wire size 0.00 - 0.00 Cable Ø 0.00 - 0.00 mm

Status active

Matching parts FFA.00.250.CTAC31

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model ERT*: Straight receptacle without thread, force or adhesive fit

Keying Circular, female

Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] **Housing Material**

brass latch sleeve and mid pieces

Weight 2.13 g

Performance

Configuration 00.250 : 1 Coax (50 Ohm)

Insulator T: PTFE **Rated Current** 4 Amps

Specifications

Contact Type: Coaxial 50 Ohm (Solder)

Contact Dia.: 0.7 mm (0.028in) Bucket Dia.: 0.6 mm (0.024in) Test voltage: 2.1 kV (rms)

R (max): 6.1 mOhm

Vtest: 2100 V (AC), 3000 V (DC)

Impedance: 50 Ohm

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

VSWR: 1.09 + 0.11 * f/GHz


Others


Endurance (Shell): 5000 mating cycles

F ret (min): 100 N

Salt Spray Corrosion: >1000 hr

DRAWINGS







Dimensions

	Α	L
mm.	8	15
in.	0,31	0,59

RECOMMENDED BY LEMO

Tools

Cables

159580	PVC	Black	
17420	PVC	Black	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

17450	COPOLYMER	Black	
178190	PTFE	Brown	
18000	PTFE	Brown	-12 -
18700	PTFE	White	- a - b -
18800	PTFE	White	
196270	PTFE	White	
31600	PTFE	Brown	
62000	PVC	Black	
CCX.50.030.083.180B		White	
CCX.50.RG0.58AU14B	FEP	White	
CCX.50.RG1.74-U25N	PVC	Black	
CCX.50.RG1.74AU28N	PVC	Black	
CCX.50.RG1.74AU28N	PVC	Black	
CCX.50.RG1.74U25N	PVC	Black	
CCX.50.RG1.78BU18M	FEP	Brown	
CCX.50.RG1.78BU18M	PTFE	Brown	
CCX.50.RG1.88AU24B	TFE	White	
CCX.50.RG1.88AU26B	PFA	White	
CCX.50.RG1.88AU26B	PTFE	White	
CCX.50.RG1.96AU19B	PTFE	White	
CCX.50.RG1.96AU20B	PFA	White	
CCX.50.RG3.16BU26M	FEP	Brown	
CCX.50.RG3.16U28M	PTFE	Brown	
CCX.75.040.195327G	PVC	Grey	
CCX.75.RG0.59BU62N	PVC	Black	
CCX.75.RG1.79BU26M	FEP	Brown	
CCX.75.RG1.87AU26B	PFA	White	
CCX.75.RG1.87AU27B	PTFE	White	- a = =-
CCX.93.RG0.62AU62N	PVC	Black	
CCX.95.RG1.80BU36M	PTFE	Brown	-15
CCX.95.RG1.95AU37B	PFA	White	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Push Pull Connectors category:

Click to view products by LEMO manufacturer:

Other Similar products are found below:

6407-249V-11273P 6408-201V-13273 6408-202V-13343 6408-202V-17343 FAG.2B.319.CYC FGA.1B.307.CYCD72Z
FGC.0B.309.CLAD56 FLS.01.250.DLAE24 PFG.1B.308.CYZZ PKG.M0.6BL.LZ PLC.M1.0SL.LA GMA.2B.045.DJ GMA.3B.090.DA
PRG.M0.6GL.LC52GZ ABF.1S.250.NTA 1332M107MS EAJ.1B.306.CWA 1589430-2 ELF.00.250.NTL ERA.01.250.DLL
BRD.0B.200.PCSG HVP.03.250.CLLPV CAH.M34.SLL.C72GZ CAJ.M34.SLL.C72GZ 300500 EXG.0B.309.HLN FFB.1S.250.CLAC27
FLC.00.250.CTAC31 FPG.0B.305.CLAD52 PCS.01.250.DLLE31 PKC.M0.7GL.NG PKG.M0.4TL.LZ PXG.M0.8GG.NG
HEG.1B.307.CLNP BRR.3S.200.PZVG JDXEP2T19FSN 400374 DTA.99.700.5Z ECG.00.304.CLL ECP.0S.304.CLN EEG.1B.306.CYZ
MS3117-12BU EGA.00.303.CLL SAN.M13.GLA.6G 6408-201V-11343 6408-202V-25273 PAC.M0.4NL.AC52J 980-0009-471
NCG044SC2DC006 13303PM20