www.lemo.com

ERX.00.650.NLL

SUMMARY

Wires

Low	0
High	0
Coax	0
Triax	1
Quad	0
Fiber	0
Fluidic	0

Image is for illustrative purpose only

Download

Request a quote

Catalog

Series	00
Termination type	Female solder
IP rating	50
Cable Ø	0.00 - 0.00 mm
Matching parts	FAA.00.650.NLA
Status	active
Alternative part	

TECHNICAL DETAILS

Mechanics

Shell Style/Model	*:
Keying	Circular (can rotate)
Housing Material	Brass (nickel plated) shell, collet nut, latch sleeve and mid pieces
Cable Fixing	⌀0 - 0 mm
Variant	
Weight	1.93 g

Performance

Configuration	0.65 : 1 Triax (50 Ohm)
Insulator	L: PEEK (UL 94 / V-0/3.2, depends on material thickness)
Rated Current	3 Amps

Specifications

Contact Type: Triaxial 50 Ohm (Solder)
Max. Matings: 1000
Contact Dia.: 0.5 mm (0.02"in)

Vtest: 1200 V (AC), 1700 V (DC)
Impedance: 50 Ohm
VSWR: 1.1 + 0.11 * f/GHz

Others

IP Rating: 50

DRAWINGS

Draws

Dimensions

RECOMMENDED BY LEMO

Tools

None

Cables

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Push Pull Connectors ***category:***

Click to view products by LEMO ***manufacturer:***

Other Similar products are found below :

6407-249V-11273P 6408-201V-13273 6408-202V-13343 6408-202V-17343 D38999/20ZG35PN-LC D38999/20ZJ29PA-LC D38999/20ZJ43HA D38999/20ZJ43PA-LC D38999/20ZJ61PA-LC FAG.2B.319.CYC FGA.1B.307.CYCD72Z FGC.0B.309.CLAD56 FLS.01.250.DLAE24 PFG.1B.308.CYZZ PKG.M0.6BL.LZ PLC.M1.0SL.LA GMA.2B.045.DJ GMA.3B.090.DA PRG.M0.6GL.LC52GZ ABF.1S.250.NTA 1332M107MS EAJ.1B.306.CWA 1589430-2 ELF.00.250.NTL ERA.01.250.DLL BRD.0B.200.PCSG HVP.03.250.CLLPV CAH.M34.SLL.C72GZ CAJ.M34.SLL.C72GZ 300500 EXG.0B.309.HLN FFB.1S.250.CLAC27 FLC.00.250.CTAC31 FPG.0B.305.CLAD52 PCS.01.250.DLLE31 PKC.M0.7GL.NG PKG.M0.4TL.LZ PXG.M0.8GG.NG HEG.1B.307.CLNP BRR.3S.200.PZVG JDXEP2T19FSN 400374 DTA.99.700.5Z ECG.00.304.CLL ECP.0S.304.CLN EEG.1B.306.CYZ MS3117-12BU EGA.00.303.CLL SAN.M13.GLA.6G 6408-201V-11343