www.lemo.com

FGG.2B.571.ZZC

SUMMARY

Wires

Low voltage	1

Image is for illustrative purpose only

Series	2B
Termination type	Male crimp
IP rating	50
AWG wire size	22.00 - 18.00
Cable Ø	0.00 - 0.00 mm
Status	active
Matching parts	EGG.2B.671.ZZM

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model	FG*: Male crimp contact, oversize barrel
Keying	No keying
Housing Material	Gold plated [ISO 27874] brass
Weight	.44 g

Performance

Configuration

Insulator

Rated Current

Others

Endurance (Shell): 5000
Temp (min / max): -55°C / +250°C
Humidity (max): <=95% [at 60 deg C /140 F]
Vibration: 15 g [10 Hz - 2000 Hz]
Shock Resistance: 100 g [6 ms]

Climatical Category: 50/175/21
Shielding (min): 75 dB (10 MHz)
Shielding (min): 40 dB (1 GHz)

DRAWINGS



No keying

Dimensions

	A	C
mm.	1.6	1.4
in.	0,06	0,06

RECOMMENDED BY LEMO

Tools

Crimp Tool: DPC.91.101.A
Positionner: DCE.91.162.BVCM

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Push Pull Connectors ***category:***

Click to view products by LEMO ***manufacturer:***

Other Similar products are found below :

6407-249V-11273P 6408-201V-13273 6408-202V-13343 6408-202V-17343 FAG.2B.319.CYC FGA.1B.307.CYCD72Z FGC.0B.309.CLAD56 FLS.01.250.DLAE24 PFG.1B.308.CYZZ PKG.M0.6BL.LZ PLC.M1.0SL.LA GMA.2B.045.DJ GMA.3B.090.DA PRG.M0.6GL.LC52GZ ABF.1S.250.NTA 1332M107MS EAJ.1B.306.CWA 1589430-2 ELF.00.250.NTL ERA.01.250.DLL BRD.0B.200.PCSG HVP.03.250.CLLPV CAH.M34.SLL.C72GZ CAJ.M34.SLL.C72GZ 300500 EXG.0B.309.HLN FFB.1S.250.CLAC27 FLC.00.250.CTAC31 FPG.0B.305.CLAD52 PCS.01.250.DLLE31 PKC.M0.7GL.NG PKG.M0.4TL.LZ PXG.M0.8GG.NG HEG.1B.307.CLNP BRR.3S.200.PZVG JDXEP2T19FSN 400374 DTA.99.700.5Z ECG.00.304.CLL ECP.0S.304.CLN EEG.1B.306.CYZ MS3117-12BU EGA.00.303.CLL SAN.M13.GLA.6G 6408-201V-11343 6408-202V-25273 PAC.M0.4NL.AC52J 980-0009-471 NCG044SC2DC006 13303PM20