

www.lemo.com

FGJ.3B.308.CLLD72Z

SUMMARY

Wires

 Low
 8

 High
 0

 Coax
 0

 Triax
 0

 Quad
 0

 Fiber
 0

 Fluidic
 0

Series 3B

Termination type Female solder

IP rating 50

Cable Ø 6.30 - 7.70 mm

Matching parts EGJ.3B.308.CLA

Status active

Alternative part



Image is for illustrative purpose only

Download

Request a quote

Catalog

TECHNICAL DETAILS

Mechanics

Shell Style/Model FG*: Straight plug, cable collet and nut for fitting a bend relief

Keying 2 keys (alpha=37.5, plug: female contacts, receptacle: male contacts)

Housing Material Brass (chrome plated) shell and collet nut, nickel plated brass latch sleeve and mid pieces

Cable Fixing D72: 6.3 - 7.7 mm

Variant Z: Nut for fitting a bend relief

Weight 50.33 g

Performance

Configuration 3B.308: 8 Low Voltage

Insulator L: PEEK (UL 94 / V-0/3.2, depends on material thickness)

Rated Current 13 Amps

Specifications

Contact Type: Solder Max. Matings: 5000

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Contact Dia.: 1.3 mm (0.051in) Bucket Dia.: 1 mm (0.039in)

Max. Solid Conductor: 0.5 mm² (AWG 20) Max. Stranded Conductor: 0.5 mm² (AWG 20)

R (max): 3.6 mOhm

Vtest (contact-shell): 1150 V (AC), 1630 V (DC) Vtest (contact-contact): 1650 V (AC), 2350 V (DC)

Others

Temp (min / max): -55°C / +250°C


Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [6 ms] Salt Spray Corrosion: >1000 hr Climatical Category: 50/175/21 Shielding (min): 75 dB (10 MHz) Shielding (min): 40 dB (1 GHz)

IP Rating: 50

DRAWINGS

Draws







Dimensions

	А	L	М	S1	S2
mm.	18	56.5	41.5	15	15
in.	0,71	2,22	1,63	0,59	0,59

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

RECOMMENDED BY LEMO

Tools

Spanner wrench: DCD.3B.040.PA150

Cables

CMN.08.T20.067PGCE	PVC	GREY	>====
CMN.08.T20.067PGZE		Grey	
CMN.08.T20.067PNCE	PVC	Black	>====
CMN.08.T20.067PNZE			>
108 220	PVC	Black	
208 200	PVC	Black	
280 250	PVC	Grey	>====

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Push Pull Connectors category:

Click to view products by LEMO manufacturer:

Other Similar products are found below:

FEA.1B.308.CYCD72Z D38999/20ZC8JA D38999/20ZG35PN-LC D38999/20ZG39BN D38999/20ZG41PN-LC D38999/20ZH21SA D38999/20ZJ4SA D38999/20ZJ29PA-LC D38999/20ZJ43HA D38999/20ZJ43PA-LC D38999/20ZJ61PA-LC D38999/24ZF31SA-LC D38999/24ZF32BA D38999/24ZF32PA-LC D38999/24ZF32SA-LC D38999/24ZF35BA D38999/24ZF35SA-LC EXG.00.250.NTNY FFA.00.250.CTAZ FFA.1S.302.CLAZ FFA.1Y.410.CTAC52 FFA.2S.310.ZLA FFG.1B.302.CLAD52Z FFG.1B.304.CLAD42Z FFG.1B.304.CLAD42Z FGA.1B.304.CLAD62Z FGA.1B.304.CYCD72Z FGA.1B.305.CLAD76 FGA.1B.306.CYCD72 FGA.1B.307.CYCD72Z FGA.1B.308.CLAD76Z FGA.1B.308.CYCD42Z FGA.1B.308.CYCD52Z FGA.1B.308.CYCD72Z FGA.1B.310.CLAD42 FGA.1B.310.CLAD52Z FGA.1B.316.CLAD42 FGA.1B.316.CLAD62Z FGA.1B.316.CLAD42 FGB.1B.316.CLAD62Z FGB.1B.316.CLAD76 FGB.0B.307.CYCD31Z FGB.1B.302.CLAD72 FGB.1B.303.CYCD62 FGB.1B.305.CLAZ FGB.1B.307.CYCD62Z FGB.1B.316.CLAD42 FGC.0B.309.CLAD56 FGC.1B.304.CLAD52Z FGC.1B.305.CLAD52Z