

# PAB.MO.4TL.AC39NZ

## SUMMARY

#### # Wires

Low voltage 4



Image is for illustrative purpose only

Series 1P

Termination type Male solder

IP rating 50

AWG wire size 0.00 - 22.00

Cable Ø 2.70 - 3.90 mm

**Status** active

Matching parts PLB.M0.4TL.LN

#### **Download**

Request a quote

Eplan Catalog

### **TECHNICAL DETAILS**

#### Mechanics

Shell Style/Model PA\*: Straight plug with cable collet and nut for fitting a bend relief

Keying 2 keys (alpha=60; Plug: male contacts; Receptacle: female contacts)

Housing Material PEI (Polyetherimide), black

Variant N: Black collet nut for bend relief

Weight 5.18 g

#### **Performance**

Configuration 1P.M04: 4 Low Voltage Insulator L: PEEK (UL 94 / V-0/1.5)

Rated Current 8 Amps

### **Specifications**

Contact Type: Solder

Contact Dia.: 0.9 mm (0.035in) Bucket Dia.: 0.8 mm (0.031in)

Max. Solid Conductor: 0.34 mm<sup>2</sup> (AWG 22) Max. Stranded Conductor: 0.34 mm<sup>2</sup> (AWG 22)

R (max): 4.5 mOhm

Test voltage (kV rms) Contact-contact: 1.2

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Air clearance min.: 1.2 mm Creepage distance min.: 1.2 mm


### **Others**


Endurance (Shell): >2000 mating cycles

F ret (min): 50 N F ret (max): 150 N

Steam sterilization: > 100 times (with potting on rear connection)

# **DRAWINGS**







# **RECOMMENDED BY LEMO**

**Tools** 

#### **Cables**

CMN.04.T28.031PGCE	PVC	GREY	
CMN.04.T28.031PGZE		Grey	▶ €
CMN.04.T28.031PNCE	PVC	Black	
CMN.04.T28.031PNZE			<b>&gt;</b>
CMN.04.T28.031QGC	TPR	Grey	
40080	PVC	Black	
40086	PVC	Blue	

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

40240	PTFE	White	<b>&gt;</b>
4041	PVC	Grey	∍
4050	PVC	Black	
4260	PTFE	White	>=====================================

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Circular Push Pull Connectors category:

Click to view products by LEMO manufacturer:

Other Similar products are found below:

6407-249V-11273P 6408-201V-13273 6408-202V-13343 6408-202V-17343 EZG.0B.309.CLN FFA.2S.310.ZLA FGA.1B.307.CYCD72Z FGJ.1B.304.CLLD76 FGJ.1B.306.CWLD72 FGJ.3B.304.CYMD10Z FGJ.3B.304.CYMD82Z PCS.01.250.DLLE24 PHG.0K.305.CYMC40Z PHG.1K.308.CLLK85 PKG.M0.6BL.LZ PLC.M1.0SL.LA GMA.10.290.DN GMA.3B.090.DA PRG.M0.6GL.LC52GZ PSA.1S.275.CTLC66 ABF.1S.250.NTA 133020F 1331ER193MZ 1332M107MZ DTS26Z19-32JA-LC DTS26Z19-32SA DTS26Z19-32SA-LC DTS26Z23-55HA DTS26Z23-55HA-LC DTS26Z23-55JA-LC EAJ.1B.306.CWA ECG.XB.312.CLL 1589430-2 EEA.0B.305.CLN EEA.0B.309.CLL ELF.00.250.NTL ERA.01.250.DLL BRR.2S.200.PZVG HR10A-P CAH.M34.SLL.C72GZ CAJ.M34.SLL.C72GZ 300500 ESB.00.303.NLL EXG.0B.309.HLN FFB.1S.250.CLAC27 FGA.2B.306.CYCD92 FGA.2B.306.CYCD92Z FGA.XB.312.CLAD72 FGJ.1B.302.CYMD62 FGJ.3B.308.CLLD72Z