



LEOPARD IMAGING INC

Rev. 1.1

LI-USB30-OV2311-xxxH

Data Sheet

Key Features

- USB 3.0 Super Speed support
- 10-bit RAW data output without compression
- UVC compliance
- Monochrome sensor
- Global shutter
- Resolution: 1600 x 1300
- Frame rate: 30 fps
- Support register access function
- Provide customization services
- USB +5VDC powered device
- Compact Size: 26mmx26mm
- 2 Boards are stacked
- Part#:
LI-USB30-OV2311-125H
LI-USB30-OV2311-110H
- Support multiple module options
- OV2311 module Part#:
LI-OV2311-MIPI-125H
LI-OV2311-MIPI-M8-H110



Lens Specification


- Focusing Range: 50cm to Infinity
- Focal length: 2.2 mm (125H)
2.65mm (110H)
- F/#: 2.5 (125H) / 2.0 (110H)
- FOV (H): 125 °/ 110 °
- TV Distortion < -87.6% (125H)
< -15% (110H)

Applications

- Machine Vision
- Scientific Camera

SDK Supported

- Camera Tool Source Code in C#
- Capture & Display
- RAW to Grayscale Conversion
- Save file as BMP & RAW format
- Access registers



RAW data streaming



Camera Tool view mode



Leopard Imaging Inc.

48820 Kato Road, Suite 100B, Fremont, CA 94538, USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email: sales@leopardimaging.com
Website: www.leopardimaging.com

Specification

General Behavior	
Video Resolution @ Frame rate	1600 x 1300 @ 30 fps
Dynamic range	10 bit
Interface (Optical)	
IR cut filter (on lens)	No
Sensor specification	OmniVision CMOS 2MP image sensor OV2311
Shutter	Global shutter
Format	1/2.9"
Resolution	H:1600, V:1300
Pixel size	H: 3 um, V: 3 um
Interface (Electrical)	
Interface	USB 3.0
Supply voltage	USB 3.0 +5 VDC power source
Current consumption	Approx. 225 mA at 5 VDC
Interface (Mechanical)	
Dimensions	L: 26 mm, W: 26 mm, H: 20 mm
Mass	20 g
Adjustment (Manual)	
Shutter	Support
Gain	Support
Register Access	Support
Adjustment (Auto)	
Shutter	TBD
Gain	TBD
Environmental	
Max. temperature (operation)	0 °C ~ 50 °C (32 °F~ 122 °F)
Max. temperature (storage)	-20 °C ~ 80 °C (-4 °F~176 °F)
Max. humidity (operation)	20 % ~ 80 %, relative, non-condensing
Max. humidity (storage)	20 % ~ 80 %, relative, non-condensing



Leopard Imaging Inc.

48820 Kato Road, Suite 100B, Fremont, CA 94538, USA
Phone: +1-408-263-0988
Fax: +1-408-217-1960
Email: sales@leopardimaging.com
Website: www.leopardimaging.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Camera Development Tools](#) category:

Click to view products by [Leopard Imaging](#) manufacturer:

Other Similar products are found below :

[P0447](#) [1937](#) [MXOV10635-S32V](#) [OV10640CSP-S32V](#) [SEN0173](#) [DS90UB953-Q1EVM](#) [3508](#) [3538](#) [EP-DCOV2735-F36](#) [3100](#) [3202](#) [3622](#)
[397](#) [4407](#) [4469](#) [4959](#) [108024](#) [108025](#) [108226](#) [108225](#) [108320](#) [108328](#) [108329](#) [DFR0498](#) [DFR0620](#) [ESP-EYE](#) [030-0276-0101_A](#) [QC-DB-](#)
[U10006](#) [DP-VIP-I-EVN](#) [USB3-VIP-EVN](#) [CS-DEPTHAI-05](#) [CS-DEPTHAI-06](#) [MCIMXCAMERA1MP](#) [MINISASTOCSI](#)
[MX8XMIPI4CAM2](#) [PIM365](#) [PIM366](#) [S32V-SONYCAM](#) [110991190](#) [114991702](#) [114992261](#) [114992262](#) [114992263](#) [114992264](#)
[114992265](#) [CXD5602PWBCAM1_FG_875607605_P](#) [CXD5602PWBCAM1C_FG_875607606_P](#) [CXD5602PWBCAM1E_FG_875607607_P](#)
[SEN-15570](#) [STPI2-CAMKIT-01](#)