


LN06N060TZHG

60V N-Channel (D-S) MOSFET



1. FEATURES


- Low thermal impedance.
- Fast switching speed.
- We declare that the material of product compliance with RoHS requirements and Halogen Free.

2. APPLICATIONS

- Load/Power switch for portables and computing
- DC-DC conversion

3. DEVICE MARKING AND ORDERING INFORMATION

Device	Marking	Shipping
LN06N060TZHG	GS	1000/Tape&Reel



4. MAXIMUM RATINGS(Ta = 25°C)

Parameter	Symbol	Limits	Unit
Drain-Source Voltage	VDS	60	V
Gate-Source Voltage	VGS	± 20	
Continuous Drain Current (Note 1)	ID	4.5	A
Pulsed Drain Current (Note 2)	IDM	18	
Avalanche Current (L = 0.1mH)	IAS	12	A
Avalanche Energy (L = 0.1mH)	EAS	7.2	mJ
Power Dissipation (Note 1)	PD	2	W
Operating Junction and Storage Temperature Range	TJ , Tstg	-55~+150	°C

5. THERMAL CHARACTERISTICS

Parameter	Symbol	Limits	Unit
Thermal Resistance,Junction-to-Ambient(Note 1)	RθJA	60	°C/W
Thermal Resistance,Junction-to-Case	RθJC	10	°C/W

1."1.5 x 1.5" FR4 board using 1 sq in pad, 2 oz Cu.





2.Pulse width limited by maximum junction temperature

6. ELECTRICAL CHARACTERISTICS (Ta= 25°C)





Characteristic	Symbol	Min.	Typ.	Max.	Unit
Static					
Drain–Source Breakdown Voltage (VGS = 0 V, ID = 250 μA)	VBRDSS	60	-	-	V
Gate-Source Threshold Voltage (VDS = VGS, ID = 250 μA)	VGS(th)	1.0	2.0	3.0	V
Gate-Body Leakage Current (VDS = 0 V, VGS = ± 20 V)	IGSS	-	-	± 100	nA
Zero Gate Voltage Drain Current (VDS = 60 V, VGS = 0 V)	IDSS	-	-	1	uA
Drain-Source On-Resistance(Note 3) (VGS = 10 V, ID = 3 A) (VGS = 5 V, ID = 2 A)	RDS(ON)	-	-	60 75	mΩ
Diode Forward Voltage (IS = 1 A, VGS = 0 V)	VSD	-	-	1.2	V
Dynamic					
Total Gate Charge	(VDS = 30 V, ID = 3 A, VGS = 10 V)	Qg	-	12.7	nC
Gate-Source Charge		Qgs	-	2.3	
Gate-Drain Charge		Qgd	-	3.6	
Input Capacitance	(VGS = 0 V, VDS = 30 V, f= 1MHz)	Ciss	-	743	pF
Output Capacitance		Coss	-	38	
Reverse Transfer Capacitance		Crss	-	26	
Turn-On Delay Time	(VDS = 30 V, RL = 30 Ω, ID = 1 A, VGS = 10 V, RG = 6.2 Ω)	td(on)	-	8.1	ns
Rise Time		tr	-	4.2	
Turn-Off Delay Time		td(off)	-	26.4	
Fall Time		tf	-	5.2	

3.Pulse test: PW ≤ 300us duty cycle ≤ 2%.



7. ELECTRICAL CHARACTERISTICS CURVES



7. ELECTRICAL CHARACTERISTICS CURVES(Con.)




7. ELECTRICAL CHARACTERISTICS CURVES(Con.)



8.OUTLINE AND DIMENSIONS

SOT223




SOT223			
DIM	MIN	NOR	MAX
A	1.50	1.60	1.70
A1	0.00	0.05	0.10
A2	0.80	0.90	1.00
b1	2.90	3.02	3.10
b2	0.60	0.72	0.80
c	0.20	0.27	0.35
D	6.30	6.50	6.70
E	3.30	3.50	3.70
e	4.60BSC		
e1	2.30BSC		
HE	6.80	7.00	7.20
L	0.80	1.00	1.20
L1	1.75(REF)		
θ	0°~8°		
$\theta 1$	8°	10°	12°
All Dimensions in mm			

GENERAL NOTES

1. Top package surface finish $Ra0.4 \pm 0.2\mu m$
2. Bottom package surface finish $Ra0.7 \pm 0.2\mu m$
3. Side package surface finish $Ra0.4 \pm 0.2\mu m$
4. Protrusion or Gate Burrs shall not exceed 0.10mm per side.

9.SOLDERING FOOTPRINT



SOT223	
DIM	(mm)
X1	3.80
Y1	2.00
X2	1.20
Y2	2.00
C1	2.30
C2	6.30

DISCLAIMER

- Curve guarantee in the specification. The curve of test items with electric parameter is used as quality guarantee. The curve of test items without electric parameter is used as reference only.
- Before you use our Products for new Project, you are requested to carefully read this document and fully understand its contents. LRC shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any LRC's Products against warning, caution or note contained in this document.
- All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using LRC's Products, please confirm the latest information with a LRC sales representative.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [Leshan](#) manufacturer:

Other Similar products are found below :

[IRFD120](#) [JANTX2N5237](#) [BUK455-60A/B](#) [MIC4420CM-TR](#) [VN1206L](#) [NDP4060](#) [SI4482DY](#) [IPS70R2K0CEAKMA1](#) [SQD23N06-31L-GE3](#)
[TK16J60W,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [DMN1053UCP4-7](#) [SQJ469EP-T1-GE3](#) [NTE2384](#) [DMC2700UDMQ-7](#)
[DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [DMP22D4UFO-7B](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)
[STF5N65M6](#) [IRF40H233XTMA1](#) [STU5N65M6](#) [DMN6022SSD-13](#) [DMN13M9UCA6-7](#) [DMTH10H4M6SPS-13](#) [DMN2990UFB-7B](#)
[IPB80P04P405ATMA2](#) [2N7002W-G](#) [MCAC30N06Y-TP](#) [MCQ7328-TP](#) [NTMC083NP10M5L](#) [BXP7N65D](#) [BXP4N65F](#) [AOL1454G](#)
[WMJ80N60C4](#) [BXP2N20L](#) [BXP2N65D](#) [BXT1150N10J](#) [BXT1700P06M](#) [TSM60NB380CP](#) [ROG](#) [RQ7L055BGTGR](#) [DMNH15H110SK3-13](#)
[SLF10N65ABV2](#) [BSO203SP](#) [BSO211P](#) [IPA60R230P6](#)