

## 20V N-Channel Enhancement-Mode MOSFET

### ● APPLICATIONS

- 1) High Density Cell Design For Ultra Low On-Resistance  
Improved Shoot-Through FOM
- 2) We declare that the material of product compliant with RoHS requirements and Halogen Free

### ● FEATURES

- V<sub>DS</sub> = 20V
- R<sub>DS(ON)</sub>, V<sub>GS</sub>@4.5V, I<sub>DS</sub>@2.8A = 60mΩ
- R<sub>DS(ON)</sub>, V<sub>GS</sub>@2.5V, I<sub>DS</sub>@2.0A = 115mΩ

### ● DEVICE MARKING AND ORDERING INFORMATION



Device	Marking	Shipping
LN2302LT1G	N02	3000/Tape&Reel
LN2302LT3G	N02	10000/Tape&Reel

### ● MAXIMUM RATINGS(T<sub>a</sub> = 25°C)

Parameter	Symbol	Limits	Unit
Drain-to-Source Voltage	V <sub>DSS</sub>	20	V
Gate-to-Source Voltage	V <sub>GS</sub>	±8	V
Continuous Drain Current	I <sub>D</sub>	2.3	A
Pulsed Drain Current (Note1)	I <sub>DM</sub>	8	A
Maximum Power Dissipation	P <sub>D</sub>	T <sub>A</sub> = 25°C	0.9
		T <sub>A</sub> = 75°C	0.57
Operating and Storage Temperature Range	T <sub>J</sub> , T <sub>stg</sub>	-55 to +150	°C
Junction to Ambient Thermal Resistance(PCB mounted)(Note 2)	R <sub>θJA</sub>	145	°C/W

1. Repetitive Rating: Pulse width limited by the Maximum junction temperature
2. 1-in2 2oz Cu PCB board

### LN2302LT1G



# LN2302LT1G



● ELECTRICAL CHARACTERISTICS (Ta= 25°C)  
STATIC

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Drain-to-Source Breakdown Voltage	V(BR)DSS	20	–	–	V	VGS = 0 V, ID = 250 μA
Gate Threshold Voltage	VGS(TH)	0.6	0.95	1.2	V	VGS = VDS, ID = 250 μA
Zero Gate Voltage Drain Current	IDSS	–	–	-1	μA	VDS=9.6V, VGS=0V
Gate-to-Source Leakage Current	IGSS	–	–	±100	nA	VDS = 0 V, VGS = ±8 V
Drain-to-Source On Resistance	RDS(on)	–	40	60	mΩ	VGS = 4.5 V, ID = 2.8 A
		–	50	115	mΩ	VGS = 2.5 V, ID = 2 A
Forward Diode Voltage	VSD			1.2	V	VGS = 0 V, ISD = -1.6A
Forward Transconductance	gFS	–	6.5	–	S	VDS = 5.0 V, ID = 4 A

DYNAMIC(Note 3)

Input Capacitance	Ciss	–	427.12	–	pF	VGS = 0 V, f = 1.0 MHz, VDS= 6 V
Output Capacitance	Coss	–	80.56	–		
Reverse Transfer Capacitance	Crss	–	57.00	–		
Total Gate Charge	QG	–	3.69	–	nC	VGS = 4.5 V, VDS = 6 V ID = 2.8 A
Gate-to-Source Gate Charge	QGS	–	0.70	–		
Gate-to-Drain Charge	QGD	–	1.06	–		
Turn-On Delay Time	td(on)	–	6.16	–	ns	VDD = 6V, RL = 6 Ω ID = 1A, VGEN = 4.5V RG = 6 Ω
Rise Time	tr	–	7.56	–		
Turn-Off Delay Time	td(off)	–	16.61	–		
Fall Time	tf	–	4.07	–		

3. Pulse test: pulse width ≅ 300us, duty cycle ≅ 2%



# LN2302LT1G

## ELECTRICAL CHARACTERISTIC CURVES




FIG.1 Transfer Characteristics




FIG.2 On-Region Characteristics




FIG.3 On-Resistance vs. Drain Current




FIG.4 On-Resistance vs. Gate-to-Source Voltage



**LN2302LT1G****ELECTRICAL CHARACTERISTIC CURVES**

FIG.7 On-Resistance vs. Junction Temperature


FIG.8  $V_{TH}$  vs. Junction Temperature

# LN2302LT1G


## SOT-23

NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M,1982
2. CONTROLLING DIMENSION: INCH.



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.1102	0.1197	2.80	3.04
B	0.0472	0.0551	1.20	1.40
C	0.0350	0.0440	0.89	1.11
D	0.0150	0.0200	0.37	0.50
G	0.0701	0.0807	1.78	2.04
H	0.0005	0.0040	0.013	0.100
J	0.0034	0.0070	0.085	0.177
K	0.0140	0.0285	0.35	0.69
L	0.0350	0.0401	0.89	1.02
S	0.0830	0.1039	2.10	2.64
V	0.0177	0.0236	0.45	0.60



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [MOSFET](#) category:*

*Click to view products by [Leshan](#) manufacturer:*

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [NTNS3A92PZT5G](#) [IRFD120](#) [IRFF430](#) [JANTX2N5237](#) [2N7000](#)  
[2SK2464-TL-E](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [2SK2267\(Q\)](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#)  
[715780A](#) [SSM6J414TU,LF\(T](#) [751625C](#) [PSMN4R2-30MLD](#) [TK31J60W5,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#)  
[EFC2J004NUZTDG](#) [FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE2384](#) [NTE2969](#) [NTE6400A](#) [DMN61D9UWQ-13](#)  
[US6M2GTR](#) [DMN31D5UDJ-7](#) [SSM6P54TU,LF](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#)  
[STF5N65M6](#) [STU5N65M6](#) [C3M0021120D](#) [DMN13M9UCA6-7](#) [BSS340NWH6327XTSA1](#) [MCM3400A-TP](#) [DMTH10H4M6SPS-13](#)  
[IPS60R1K0PFD7SAKMA1](#)