



LN2306LT1G

S-LN2306LT1G

30V N-Channel Enhancement-Mode MOSFET

1. FEATURES

- $V_{DS} = 30V$
- $R_{DS(ON)}, V_{GS}@10V, I_{DS}@5.8A = 38m\Omega$
- $R_{DS(ON)}, V_{GS}@4.5V, I_{DS}@5.0A = 43m\Omega$
- $R_{DS(ON)}, V_{GS}@2.5V, I_{DS}@4.0A = 62m\Omega$
- We declare that the material of product compliance with RoHS requirements and Halogen Free.
- S- prefix for automotive and other applications requiring unique site and control change requirements; AEC-Q101 qualified and PPAP capable.



2. APPLICATIONS

- Advanced trench process technology
- High density cell design for ultra low on-resistance

3. DEVICE MARKING AND ORDERING INFORMATION

Device	Marking	Shipping
LN2306LT1G	N06	3000/Tape&Reel
LN2306LT3G	N06	10000/Tape&Reel

4. MAXIMUM RATINGS($T_a = 25^\circ C$)

Parameter	Symbol	Limits	Unit
Drain-Source Voltage	V_{DSS}	30	V
Gate-to-Source Voltage – Continuous	V_{GS}	± 12	V
Drain Current			A
– Continuous $T_A = 25^\circ C$	I_D	5.8	
– Pulsed(Note 1)	I_{DM}	30	

5. THERMAL CHARACTERISTICS

Parameter	Symbol	Limits	Unit
Maximum Power Dissipation	PD	1.4	W
Thermal Resistance, Junction-to-Ambient(Note 2)	$R_{\theta JA}$	140	$^\circ C/W$
Junction and Storage temperature	T_J, T_{stg}	$-55 \sim +150$	$^\circ C$

1. Repetitive Rating: Pulse width limited by the Maximum junction temperature.
2. 1-in² 2oz Cu PCB board.

6. ELECTRICAL CHARACTERISTICS (Ta= 25°C)
OFF CHARACTERISTICS

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Drain–Source Breakdown Voltage (VGS = 0, ID = 250μAdc)	V(BR)DSS	30	-	-	Vdc
Zero Gate Voltage Drain Current (VDS=9.6V, VGS=0V)	IDSS	-	-	1	μAdc
Gate–Body Leakage Current, Forward (VDS = 0 V, VGS = 8 V)	IGSSF	-	-	100	nAdc
Gate–Body Leakage Current, Reverse (VDS = 0 V, VGS = -8 V)	IGSSR	-	-	-100	nAdc
Forward Transconductance (VDS = 5.0 V, ID = 5 A)	gfs	10	15	-	S

ON CHARACTERISTICS (Note 3)

Gate Threshold Voltage (VDS = VGS, ID = 250μAdc)	VGS(th)	0.7	-	1.4	Vdc
Static Drain–Source On–State Resistance (VGS = 10 V, ID =5.8 A) (VGS = 4.5 V, ID =5 A) (VGS = 2.5 V, ID = 4 A)	RDS(on)	- - -	31 34 45	38 43 62	mΩ

DYNAMIC CHARACTERISTICS

Input Capacitance (VGS = 0 V, f = 1.0MHz, VDS= 15 V)	Ciss	-	513.51	-	pF
Output Capacitance (VGS = 0 V, f = 1.0MHz, VDS= 15 V)	Coss	-	80.85	-	pF
Reverse Transfer Capacitance (VGS = 0 V, f = 1.0MHz, VDS= 15 V)	Crss	-	54.87	-	pF

SWITCHING CHARACTERISTICS





Turn-On Delay Time	(VDD = 15V, RL = 2.7Ω ID = 1A, VGEN = 10V, RG = 3Ω)	td(on)	-	7	14	ns
Rise Time		tr	-	15	30	
Turn-Off Delay Time		td(off)	-	38	76	
Fall Time		tf	-	3	6	


SOURCE–DRAIN DIODE CHARACTERISTICS

Forward Voltage (VGS = 0 Vdc, ISD = 1 Adc)	VSD	-	-	1.2	V
---	-----	---	---	-----	---

3.Pulse Test: Pulse Width ≤300 μs, Duty Cycle ≤2.0%.

7. ELECTRICAL CHARACTERISTICS CURVES




7. ELECTRICAL CHARACTERISTICS CURVES (Con.)**RDS(on) vs. VGS**

8.OUTLINE AND DIMENSIONS


Notes:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.



DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.89	1	1.11	0.035	0.04	0.044
A1	0.01	0.06	0.1	0.001	0.002	0.004
b	0.37	0.44	0.5	0.015	0.018	0.02
c	0.09	0.13	0.18	0.003	0.005	0.007
D	2.80	2.9	3.04	0.11	0.114	0.12
E	1.20	1.3	1.4	0.047	0.051	0.055
e	1.78	1.9	2.04	0.07	0.075	0.081
L	0.10	0.2	0.3	0.004	0.008	0.012
L1	0.35	0.54	0.69	0.014	0.021	0.029
HE	2.10	2.4	2.64	0.083	0.094	0.104
θ	0°	---	10°	0°	---	10°

9.SOLDERING FOOTPRINT



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [Leshan](#) manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [FDPF9N50NZ](#) [IRFD120](#) [IRFF430](#) [JANTX2N5237](#) [2N7000](#) [FCA20N60_F109](#) [FDZ595PZ](#) [2SK2267\(Q\)](#) [2SK2545\(Q,T\)](#)
[405094E](#) [423220D](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [SSM6J414TU,LF\(T](#) [751625C](#) [PSMN4R2-30MLD](#)
[TK31J60W5,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#) [EFC2J004NUZTDG](#) [FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#)
[NTE2384](#) [NTE2969](#) [NTE6400A](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [SSM6P54TU,LF](#) [DMP22D4UFO-7B](#)
[IPS60R3K4CEAKMA1](#) [DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#) [STU5N65M6](#) [C3M0021120D](#) [DMN13M9UCA6-7](#)
[BSS340NWH6327XTSA1](#) [MCM3400A-TP](#) [DMTH10H4M6SPS-13](#) [IPS60R1K0PFD7SAKMA1](#) [IPS60R360PFD7SAKMA1](#)
[IPS60R600PFD7SAKMA1](#) [IPS60R210PFD7SAKMA1](#) [DMN2990UFB-7B](#)