


LNA2306LT1G

S-LNA2306LT1G

30V N-Channel Enhancement-Mode MOSFET


1. FEATURES

- $V_{DS} = 30V$
- $R_{DS(ON)}, V_{GS}@10V, I_{DS}@5.8A = 38m\Omega$
- $R_{DS(ON)}, V_{GS}@4.5V, I_{DS}@5.0A = 43m\Omega$
- $R_{DS(ON)}, V_{GS}@2.5V, I_{DS}@4.0A = 62m\Omega$
- We declare that the material of product compliance with RoHS requirements and Halogen Free.
- S- prefix for automotive and other applications requiring unique site and control change requirements; AEC-Q101 qualified and PPAP capable.



2. APPLICATIONS

- Advanced trench process technology
- High density cell design for ultra low on-resistance



3. DEVICE MARKING AND ORDERING INFORMATION

Device	Marking	Shipping
LNA2306LT1G	A06	3000/Tape&Reel
LNA2306LT3G	A06	10000/Tape&Reel

4. MAXIMUM RATINGS($T_a = 25^\circ C$)

Parameter	Symbol	Limits	Unit
Drain-Source Voltage	V_{DSS}	30	V
Gate-to-Source Voltage – Continuous	V_{GS}	± 12	V
Drain Current			A
– Continuous $T_A = 25^\circ C$	I_D	5.8	
– Pulsed(Note 1)	I_{DM}	30	

5. THERMAL CHARACTERISTICS

Parameter	Symbol	Limits	Unit
Maximum Power Dissipation	PD	1.4	W
Thermal Resistance, Junction-to-Ambient(Note 2)	$R_{\theta JA}$	140	$^\circ C/W$
Junction and Storage temperature	T_J, T_{stg}	$-55 \sim +150$	$^\circ C$

1. Repetitive Rating: Pulse width limited by the Maximum junction temperature.
2. 1-in² 2oz Cu PCB board.

6. ELECTRICAL CHARACTERISTICS (Ta= 25°C)
OFF CHARACTERISTICS

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Drain–Source Breakdown Voltage (VGS = 0, ID = 250μA)	V(BR)DSS	30	-	-	V
Zero Gate Voltage Drain Current (VDS=24V, VGS=0V)	IDSS	-	-	1	μA
Gate–Body Leakage Current, Forward (VDS = 0 V, VGS = 8 V)	IGSSF	-	-	100	nA
Gate–Body Leakage Current, Reverse (VDS = 0 V, VGS = -8 V)	IGSSR	-	-	-100	nA
Forward Transconductance (VDS = 5.0 V, ID = 5 A)	gfs	10	15	-	S

ON CHARACTERISTICS (Note 3)

Gate Threshold Voltage (VDS = VGS, ID = 250μA)	VGS(th)	0.7	-	1.4	V
Static Drain–Source On–State Resistance (VGS = 10 V, ID =5.8 A) (VGS = 4.5 V, ID =5 A) (VGS = 2.5 V, ID = 4 A)	RDS(on)	- - -	31 34 45	38 43 62	mΩ

DYNAMIC CHARACTERISTICS

Input Capacitance (VGS = 0 V, f = 1.0MHz, VDS= 15 V)	Ciss	-	496	-	pF
Output Capacitance (VGS = 0 V, f = 1.0MHz, VDS= 15 V)	Coss	-	50	-	pF
Reverse Transfer Capacitance (VGS = 0 V, f = 1.0MHz, VDS= 15 V)	Crss	-	42	-	pF

SWITCHING CHARACTERISTICS





Turn-On Delay Time	(VDD = 15V, RL = 2.55Ω ID = 1A, VGEN = 10V, RG = 3.1Ω)	td(on)	-	5	-	ns
Rise Time		tr	-	5	-	
Turn-Off Delay Time		td(off)	-	72	-	
Fall Time		tf	-	28	-	


SOURCE–DRAIN DIODE CHARACTERISTICS

Forward Voltage (VGS = 0 V, IF = 1 A)	VSD	-	-	1.2	V
--	-----	---	---	-----	---

3.Pulse Test: Pulse Width ≤300 μs, Duty Cycle ≤2.0%.

7. ELECTRICAL CHARACTERISTICS CURVES






7. ELECTRICAL CHARACTERISTICS CURVES (Con.)

RDS(on) vs. VGS

8. OUTLINE AND DIMENSIONS

SOT23E




SOT23E			
DIM	MIN	NOR	MAX
A	0.90	1.00	1.10
A1	0.01	0.06	0.10
b	0.30	0.40	0.50
c	0.10	0.15	0.20
D	2.80	2.90	3.00
E	1.20	1.30	1.40
e	1.80	1.90	2.00
L	0.20	0.40	0.60
L1	0.45	0.55	0.65
HE	2.20	2.40	2.60
θ	0°	-	10°
All Dimensions in mm			

GENERAL NOTES

1. Top package surface finish $Ra0.4 \pm 0.2\mu m$
2. Bottom package surface finish $Ra0.7 \pm 0.2\mu m$
3. Side package surface finish $Ra0.4 \pm 0.2\mu m$

9. SOLDERING FOOTPRINT



SOT23E	
DIM	(mm)
X	0.80
Y	0.90
A	2.00
B	0.95
C	0.95

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [MOSFET](#) category:

Click to view products by [Leshan](#) manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [FW216A-TL-2W](#) [FW231A-TL-E](#) [APT5010JVR](#) [NTNS3A92PZT5G](#)
[IRF100S201](#) [JANTX2N5237](#) [2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FSS804-TL-E](#) [2SJ277-DL-E](#)
[2SK1691-DL-E](#) [2SK2545\(Q,T\)](#) [D2294UK](#) [405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#) [367-8430-0972-503](#) [VN1206L](#)
[424134F](#) [026935X](#) [051075F](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#) [IRF7380TRHR](#)
[IPS70R2K0CEAKMA1](#) [RJK60S3DPP-E0#T2](#) [RJK60S5DPK-M0#T0](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [DMN3404LQ-7](#)
[NTE6400](#) [JANTX2N6796U](#) [JANTX2N6784U](#) [JANTXV2N5416U4](#) [SQM110N05-06L-GE3](#) [SIHF35N60E-GE3](#)