


LP3418DT2AG

30V P-Channel (D-S) MOSFET


1. FEATURES

- VDS = -30V
RDS(ON)≤25mΩ ,VGS@-10V,IDS@-7.3A
- RDS(ON)≤38mΩ,VGS@-4.5V,IDS@-5.9A
- Low RDS(ON) trench technology.
- Low thermal impedance.
- Fast switching speed.
- We declare that the material of product compliance with RoHS requirements and Halogen Free.



2. APPLICATIONS

- Load Switches
- DC/DC Conversion
- Motor Drives



3. DEVICE MARKING AND ORDERING INFORMATION

Device	Marking	Shipping
LP3418DT2AG	3B1	4000/Tape&Reel

4. MAXIMUM RATINGS(Ta = 25°C)

Parameter		Symbol	Limits	Unit
Drain-Source Voltage		VDS	-30	V
Gate-Source Voltage		VGS	± 20	
Continuous Drain Current(Note 1)		ID	-9.4	A
Pulsed Drain Current(Note 2)		IDM	-40	
Maximum Power Dissipation(Note 1)	TA = 25°C	PD	3.1	W
	TA = 70°C		2	
Operating Junction and Storage Temperature Range		TJ , Tstg	-50~+150	°C
Continuous Source Current (Diode Conduction)(Note 1)		IS	3.8	A

Note: 1. Surface Mounted on 1" x 1" FR4 Board.

2. Pulse width limited by maximum junction temperature.

5. THERMAL CHARACTERISTICS

Parameter		Symbol	Max	Unit
Maximum Junction-to-Ambient (Note 1)	t≤10S	RθJA	40	°C/W
	Steady State		90	





6. ELECTRICAL CHARACTERISTICS (Ta= 25°C)

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Static					
Drain-Source Breakdown Voltage (VGS =0V, ID =-250μA)	V(BR)DSS	-30	-	-	V
Gate Threshold Voltage (VDS =VGS , ID =-250μA)	VGS(th)	-1	-	-3	V
Gate Leakage Current (VDS =0V, VGS =±20V)	IGSS	-	-	±100	nA
Zero Gate Voltage Drain Current (VDS =-24V, VGS =0V)	IDSS	-	-	-1	μA
On-State Drain Current(Note 3) (VDS = -5 V, VGS = -10 V)	ID(on)	-14	-	-	A
Drain-Source On-Resistance (VGS =-10V, ID = -7.3A)	RDS(ON) (Note 3)	-	-	25	mΩ
Drain-Source On-Resistance (VGS =-4.5V, ID = -5.9A)		-	-	38	
Diode Forward Voltage(Note 3) (IS =-1A, VGS =0V)	VSD	-	-	-1.5	V
Forward Transconductance(Note 3) (VDS = -15 V, ID = -7.3 A)	gfs	-	10	-	S
DYNAMIC(Note 4)					
Total Gate Charge	(VDS = -15 V, VGS = -4.5 V, ID = -7.3 A)	Qg	-	11.2	-
Gate-Source Charge		Qgs	-	2.8	-
Gate-Drain Charge		Qgd	-	4.2	-
Input Capacitance	(VDS = -15 V, VGS = 0 V, f = 1 MHz)	Ciss	-	1370	-
Output Capacitance		Coss	-	133	-
Reverse Transfer Capacitance		Crss	-	112	-
Turn-On Delay Time	(VDS = -15 V, RL =2.1 Ω, ID = -7.3 A, VGEN = -10 V, RGEN = 6 Ω)	td(on)	-	6	-
Turn-On Rise Time		tr	-	5	-
Turn-Off Delay Time		td(off)	-	55	-
Turn-Off Fall Time		tf	-	21	-





Note: 3. Pulse test; pulse width≤ 300us, duty cycle≤ 2%.

4. Guaranteed by design, not subject to production testing.


7. ELECTRICAL CHARACTERISTICS CURVES



7. ELECTRICAL CHARACTERISTICS CURVES(Con.)




8.OUTLINE AND DIMENSIONS



DFN2020-6S			
DIM	MIN	NOR	MAX
A	0.60	0.65	0.70
A1	0.01	0.03	0.05
b	0.25	0.30	0.35
D	1.95	2.00	2.05
E	1.95	2.00	2.05
e	0.65TYP.		
L	0.23	0.28	0.33
L1	0.60	0.65	0.65
D1	0.90	0.95	1.00
E1	1.10	1.15	1.20
A3	0.152REF		

All Dimensions in mm

9.SOLDERING FOOTPRINT



DFN2020-6S	
Dim	(mm)
X	0.40
X1	0.95
X2	1.70
e	0.65
Y	0.43
Y1	0.75
Y2	1.15
Y3	1.54
Y4	2.39

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for MOSFET category:

Click to view products by Leshan manufacturer:

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [NTNS3A92PZT5G](#) [IRFD120](#) [IRFF430](#) [JANTX2N5237](#) [2N7000](#)
[AOD464](#) [2SK2267\(Q\)](#) [2SK2545\(Q,T\)](#) [405094E](#) [423220D](#) [MIC4420CM-TR](#) [VN1206L](#) [614234A](#) [715780A](#) [SSM6J414TU,LF\(T](#) [751625C](#)
[IPS70R2K0CEAKMA1](#) [BSF024N03LT3 G](#) [PSMN4R2-30MLD](#) [TK31J60W5,S1VQ\(O](#) [2SK2614\(TE16L1,Q\)](#) [DMN1017UCP3-7](#)
[EFC2J004NUZTDG](#) [FCAB21350L1](#) [P85W28HP2F-7071](#) [DMN1053UCP4-7](#) [NTE2384](#) [NTE2969](#) [NTE6400A](#) [DMC2700UDMQ-7](#)
[DMN2080UCB4-7](#) [DMN61D9UWQ-13](#) [US6M2GTR](#) [DMN31D5UDJ-7](#) [SSM6P54TU,LF](#) [DMP22D4UFO-7B](#) [IPS60R3K4CEAKMA1](#)
[DMN1006UCA6-7](#) [DMN16M9UCA6-7](#) [STF5N65M6](#) [IRF40H233XTMA1](#) [IPSA70R950CEAKMA1](#) [IPSA70R2K0CEAKMA1](#) [STU5N65M6](#)
[C3M0021120D](#)