



# LBSS84LT1G

## S-LBSS84LT1G

Power MOSFET  
130 mA, 50V P-Channel SOT-23

### 1. FEATURES

- We declare that the material of product compliance with RoHS requirements and Halogen Free.
- S- prefix for automotive and other applications requiring unique site and control change requirements; AEC-Q101 qualified and PPAP capable.
- Energy efficient



### 2. DEVICE MARKING AND ORDERING INFORMATION

Device	Marking	Shipping
LBSS84LT1G	PD	3000/Tape&Reel
LBSS84LT3G	PD	10000/Tape&Reel

### 3. MAXIMUM RATINGS( $T_a = 25^\circ\text{C}$ )

Parameter	Symbol	Limits	Unit
Drain–Source Voltage	VDSS	-50	V
Gate-to-Source Voltage – Continuous	VGS	$\pm 20$	V
Drain Current			mA
– Continuous $T_A = 25^\circ\text{C}$	ID	-130	
– Pulsed ( $t_p \leq 10\mu\text{s}$ )	IDM	-520	

### 4. THERMAL CHARACTERISTICS

Parameter	Symbol	Limits	Unit
Total Device Dissipation, FR-5 Board (Note 1) @ $T_A = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	PD	225 1.8	mW mW/ $^\circ\text{C}$
Thermal Resistance, Junction-to-Ambient(Note 1)	R $\Theta$ JA	556	$^\circ\text{C}/\text{W}$
Junction and Storage temperature	T <sub>J,Tstg</sub>	-55~+150	$^\circ\text{C}$
Maximum Lead Temperature for Soldering Purposes, for 10 seconds	TL	260	$^\circ\text{C}$

1. FR-5 = 1.0×0.75×0.062 in.

## 5. ELECTRICAL CHARACTERISTICS (Ta= 25°C)

### OFF CHARACTERISTICS

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Drain–Source Breakdown Voltage (VGS = 0, ID = -250µA)	VBRDSS	-50	-	-	V
Zero Gate Voltage Drain Current (VGS = 0, VDS = -25 V) (VGS = 0, VDS = -50 V) (VGS = 0, VDS = -50 V, TJ=125°C)	IDSS	-	-	-0.1	µA
		-	-	-15	
		-	-	-60	
Gate–Body Leakage Current, Forward (VGS = 20V)	IGSSF	-	-	10	µA
Gate–Body Leakage Current, Reverse (VGS = - 20V)	IGSSR	-	-	-10	µA

### ON CHARACTERISTICS (Note 2)

Gate Threshold Voltage (VDS = VGS, ID = -250µA)	VGS(th)	-0.8	-	-2	V
Static Drain–Source On–State Resistance (VGS = -5.0 V, ID = -100 mA) (VGS = -10 V, ID = -100 mA)	RDS(on)	-	2	6	Ω
Transfer Admittance (VDS = -25 V, ID = -100 mA, f = 1.0 kHz)	yfs	50	-	-	mS

### DYNAMIC CHARACTERISTICS

Input Capacitance (VDS = - 15V,VGS=0V,f=1MHz)	Ciss	-	38	-	pF
Output Capacitance (VDS = - 15V,VGS=0V,f=1MHz)	Coss	-	4.8	-	pF
Reverse Transfer Capacitance (VDS = - 15V,VGS=0V,f=1MHz)	Crss	-	2.7	-	pF

### SWITCHING CHARACTERISTICS





Turn-On Delay Time	(VDS = -15 V, VGS=-10V ,RL = 50Ω, RG=25Ω)	td(on)	-	16.7	-	ns
Rise Time		tr	-	8.6	-	
Turn-Off Delay Time		td(off)	-	17.9	-	
Fall Time		tf	-	5.3	-	

### SOURCE–DRAIN DIODE CHARACTERISTICS




Continuous Current	IS	-	-	-0.13	A
Pulsed Current	ISM	-	-	-0.52	A
Forward Voltage	VSD	-	-2.5	-	V

2.Pulse Test: Pulse Width ≤300 µs, Duty Cycle ≤2.0%.


## 6. ELECTRICAL CHARACTERISTICS CURVES



## 6. ELECTRICAL CHARACTERISTICS CURVES(Con.)



## 7. OUTLINE AND DIMENSIONS




Notes:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.

DIM	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	0.89	1	1.11	0.035	0.04	0.044
A1	0.01	0.06	0.1	0.001	0.002	0.004
b	0.37	0.44	0.5	0.015	0.018	0.02
c	0.09	0.13	0.18	0.003	0.005	0.007
D	2.80	2.9	3.04	0.11	0.114	0.12
E	1.20	1.3	1.4	0.047	0.051	0.055
e	1.78	1.9	2.04	0.07	0.075	0.081
L	0.10	0.2	0.3	0.004	0.008	0.012
L1	0.35	0.54	0.69	0.014	0.021	0.029
H <sub>E</sub>	2.10	2.4	2.64	0.083	0.094	0.104
θ	0°	---	10°	0°	---	10°

## 8. SOLDERING FOOTPRINT



# X-ON Electronics

Largest Supplier of Electrical and Electronic Components

***Click to view similar products for MOSFET category:***

***Click to view products by Leshan manufacturer:***

Other Similar products are found below :

[614233C](#) [648584F](#) [MCH3443-TL-E](#) [MCH6422-TL-E](#) [FDPF9N50NZ](#) [FW216A-TL-2W](#) [FW231A-TL-E](#) [APT5010JVR](#) [NTNS3A92PZT5G](#)  
[IRF100S201](#) [JANTX2N5237](#) [2SK2464-TL-E](#) [2SK3818-DL-E](#) [FCA20N60\\_F109](#) [FDZ595PZ](#) [STD6600NT4G](#) [FSS804-TL-E](#) [2SJ277-DL-E](#)  
[2SK1691-DL-E](#) [2SK2545\(Q,T\)](#) [D2294UK](#) [405094E](#) [423220D](#) [MCH6646-TL-E](#) [TPCC8103,L1Q\(CM](#) [367-8430-0972-503](#) [VN1206L](#)  
[424134F](#) [026935X](#) [051075F](#) [SBVS138LT1G](#) [614234A](#) [715780A](#) [NTNS3166NZT5G](#) [751625C](#) [873612G](#) [IRF7380TRHR](#)  
[IPS70R2K0CEAKMA1](#) [RJK60S3DPP-E0#T2](#) [RJK60S5DPK-M0#T0](#) [APT5010JVFR](#) [APT12031JFLL](#) [APT12040JVR](#) [DMN3404LQ-7](#)  
[NTE6400](#) [JANTX2N6796U](#) [JANTX2N6784U](#) [JANTXV2N5416U4](#) [SQM110N05-06L-GE3](#) [SIHF35N60E-GE3](#)