


SOD-323


Features

- ✧ Wide zener voltage range selection: 2.4V to 75V .
- ✧ VZ Tolerance selection of $\pm 2\%$ (B series).
- ✧ Ideally suited for automated assembly processes.
- ✧ Moisture sensitivity level 1.

Applications

- ✧ Zener diode.
- ✧ Ultra-small surface mount package.

Dimensions in inches and (millimeters)

Ordering Information

Type No.	Marking	Package Code
BZT52C2V4S-BZT52C39S	See table 2	SOD-323

MAXIMUM RATING @ Ta=25°C unless otherwise specified

Characteristic	Symbol	Value	Unit
Forward Voltage @ I _F =10mA	V _F	1	V
Power Dissipation	P _d	200	mW
Thermal resistance, junction to ambient air	R _{θJA}	625	°C/W
Junction temperature	T _j	150	°C
Storage temperature range	T _{stg}	-65 to +150	°C

Notes: These ratings are limiting values above which the serviceability of the diodes may be impaired.

ELECTRICAL CHARACTERISTICS @ Ta=25°C unless otherwise specified

Type Number	Marking Code	Zener Voltage Range				Maximum Zener Impedance			Maximum Reverse Current	
		V _Z @I _{ZT}			I _{ZT}	Z _{ZT} @I _{ZT}	I _{ZK}	Z _{ZK} @I _{ZK}	I _R	@V _R
		Nom(V)	Min(V)	Max(V)	mA	Ω	mA	Ω	μA	V
BZT52B2V4S	0Z	2.4	2.35	2.45	5	94	1	564	45	1
BZT52B2V7S	1Z	2.7	2.65	2.75	5	94	1	564	18	1
BZT52B3V0S	2Z	3.0	2.94	3.06	5	89	1	564	9	1
BZT52B3V3S	3Z	3.3	3.23	3.37	5	89	1	564	4.5	1
BZT52B3V6S	4Z	3.6	3.53	3.67	5	84	1	564	4.5	1
BZT52B3V9S	5Z	3.9	3.82	3.98	5	84	1	564	2.7	1
BZT52B4V3S	6Z	4.3	4.21	4.39	5	84	1	564	2.7	1
BZT52B4V7S	7Z	4.7	4.61	4.79	5	75	1	564	2.7	2
BZT52B5V1S	8Z	5.1	5.00	5.20	5	56	1	470	1.8	2
BZT52B5V6S	9Z	5.6	5.49	5.71	5	37	1	451	0.9	2
BZT52B6V2S	AZ	6.2	6.08	6.32	5	9	1	376	2.7	4
BZT52B6V8S	BZ	6.8	6.66	6.94	5	14	1	141	1.8	4
BZT52B7V5S	CZ	7.5	7.35	7.65	5	14	1	75	0.9	5
BZT52B8V2S	DZ	8.2	8.04	8.36	5	14	1	75	0.63	5
BZT52B9V1S	EZ	9.1	8.92	9.28	5	14	1	94	0.45	6
BZT52B10S	FZ	10	9.80	10.20	5	18	1	141	0.18	7
BZT52B11S	GZ	11	10.78	11.22	5	18	1	141	0.09	8
BZT52B12S	HZ	12	11.76	12.24	5	23	1	141	0.09	8
BZT52B13S	JZ	13	12.74	13.26	5	28	1	160	0.09	8
BZT52B15S	KZ	15	14.70	15.30	5	28	1	188	0.045	10.5
BZT52B16S	LZ	16	15.68	16.32	5	37	1	188	0.045	11.2
BZT52B18S	MZ	18	17.64	18.36	5	42	1	212	0.045	12.6
BZT52B20S	NZ	20	19.60	20.40	5	51	1	212	0.045	14.0
BZT52B22S	PZ	22	21.56	22.44	5	51	1	235	0.045	15.4
BZT52B24S	RZ	24	23.52	24.48	5	65	1	235	0.045	16.8
BZT52B27S	SZ	27	26.46	27.54	5	75	0.5	282	0.045	18.9
BZT52B30S	TZ	30	29.40	30.60	5	75	0.5	282	0.045	21.0
BZT52B33S	UZ	33	32.34	33.66	5	75	0.5	306	0.045	23.0
BZT52B36S	VZ	36	35.28	36.72	5	84	0.5	329	0.045	25.2
BZT52B39S	WZ	39	38.22	39.78	5	122	0.5	329	0.045	27.3
BZT52B43S	XZ	43	42.14	43.86	5	141	0.5	353	0.045	30.1
BZT52B47S	YZ	47	46.06	47.94	5	160	0.5	353	0.045	33.0
BZT52B51S	-Z	51	49.98	52.02	5	169	0.5	376	0.045	35.7

Type Number	Marking Code	Zener Voltage Range				Maximum Zener Impedance			Maximum Reverse Current	
		$V_Z @ I_{ZT}$			I_{ZT}	$Z_{ZT} @ I_{ZT}$	I_{ZK}	$Z_{ZK} @ I_{ZK}$	I_R	@ V_R
		Nom(V)	Min(V)	Max(V)	mA	Ω	mA	Ω	μA	V
BZT52B56S	=Z	56	54.88	57.12	5	188	0.5	400	0.045	39.2
BZT52B62S	≡Z	62	60.76	63.24	5	202	0.5	423	0.045	43.4
BZT52B68S	>Z	68	66.64	69.36	5	226	0.5	447	0.045	47.6
BZT52B75S	<Z	75	73.5	76.50	5	240	0.5	470	0.045	52.5

Notes: 1. The zener voltage (V_Z) is tested under pulse condition of 10ms.

2. The device numbers listed have a standard tolerance on the nominal zener voltage of $\pm 2\%$.

3. The zener impedance is derived from the 60-cycle ac voltage, which results when an ac current having an rms value equal to 10% of the dc zener current (I_{ZT} or I_{ZK}) is superimposed to I_{ZT} or I_{ZK} .

PACKAGE	SPQ/PCS	CARTON SPQ/PCS	CARTON SIZE/CM	CARTON GW/KG	CARTON NW/KG
SOD-323	3000/REEL	180000	44X44X22	9.00	8.00

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Zener Diodes](#) category:

Click to view products by [LGE](#) manufacturer:

Other Similar products are found below :

[MMSZ5245BS-7-F](#) [RKZ13B2KG#P1](#) [RKZ5.6B2KJ#R1](#) [EDZTE6113B](#) [EDZTE6116B](#) [EDZTE616.8B](#) [1N747A](#) [1N966B](#) [NTE5116A](#)
[NTE5121A](#) [NTE5139A](#) [NTE5147A](#) [NTE5152A](#) [NTE5155A](#) [NTE5156A](#) [NTE5164A](#) [JANS1N4974US](#) [SMAJ4764A-TP](#) [RKZ5.1BKU#P6](#)
[3SMAJ5946B-TP](#) [3SMAJ5950B-TP](#) [3SMBJ5920B-TP](#) [3SMBJ5925B-TP](#) [TDZTR24](#) [441774C](#) [MMSZ4678-TP](#) [MMSZ5232BQ-13-F](#)
[BZG04-36](#) [BZG05C9V1-HE3-TR](#) [HZM30NBTR-E](#) [UDZTE-175.1B](#) [3SMAJ5945B-TP](#) [3SMAJ5947B-TP](#) [3SMBJ5941B-TP](#) [DL4746A-TP](#)
[RKZ18B2KK#R1](#) [RKZ10B2KL#R1](#) [RKZ6.8B2KL#R1](#) [RKZ8.2B2KL#R1](#) [DZ2S240M0L](#) [SMAZ27-TP](#) [SMBZ5920B-E3/52](#) [ZMM3.0](#)
[RD16UM-T1-A](#) [RD39S-T1-A](#) [RD9.1S-T1-A](#) [RD10S-T1-A](#) [RD20S-T1-A](#) [RD2.2S-T1-A](#) [RD2.7UM-T1-A](#)