





RoHS

SPECIFICATIONS

Rated Current:3.0AMP  
 Contact Resistance:20mΩ Max  
 Withstand Voltage:1000V AC/DC  
 Insulation Resistance:1000MΩ Min  
 Operation Temperature:-40°C to +105°C

Contact Material:Brass  
 Contact Plating:Au Or Tin Over Ni  
 Insulator Material:Polyester(UL94V-0)  
 Standard: PA6T  
 Max.Processing Temp: 230°C for 30-60 seconds  
 (260°C for 10 seconds)

Recommended P.C.B Layout(Top Side)  
 (PCB BOARD TOLERANCE±0.05)



| Dimension antitheses list |     |    |     |      |    |    |     |     |
|---------------------------|-----|----|-----|------|----|----|-----|-----|
| ITEM                      | PA  | PW | PC  | L1   | L2 | L3 | H   | W   |
| 001                       | 6.0 |    | 3.0 | 11.5 |    |    | 2.5 | 2.5 |
| Alternate                 |     |    |     |      |    |    |     |     |

|     |            |                          |  |           |       |         |  |       |     |     |  |  |  |  |
|-----|------------|--------------------------|--|-----------|-------|---------|--|-------|-----|-----|--|--|--|--|
|     |            |                          |  | OPERATION |       | DRAW    |  | SCALE |     | FIT |  | 深圳市连盛精密连接器有限公司<br>PART NO. 1010301428<br>TITLE: 2.54PH H=2.5 1*22P DIP PA6.0<br>PC3.0 L=11.5 AU0.6U PA6T |  |  |
|     |            |                          |  | X.X       | ±0.30 |         |  | UNIT  | mm  |     |  |  |  |  |
|     |            |                          |  | X.XX      | ±0.20 | CHECK   |  | SIZE  | A4  |     |  |  |  |  |
|     |            |                          |  | X.XXX     | ±0.10 |         |  | SHEET | 1/1 |     |  |  |  |  |
| A0  | 2012.03.28 | NEW DRAWING              |  | Angle     | ±3°   | APPROVE |  | PROJ. | ☐   |     |  |  |  |  |
| REV | DATE       | MODIFICATION DESCRIPTION |  | CHANGE    | DIM   | TOL     |  |       |     |     |  |  |  |  |

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [Liansheng](#) manufacturer:*

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-](#)  
[5028](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)  
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)  
[820-22-008-30-001101](#) [821-22-002-10-001101](#)