



技术特性

温度范围: Temp. range $-65\sim+165^{\circ}\text{C}$ (PE Cable $-40\sim+85^{\circ}\text{C}$)
 振动: Vibration MTL-STD-202, Method 213
 特性阻抗: Impedance $50\ \Omega$
 频率范围: Frequency Range DC \sim 0-6GHz
 工作电压: Working Voltage 335V max (有效值)
 耐压: Withstand Voltage 1000V rms (海平面最小值)
 接触电阻: Contact resistance
 内导体之间: Center Contact $\leq 3\ \text{m}\Omega$
 外导体之间: Outer Contact $\leq 2\ \text{m}\Omega$
 绝缘电阻: Insulation resistance $\geq 5000\ \text{M}\Omega$
 插入损耗: Insertion loss $\leq 0.15\ \text{dB}/6\text{GHz}$

GENERAL TOLERANCE (UNLESS SPECIFIED) $\leq 10\ \pm 0.1$ $<10^{\circ}\leq 20\ \pm 0.2$ $<20^{\circ}\leq 50\ \pm 0.5$ Angle $\pm 3^{\circ}$	DWN	 连欣科技 Lian Xin Technology
	CHK	
 THIRD ANGLE	APVD	TITLE STARF
	CNIT MM	REV A
SIZE A4	SHEET 1 OF 1	DRAWING NO

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors](#) / [Coaxial Connectors](#) category:

Click to view products by [Lian Xin](#) manufacturer:

Other Similar products are found below :

[89674-0827](#) [6059674-1](#) [630059-000](#) [6501-1071-002](#) [6769](#) [7002-1541-010](#) [7002-1572-002](#) [7004-1512-000](#) [7009-1511-004](#) [7101-1541-010](#)
[7101-1571-002](#) [7105-1521-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-040](#) [7242-1511-000](#) [7405-1521-005](#) [7405-1521-](#)
[802](#) [804S01D04M040](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [8808-1511-001](#) [9049-9513-000](#) [9074-9513-000](#) [PL11C-026](#) [PL40-36](#) [9408-1113-000](#)
[980-8666-005](#) [11 SMA-50-2-6 / 111 NE](#) [11 SMA-50-3-6 / 111 NE](#) [11 SMA-50-2-6/111 NH](#) [1-201144-1](#) [120919](#) [R107003010W](#) [R112186000](#)
[R113053000W](#) [R113082097](#) [R113236000](#) [R114083000](#) [R114670000W](#) [R123415000W](#) [R124072220W](#) [R124076320](#) [R124076450](#)
[R124175123](#) [R124176123W](#) [R125075000W](#)