



P.C.B. LAYOUT

SPECIFICATIONS
 Current rating : 5~8.5A AC DC
 Voltage rating : 250V AC, DC
 Temperature range : -45°C~+105°C
 Contact resistance : 10mΩMax
 Insulation resistance : 1000MΩ Min
 Withstanding voltage : 1500 V AC/minute
 Contact Material : Brass
 Finished : Tin-plated
 Housing Material : LCP UL94-V0
 Color : Black

PART NO:	Dimension mm	
	A	B
C3030WT-F-2*1P	3.00	6.65
C3030WT-F-2*2P	3.00	9.65
C3030WT-F-2*3P	6.00	12.65
C3030WT-F-2*4P	9.00	15.65
C3030WT-F-2*5P	12.00	18.65
C3030WT-F-2*6P	15.00	21.65
C3030WT-F-2*7P	18.00	24.65
C3030WT-F-2*8P	21.00	27.65
C3030WT-F-2*9P	24.00	30.65
C3030WT-F-2*10P	27.00	33.65
C3030WT-F-2*11P	30.00	36.65
C3030WT-F-2*12P	33.00	39.65

深圳市连欣科技有限公司

TITLE
 3.0MM Pitch Wire to Board Header

TOLERANCE	APPROVALS
X, XX, XXX, X.XXX, ANGULAR	---
±0.25	---
±0.20	---
±0.05	---

VIEW	SCALE	PART NO.	REV.
FRONT	3:1	XDWF-C3030WT-**P	A2
CHECKED	UNIT	DWG. NO.	SHEET
16-Jul-2010	MM	A4	1 OF 1
APPROVED		C3030WT-005	
16-Jul-2010			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [Lian Xin](#) manufacturer:

Other Similar products are found below :

[0015917161](#) [0022155065](#) [57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-](#)
[4853B](#) [71.350.2428.0](#) [733-134](#) [733-162](#) [760-3052](#) [MHR-64-VUAL](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#)
[801-43-006-10-002000](#) [803-43-024-10-001000](#) [803-93-012-10-001000](#) [8-1437020-4](#) [819-22-004-30-001101](#) [820-22-006-30-001101](#)
[820-22-008-30-001101](#) [821-22-002-10-001101](#)