



3.2×2.5×0.7mm typ

12MHz up to 60MHz



### Feature

A small surface mount type crystal unit, especially suited for small-sizing requirements.

- Ultra compact and thin. (3.2×2.5×0.7 mm typ.)
- Tight Tolerance 10ppm available.
- Application: Bluetooth ; Mobile phone; W-LAN; Office Automation; Audio & Visual.
- Meets the requirements for re-flow profiling using lead-free solder.

### Specifications

| Item                        | Type | TX3-Type  |            |            |          |
|-----------------------------|------|---|------------|------------|----------|
| Frequency Range             |      | 12~13MHz  | 13~19.5MHz | 19.5~27MHz | 27~60MHz |
| Oscillator Mode             |      | Fundamental   |            |            |          |
| Load Capacitance            |      | Series, 6~32pf, or specify  |            |            |          |
| Drive Level                 |      | 10μW(200μW max.)  |            |            |          |
| Frequency Tolerance         |      | ±10×10 <sup>-6</sup> , ±20×10 <sup>-6</sup> , ±30×10 <sup>-6</sup> , ±50×10 <sup>-6</sup> (at 25°C) |            |            |          |
| Series Resistance           |      | 150Ω max.   | 80Ω max.   | 60Ω max.   | 50Ω max. |
| Operating Temperature Range |      | -10~+60°C, -20~+70°C, -40~+85°C   |            |            |          |
| Storage Temperature Range   |      | -55~+125°C  |            |            |          |
| Packing Unit                |      | 3000pcs/reel(Ø180)  |            |            |          |

### Outline Drawing(mm)



### Frequency Stability Vs. Temperature Range

| Temp.(°C) | Ppm | ±5 | ±10 | ±15 |
|-----------|-----|----|-----|-----|
| -10 ~ +60 |     | +  | ✓   | ✓   |
| -20 ~ +70 |     | ×  | ✓   | ✓   |
| -40 ~ +85 |     | ×  | ×   | +   |

  

| Temp.(°C)  | Ppm | ±15 | ±20 | ±30 | ±50 |
|------------|-----|-----|-----|-----|-----|
| -40 ~ +105 |     | +   | ✓   | ✓   | ✓   |
| -40 ~ +125 |     | ×   | ×   | +   | ✓   |

✓ Available + Conditional × Not Available

### Oscillation Circuit of Fundamental Mode





## Model Numbering Guide – Crystal Units

### Available options

| ①    | ②               | ③               | ④                     |                        | ⑤                     |                                      |  |  |            |                |      |
|------|-----------------|-----------------|-----------------------|------------------------|-----------------------|--------------------------------------|--|--|------------|----------------|------|
| Type | package (mm)    | Frequency range | Load Capacitance (pF) | Freq. Tol. @25°C (ppm) | Freq. Stability (ppm) | Temp. Range(°C)                      | Special Requirement  | Oscillator Mode                            | Appearance | Lead Free      | Dash |
| 1612 | 1.6x1.2         | 3.00~100.00MHZ  | 6                     | ±5                     | ±5                    | A:-20~+70<br>B:-40~+85<br>J:-40~+105 | For Automotive Spurious DLD No Special Pullability Several | AT Fundamental AT 3 <sup>rd</sup> Overtone | Normal     | RoHs Compliant | -    |
| 2016 | 2.0x1.6         |                 | 7                     | ±10                    | ±10                   |                                      |  |  |            |                |      |
| 2520 | 2.5x2.0         |                 | 8                     | ±15                    | ±15                   |                                      |  |  |            |                |      |
| 3225 | 3.2x2.5         |                 | 9                     | ±20                    | ±20                   |                                      |  |  |            |                |      |
| 5032 | 5.0x3.2 (4Pads) |                 | 10                    | ±25                    | ±25                   |                                      |  |  |            |                |      |
| 6035 | 6.0x3.5         |                 | 12                    | ±25                    | ±30                   |                                      |  |  |            |                |      |
| 3225 | 3.2x2.5         |                 | 15                    | ±30                    | ±40                   |                                      |  |  |            |                |      |
| 5032 | 5.0x3.2 (2Pads) |                 | 16                    | ±30                    | ±40                   |                                      |  |  |            |                |      |
| 8045 | 8.0x4.5         |                 | 18                    | ±40                    | ±50                   |                                      |  |  |            |                |      |
| 49S  | 11.1x4.68       |                 | 20                    | ±40                    | ±50                   |                                      |  |  |            |                |      |
| 49MD | 13.0x4.85       |                 | 22                    | ±50                    | ±100                  |                                      |  |  |            |                |      |
|      |                 |                 | 25                    | ±50                    | ±150                  |                                      |  |  |            |                |      |
|      |                 | 30              | ±100                  | ±150 above             |                       |                                      |  |  |            |                |      |
|      |                 | 32              | ±150                  | ±150 above             |                       |                                      |  |  |            |                |      |

产品编号:  -  -  -  -

① 型号    ② 频率    ③ 负载电容    ④ 频率稳定度 (X10<sup>-6</sup>, +25°C)    ⑤ 温度

范例: 3225-12.00-20-20-20/A

①    ②    ③    ④    ⑤

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Resonators](#) category:*

*Click to view products by [Liming](#) manufacturer:*

Other Similar products are found below :

[B39431R820H210](#) [CSAC2.00MGCM-TC](#) [ECS-HFR-40.00-B-TR](#) [CSTLS4M00G53Z-A0](#) [ZTB455E](#) [ECS-CR2-16.00-A-TR](#) [ECS-HFR-20.00-B-TR](#) [ECS-CR2-20.00-A-TR](#) [RO3164E-3](#) [ASR418S2-T](#) [CSTNE10M0G520000R0](#) [CSTLS8M00G53093-A0](#) [CSTNE12M0G52A000R0](#) [CSTLS18M4X54-A0](#) [CSTLS16M9X53Z-B0](#) [CSTLS24M0X51-A0](#) [CSTLS25M0X51-B0](#) [CSTLS18M0X51-B0](#) [CSTLS4M00G53093-A0](#) [CSTLS18M4X53-A0](#) [CSTNE16M0V510000R0](#) [CSTLS30M0X53-B0](#) [CSTLS33M8X53-B0](#) [CSTLS16M9X53-A0](#) [CSTLS6M40G56-B0](#) [CSTLS6M25G56-A0](#) [CSTNE14M7V510000R0](#) [CSTLS18M4X53-B0](#) [CSTLS33M0X51-B0](#) [CSTLS5M50G56-B0](#) [7B008000I01](#) [7D038400I01](#) [TAXM24M2ILDBET2T](#) [TAXM26M2IHDBET2T](#) [146-32.768-12.5-20-20/A](#) [3225-24.00-12-10-10/A](#) [7B009843M01](#) [CF4016M00009T8188042](#) [S32400001B0730D1JB](#) [X252016MLB4SI](#) [Q24FA20H00389](#) [CSTLS16M0X54-B0](#) [CSTLS4M19G56-B0](#) [9AC04194152080D2JB](#) [CST3.58MGW](#) [CSTCR4M91G55B-R0](#) [CSTLS3M68G56-B0](#) [S2100327072090](#) [FC-12M32.768KHZ9PF20PPM](#) [7Y032768NW2](#)