



上海立凯电控科技有限公司

Shanghai LineKey Technology Co., Ltd.



Specification For Approval

规格书

客户名称: _____

部件名称: 叠层射频电感

客户料号: _____

立凯料号: HFM0603-47NJCS

供方确认			客户确认
制作	审核	核准	
吴子晗	薄双燕	陈余想	

Spec 变更记录:

版本	序号	更改描述	更改原因	备注
A0	01	Released		

地址: 上海市浦东新区商城路800号斯米克大厦1102室

电话: 021-61993616

邮箱: Sales@linekey.cn

网址: www.linekey.cn

Add: No.1101, Pudong South Road, Shanghai, China

Tel: 021-61993616

E-mail: Sales@linekey.cn

Website: www.linekey.cn

客户/CLIENT:

承制方/MANUFACTURER: 上海立凯电控科技有限公司

型号/MODEL: HFM0603-47NJCS

版本/REV.: A0 页数: 2/4

1. Scope

This specification applies to HFM0603-47NJCS SMD multilayer RF inductor.

2. Product Description and Identification (Part Number)

HFM 0603 - 47N J CS
 ① ② ③ ④ ⑤





- ① Product Series: HFM Series
- ② Size: 0.6mm×0.3mm×0.3mm
- ③ Inductance: 47N = 47nH
- ④ Tolerance: J=±5%
- ⑤ Internal code

3. Operating & Storage Temperature

1) Operating temperature range : -55℃ ~ +125℃ (Including Self-heating) .

4. Shape and Dimensions (Unit: mm)

Dimensions and recommended PCB pattern for reflow soldering



Series	L(mm)	W(mm)	T(mm)	D(mm)	E(mm)	F(mm)	G(mm)
HFW0603	0.6±0.03	0.3±0.03	0.3±0.03	0.15±0.05	0.3 Typ.	0.3 Typ	0.8 Typ.

5. Electrical Characteristics

Part Number	Inductance (nH)	Tolerance	Q Value (Min)	Test Freq. L/Q (MHz)	SRF Min. (GHz)	DCR Max(Ω)	Rated Current Max (mA)
HFM0603-47NJCS	47	±5%	8	100	1.4	1.2	150

拟制/PREPARED BY: 吴子晗	审核/CHECKED BY: 薄双燕	批准/APPROVED BY: 陈余想
------------------------	-----------------------	------------------------

客户/CLIENT:

型号/MODEL: HFM0603-47NJCS

承制方/MANUFACTURER: 上海立凯电控科技有限公司


版本/REV.: A0 页数: 3/4

Note*

- 1) Rated Current: Max. DC current which causes 20K temperature rise from 20° C ambient;
- 2) Measuring Instrument: L/Q:CH-1062, DCR: HIOKI-3540, Rated Current:CH-1062

6. Typical Characteristic Chart

L/Q Vs. Frequency



拟制/PREPARED BY:

吴子晗

审核/CHECKED BY:

薄双燕

批准/APPROVED BY:

陈余想




客户/CLIENT:

型号/MODEL: HFM0603-47NJCS

承制方/MANUFACTURER: 上海立凯电控科技有限公司

版本/REV.: A0 页数: 4/4

6. Reliability Test

Items	Requirements	Test Methods and Remarks
6.1 Terminal Strength		<ol style="list-style-type: none"> 1) Solder the inductor to the testing jig using eutectic solder. Then apply a force in the direction of the arrow. 2) No removal or split of the termination or other defects shall occur. 3) 10N force. 4) Keep time: 5±2s.
6.2 High Temperature	<ol style="list-style-type: none"> 1) No visible mechanical damage. 2) Inductance change: Within ±10% 	<ol style="list-style-type: none"> 1) Storage Temperature :125+/-5°C. 2) Duration: 96 ±4 Hours. 3) Recovery: then measured at room ambient temperature after placing 24 hours.
6.3 Low Temperature	<ol style="list-style-type: none"> 1) No visible mechanical damage. 2) Inductance change: Within ±10% 	<ol style="list-style-type: none"> 1) Storage Temperature :125+/-5°C 2) Duration: 96 ±4 Hour. 3) Recovery: then measured at room ambient temperature after placing 24 hours.
6.4 Vibration test	<ol style="list-style-type: none"> 1) No visible mechanical damage. 2) Inductance change: Within ±10% 	<ol style="list-style-type: none"> 1) Frequency range:10HZ~55HZ~10HZ. 2) Amplitude:1.5mm p-p. 3) Direction: X, Y, Z. 4) Time:1 minute/cycle,2hours per axis
6.5 High Temperature Storage Tested	<ol style="list-style-type: none"> 1) No visible mechanical damage. 2) Inductance change: Within ±10% 	<ol style="list-style-type: none"> 1) Storage Temperature :60+/-2°C. 2) Relative Humidity:90-95% RH. 3) Duration: 96 ±4 Hours. 4) Recovery: then measured at room ambient temperature after placing 24 hours.
6.6 Resistance to Soldering Heat	<ol style="list-style-type: none"> 1) No visible mechanical damage. 2) Inductance change: Within ±10% 	<ol style="list-style-type: none"> 1) Re-flowing Profile: Please refer to the left graph. 2) Test board thickness: 1.0mm. 3) Test board material: glass epoxy resin. 4) The chip shall be stabilized at normal condition for 1~2 hours before measuring.
6.7 Thermal Shock	<ol style="list-style-type: none"> 1) No visible mechanical damage. 2) Inductance change: Within ±10% 	<ol style="list-style-type: none"> 1) Temperature and time: -40±3°C for 30±3 min→105°C for 30±3min, please refer to the left graph. 2) Transforming interval: Max, 3 minutes 3) Tested cycle: 100 cycles. 4) The chip shall be stabilized at normal condition for 1~2 hours before measuring.

拟制/PREPARED BY:

吴子晗

审核/CHECKED BY:

薄双燕

批准/APPROVED BY:

陈余想

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [Linekey](#) manufacturer:

Other Similar products are found below :

[CR43NP-680KC](#) [CR54NP-470LC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHQ1005P10NJ](#)
[MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2LP-R47-R](#) [HC2-R47-R](#) [HC3-2R2-R](#) [HC3-R50-R](#) [HC8-1R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#) [RCR1010NP-470M](#) [RCR110DNP-331L](#) [DH2280-4R7M](#) [DS1608C-106](#)
[ASPI-4020HI-R10M-T](#) [B10TJ](#) [B82498B3680J000](#) [ELJ-RE27NJF2](#) [1812CS-153XJ](#) [1812CS-183XJ](#) [1812CS-223XJ](#)