

SMA and Reverse Polarity SMA Specifications

Materials		
Connector Part	Material	Finish
Bodies	Brass	Nickel or Gold
	Stainless Steel	Passivated or Gold
Center contact	Male: Brass	Gold
	Female: Beryllium Copper	
Insulator	PTFE	N/A
Crimp ferrule	Annealed Copper	Nickel or Gold

Electrical			
Electrical Data	Detail		
Impedance	50 ohm		
Frequency range	Flexible cable: 0~12.4GHz		
	Semi-rigid cable: 0~18GHz		
Working voltage	RG402 (.141") » 500 volts rms max.		
	RG405 (.085") » 335 volts rms max.		
	RG58, 141, 142, 223/U » 500 volts rms max.		
	RG174, 188, 316/U » 335 volts rms max.		
	RG178, 196/U » 250 volts rms max.		
Insulation resistance	5,000 megaohms min.		
Dielectric withstanding voltage	RG402 (.141") » 1,000 volts rms max.		
	RG405 (.085") » 750 volts rms max.		
	RG58, 141, 142, 223/U » 1,000 volts rms max.		
	RG174, 188, 316/U » 750 volts rms max.		
	RG178, 196/U » 500 volts rms max.		
Contact resistance	Center contact: 3.0 milliohms max.		
	Outer contact: 2.0 milliohms max.		
VSWR: f(GHz)		Straight	Right angle
	RG178/U	1.20+0.025f	1.20+0.03f
	RG174, 316/U	1.15+0.02f	1.15+0.03f
	RG58, 141, 142, 223/U	1.10+0.01f	1.15+0.02f
	RG402 (.141")	1.05+0.005f	1.15+0.15f
	RG405 (.085")	1.05+0.005f	1.18+0.15f
Insertion loss	0.04dB max. x \sqrt{f} GHz (straight)		
	0.06dB max. x \sqrt{f} GHz (right angle)		

Mechanical

Mechanical Data	Detail
Engagement force	60lbs min.
Disengagement force	15 inch-pound
Connector durability	500 cycles min.
Cable retention force	RG58, 141, 142, 223/U » 40lbs min.
	RG174, 188, 316/U » 20lbs min.

Environmental

Environmental Data	Detail
Corrosion (salt spray)	MIL-STD-202 METHOD 101 TEST CONDITION B
Thermal shock	MIL-STD-202 METHOD 107 TEST CONDITION B
Vibration	MIL-STD-202 METHOD 204 TEST CONDITION D
Mechanical shock	MIL-STD-202 METHOD 213 TEST CONDITION I
Temperature Range	-65°C to 165°C

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:

Click to view products by [Linx Technologies](#) manufacturer:

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7105-1521-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [7325-1512-000](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [7406-1521-005](#) [8527](#) [8547](#) [FS11V](#) [8808-1511-001](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL71-9](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [980-8666-005](#) [1200690078](#)