

Description

The 5KP series is designed specifically to protect sensitive electronic equipment from voltage transients induced by lightning and other transient voltage events.

Features

- Halogen free and RoHS compliant
- Glass passivated junction
- Low incremental surge resistance
- Excellent clamping capability
- 5000W peak pulse power capability at 10/1000μs waveform, repetition rate (duty cycle): 0.05%
- Fast response time
- Typical I_R less than 2μA above 10V devices
- High Temperature soldering guaranteed: 265°C/10 seconds/.375", (9.5mm) lead length, 5lbs (2.3kg) tension
- Plastic package has underwriters laboratory flammability 94V-0
- Meet MSL level1, per J-STD-020
- IEC-61000-4-2 ESD 30kV(Air), 30kV (Contact)
- Unit Weight: 2.1g



Applications

TVS components are ideal for the protection of I/O Interfaces, VCC bus and other vulnerable circuits used in telecom, computer, Industrial and consumer electronic applications.

Maximum Ratings and Characteristics ($T_A=25^\circ\text{C}$)

| Rating | Symbol | Value |
|---|-----------------|-----------------|
| Peak pulse power dissipation at 10/1000μs waveform (Note1, Fig.1) | P_{PPM} | 5000W |
| Peak pulse current of at 10/1000μs waveform (Note 1, Fig.3) | I_{PPM} | See Table(A) |
| Steady state power dissipation at $T_L=75^\circ\text{C}$ (Fig.5) | $P_{M(AV)}$ | 8.0W |
| Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load, (JEDEC Method) (Note2, Fig.6) | I_{FSM} | 400A |
| Operating junction and Storage Temperature Ranges | T_J, T_{STG} | -55°C to +150°C |
| Typical thermal resistance junction to lead | $R_{\theta JL}$ | 8°C/W |
| Typical thermal resistance junction to ambient | $R_{\theta JA}$ | 40°C/W |

Notes:1. Non-repetitive current pulse, per Fig.3 and derating above $T_A=25^\circ\text{C}$ per Fig.2.

2. 8.3ms single half sine-wave or equivalent square wave, duty cycle=4 pulses per minutes maximum.

Electrical Characteristics ($T_A=25^{\circ}\text{C}$)

| Part Number | | Reverse Stand-Off Voltage | Breakdown Voltage @ I_T | | Test Current | Maximum Clamping Voltage @ I_{PP} | Peak Pulse Current | Reverse Leakage @ V_R |
|-------------|----------|---------------------------|---------------------------|------------------|--------------|-------------------------------------|--------------------|-------------------------|
| Uni. | Bi. | $V_R(V)$ | $V_{B\ Min.}(V)$ | $V_{B\ Max.}(V)$ | $I_T(mA)$ | $V_C(V)$ | $I_{PP}(A)$ | $I_R(\mu A)$ |
| 5KP5.0A | 5KP5.0CA | 5.0 | 6.40 | 7.00 | 50 | 9.2 | 554.3 | 3000 |
| 5KP6.0A | 5KP6.0CA | 6.0 | 6.67 | 7.37 | 50 | 10.3 | 495.1 | 2000 |
| 5KP6.5A | 5KP6.5CA | 6.5 | 7.22 | 7.98 | 50 | 11.2 | 455.4 | 1000 |
| 5KP7.0A | 5KP7.0CA | 7.0 | 7.78 | 8.60 | 50 | 12.0 | 425.0 | 800 |
| 5KP7.5A | 5KP7.5CA | 7.5 | 8.33 | 9.21 | 5 | 12.9 | 395.3 | 250 |
| 5KP8.0A | 5KP8.0CA | 8.0 | 8.89 | 9.83 | 5 | 13.6 | 375.0 | 150 |
| 5KP8.5A | 5KP8.5CA | 8.5 | 9.44 | 10.40 | 5 | 14.4 | 354.2 | 50 |
| 5KP9.0A | 5KP9.0CA | 9.0 | 10.00 | 11.10 | 5 | 15.4 | 331.2 | 20 |
| 5KP10A | 5KP10CA | 10.0 | 11.10 | 12.30 | 5 | 17.0 | 300.0 | 10 |
| 5KP11A | 5KP11CA | 11.0 | 12.20 | 13.50 | 5 | 18.2 | 280.2 | 2 |
| 5KP12A | 5KP12CA | 12.0 | 13.30 | 14.70 | 5 | 19.9 | 256.3 | 2 |
| 5KP13A | 5KP13CA | 13.0 | 14.40 | 15.90 | 5 | 21.5 | 237.2 | 2 |
| 5KP14A | 5KP14CA | 14.0 | 15.60 | 17.20 | 5 | 23.2 | 219.8 | 2 |
| 5KP15A | 5KP15CA | 15.0 | 16.70 | 18.50 | 5 | 24.4 | 209.0 | 2 |
| 5KP16A | 5KP16CA | 16.0 | 17.80 | 19.70 | 5 | 26.0 | 196.2 | 2 |
| 5KP17A | 5KP17CA | 17.0 | 18.90 | 20.90 | 5 | 27.6 | 184.8 | 2 |
| 5KP18A | 5KP18CA | 18.0 | 20.00 | 22.10 | 5 | 29.2 | 174.7 | 2 |
| 5KP20A | 5KP20CA | 20.0 | 22.20 | 24.50 | 5 | 32.4 | 157.4 | 2 |
| 5KP22A | 5KP22CA | 22.0 | 24.40 | 26.90 | 5 | 35.5 | 143.7 | 2 |
| 5KP24A | 5KP24CA | 24.0 | 26.70 | 29.50 | 5 | 38.9 | 131.1 | 2 |
| 5KP26A | 5KP26CA | 26.0 | 28.90 | 28.90 | 5 | 42.1 | 121.1 | 2 |
| 5KP28A | 5KP28CA | 28.0 | 31.10 | 34.40 | 5 | 45.4 | 112.3 | 2 |
| 5KP30A | 5KP30CA | 30.0 | 33.30 | 36.80 | 5 | 48.4 | 105.4 | 2 |
| 5KP33A | 5KP33CA | 33.0 | 36.70 | 40.60 | 5 | 53.3 | 95.7 | 2 |
| 5KP36A | 5KP36CA | 36.0 | 40.00 | 44.20 | 5 | 58.1 | 87.8 | 2 |
| 5KP40A | 5KP40CA | 40.0 | 44.40 | 49.10 | 5 | 64.5 | 79.1 | 2 |

Electrical Characteristics (T_A=25°C)

| Part Number | | Reverse Stand-Off Voltage | Breakdown Voltage @I _T | | Test Current | Maximum Clamping Voltage @I _{PP} | Peak Pulse Current | Reverse Leakage @V _R |
|-------------|----------|---------------------------|-----------------------------------|-------------------------|---------------------|---|---------------------|---------------------------------|
| Uni. | Bi. | V _R (V) | V _{B Min.} (V) | V _{B Max.} (V) | I _T (mA) | V _C (V) | I _{PP} (A) | I _R (μA) |
| 5KP43A | 5KP43CA | 43.0 | 47.80 | 52.80 | 5 | 69.4 | 73.5 | 2 |
| 5KP45A | 5KP45CA | 45.0 | 50.00 | 55.30 | 5 | 72.7 | 70.2 | 2 |
| 5KP48A | 5KP48CA | 48.0 | 53.30 | 58.90 | 5 | 77.4 | 65.9 | 2 |
| 5KP51A | 5KP51CA | 51.0 | 56.70 | 62.70 | 5 | 82.4 | 61.9 | 2 |
| 5KP54A | 5KP54CA | 54.0 | 60.00 | 66.30 | 5 | 87.1 | 58.6 | 2 |
| 5KP58A | 5KP58CA | 58.0 | 64.40 | 71.20 | 5 | 93.6 | 54.5 | 2 |
| 5KP60A | 5KP60CA | 60.0 | 66.70 | 73.70 | 5 | 96.8 | 52.7 | 2 |
| 5KP64A | 5KP64CA | 64.0 | 71.10 | 78.60 | 5 | 103.0 | 49.5 | 2 |
| 5KP70A | 5KP70CA | 70.0 | 77.80 | 86.00 | 5 | 113.0 | 45.1 | 2 |
| 5KP75A | 5KP75CA | 75.0 | 83.30 | 92.10 | 5 | 121.0 | 42.1 | 2 |
| 5KP78A | 5KP78CA | 78.0 | 86.70 | 95.80 | 5 | 126.0 | 40.5 | 2 |
| 5KP85A | 5KP85CA | 85.0 | 94.40 | 104.0 | 5 | 137.0 | 37.2 | 2 |
| 5KP90A | 5KP90CA | 90.0 | 100.0 | 111.0 | 5 | 146.0 | 34.9 | 2 |
| 5KP100A | 5KP100CA | 100.0 | 110.0 | 123.0 | 5 | 162.0 | 31.5 | 2 |
| 5KP110A | 5KP110CA | 110.0 | 122.0 | 135.0 | 5 | 177.0 | 28.8 | 2 |
| 5KP120A | 5KP120CA | 120.0 | 133.0 | 147.0 | 5 | 193.0 | 26.4 | 2 |
| 5KP130A | 5KP130CA | 130.0 | 144.0 | 159.0 | 5 | 209.0 | 24.4 | 2 |
| 5KP150A | 5KP150CA | 150.0 | 167.0 | 185.0 | 5 | 243.0 | 21.0 | 2 |
| 5KP160A | 5KP160CA | 160.0 | 178.0 | 197.0 | 5 | 259.0 | 19.7 | 2 |
| 5KP170A | 5KP170CA | 170.0 | 189.0 | 209.0 | 5 | 275.0 | 18.5 | 2 |
| 5KP180A | 5KP180CA | 180.0 | 201.0 | 222.0 | 5 | 292.0 | 17.5 | 2 |
| 5KP190A | 5KP190CA | 190.0 | 211.0 | 233.0 | 5 | 310.0 | 16.5 | 2 |
| 5KP200A | 5KP200CA | 200.0 | 224.0 | 247.0 | 5 | 329.2 | 15.5 | 2 |
| 5KP210A | 5KP210CA | 210.0 | 237.0 | 263.0 | 5 | 349.5 | 14.6 | 2 |
| 5KP220A | 5KP220CA | 220.0 | 246.0 | 272.0 | 5 | 371.1 | 13.7 | 2 |
| 5KP250A | 5KP250CA | 250.0 | 277.0 | 306.0 | 5 | 425.0 | 12.0 | 2 |

Ratings and Characteristic Curves ($T_A=25^\circ\text{C}$)

Figure 1. Peak Pulse Power Rating Curve




Figure 2. Pulse Derating Curve




Figure 3. Pulse Waveform




Figure 4. Typical Junction Capacitance




Figure 5. Steady State Power Dissipation Derating Curve







Figure 6. Maximum Non-Repetitive Forward Surge Current Uni-Directional Only



Wave Soldering



Part Number Code and Marking Code




Dimensions (P600)

The diagram shows the dimensions of the TVS diode package. Dimensions A, B, C, and d are indicated. A is the length of the leads, B is the width of the body, C is the height of the body, and d is the thickness of the leads.

| Symbol | Millimeters | | Inches | |
|--------|-------------|------|--------|-------|
| | Min. | Max. | Min. | Max. |
| A | 25.40 | - | 1.000 | - |
| B | 8.60 | 9.10 | 0.340 | 0.360 |
| C | 8.60 | 9.10 | 0.340 | 0.360 |
| d | 1.19 | 1.35 | 0.047 | 0.053 |


Packaging Specification

Tape



Quantity: 800pcs/reel

Box



Quantity: 300pcs/box

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [ESD Suppressors / TVS Diodes](#) category:

Click to view products by [Liown](#) manufacturer:

Other Similar products are found below :

[60KS200C](#) [D18V0L1B2LP-7B](#) [D5V0F4U5P5-7](#) [DESD5V0U1BB-7](#) [NTE4902](#) [P4KE27CA](#) [P6KE11CA](#) [P6KE39CA-TP](#) [P6KE8.2A](#)
[SA110CA](#) [SA60CA](#) [SA64CA](#) [SMBJ12CATR](#) [SMBJ33CATR](#) [SMBJ8.0A](#) [ESD101-B1-02ELS E6327](#) [ESD105-B1-02EL E6327](#) [ESD112-B1-02EL E6327](#) [ESD119B1W01005E6327XTSA1](#) [ESD5V0L1B02VH6327XTSA1](#) [ESD7451N2T5G](#) [19180-510](#) [CPDT-5V0USP-HF](#)
[3.0SMCJ33CA-F](#) [3.0SMCJ36A-F](#) [HSPC16701B02TP](#) [D3V3Q1B2DLP3-7](#) [D55V0M1B2WS-7](#) [DESD5V0U1BL-7B](#) [DRTR5V0U4SL-7](#)
[SCM1293A-04SO](#) [ESD200-B1-CSP0201 E6327](#) [SM12-7](#) [SMLJ45CA-TP](#) [CEN955 W/DATA](#) [82350120560](#) [VESD12A1A-HD1-GS08](#)
[CPDUR5V0R-HF](#) [CPDQC5V0U-HF](#) [CPDQC5V0USP-HF](#) [CPDQC5V0-HF](#) [D1213A-01LP4-7B](#) [D1213A-02WL-7](#) [MMAD1108/TR13](#)
[5KP100A](#) [5KP15A](#) [5KP18A](#) [5KP48A](#) [5KP90A](#) [5KP90CA](#)