

NPN GENERAL PURPOSE TRANSISTOR


REVERSE VOLTAGE – 60 Volts
FORWARD CURRENT – 0.2 Amperes

FEATURES

- For switching and amplifier applications.
- Complementary PNP type available (MMBT3906)

MECHANICAL DATA

- Case: SOT-23 plastic
- Case material: “Green” molding compound, UL flammability classification 94V-0, (No Br. Sb. Cl)
- Lead free in RoHS 2011/65/EC compliant



ABSOLUTE RATINGS@ T_A = 25°C unless otherwise specified

PARAMETER	SYMBOL	VALUE	UNIT
Collector-base voltage	V _{CBO}	60	V
Collector-emitter voltage	V _{CEO}	40	V
Emitter-base voltage	V _{EBO}	6.0	V
Collector current-continuous	I _C	200	mA
Collector power dissipation	P _D	225 (NOTE 1) 300 (NOTE 2)	mW
Thermal resistance junction to ambient	R _{thJA}	556 (NOTE 1) 417 (NOTE 2)	°C/W
Operating temperature range	T _J	-55~+150	°C
Storage temperature range	T _{STG}	-55~+150	°C

Note:

REV.8, Jun.-2018, KSRN11

1. Device mounted on FR-5 board, 1.0 x 0.75 x 0.062 in.
2. Device mounted on Alumina substrate, 0.4 x 0.3 x 0.024 in 99.5% alumina.
3. Pulse Test: pulse width ≤ 300μs, duty cycle ≤ 2.0 %.

ORDER INFORMATION

DEVICE	MARKING	SHIPPING
MMBT3904	1AM	3000/ Tate & reel

ELECTRICAL CHARACTERISTIC
MMBT3904



OFF CHARACTERISTICS @ T_A = 25°C unless otherwise specified

PARAMETER	TEST CONDITION	SYMBOL	MIN.	MAX.	UNIT
Collector-base breakdown voltage	I _C = 10 μA, I _E = 0	V _{CBO}	60	--	V
Collector-emitter breakdown voltage	I _C = 1.0 mA, I _B = 0	V _{CEO}	40	--	V
Emitter-base breakdown voltage	I _E = 10 μA, I _C = 0	V _{EBO}	6.0	--	V
Base cutoff current	V _{CE} =30V, V _{EB} = 3.0V	I _{BL}	--	50	nA
Collector cut-off current	V _{CE} =30V, V _{BE} = 3.0V	I _{CEX}	--	50	nA

ON CHARACTERISTICS @ T_A = 25°C unless otherwise specified

PARAMETER	TEST CONDITION	SYMBOL	MIN.	MAX.	UNIT
DC current gain	V _{CE} =1.0V, I _C =0.1mA	h _{FE}	40	--	--
	V _{CE} =1.0V, I _C =1.0mA		70	--	
	V _{CE} =1.0V, I _C =10mA		100	300	
	V _{CE} =1.0V, I _C =50mA		60	--	
	V _{CE} =1.0V, I _C =100mA		30	--	
Collector-emitter saturation voltage (NOTE 3)	I _C =10mA, I _B =1.0mA	V _{CE(sat)}	--	0.2	V
	I _C =50mA, I _B =5.0mA		--	0.3	
Base-emitter saturation voltage	I _C =10mA, I _B =1.0mA	V _{BE(sat)}	0.65	0.85	V
	I _C =50mA, I _B =5.0mA		--	0.95	

SMALL-SIGNAL CHARACTERISTICS @ T_A = 25°C unless otherwise specified

PARAMETER	TEST CONDITION	SYMBOL	MIN.	MAX.	UNIT
Current-gain-band width product	V _{CE} =20V, I _C =10mA, f=100 MHz	f _T	300	--	MHz
Output capacitance	V _{CB} =5.0V, I _E =0, f=1.0 MHz	C _{obo}	--	4.0	pF
Input capacitance	V _{EB} =0.5V, I _E =0, f=1.0 MHz	C _{ibo}	--	8.0	pF
Input impedances	V _{CE} =10V, I _C =1.0mA, f=1.0 kHz	h _{ie}	1.0	10	KΩ
Voltage feedback ratio	V _{CE} =10V, I _C =1.0mA, f=1.0 kHz	h _{re}	0.5	8.0	X10 ⁻⁴
Small-signal current gain	V _{CE} =10V, I _C =1.0mA, f=1.0 kHz	h _{fe}	100	400	--
Output admittance	V _{CE} =10V, I _C =1.0mA, f=1.0 kHz	h _{oe}	1.0	40	μmhos
Noise figure	V _{CE} =5.0V, I _C =100μA, R _S =1.0kΩ, f=1.0 kHz	NF	--	5.0	dB

SWITCHING CHARACTERISTICS @ T_A = 25°C unless otherwise specified

PARAMETER	TEST CONDITION	SYMBOL	MIN.	MAX.	UNIT
Delay time	V _{CC} =3.0V, V _{BE} = - 0.5V, I _C =10mA, I _{B1} = 1.0mA	t _d	--	35	ns
Rise time		t _R	--	35	
Storage time	V _{CC} =3.0V, I _C =10mA, I _{B1} =I _{B2} =1.0mA	t _s	--	200	
Fall time		t _f	--	50	

FIG. 1 - Delay and rise time equivalent test circuit





FIG. 2 - Storage and fall time equivalent test circuit



* Total shunt capacitance of test jig and connectors

FIG. 3 - Capacitance




FIG. 4 - Current gain




FIG. 5 - DC current gain




FIG. 6 - Collector saturation region




FIG. 7 - $V_{CE(sat)}$ vs. I_C




FIG. 8 - $V_{BE(sat)}$ vs. I_C








FIG. 9 - $V_{BE(on)}$ vs. I_C



Package Dimensions :


SOT-23



Dim.	INCHES		MILLIMETERS	
	Min.	Max.	Min.	Max.
A	0.1102	0.1197	2.80	3.04
B	0.0472	0.0551	1.20	1.40
C	0.0350	0.0440	0.89	1.11
D	0.0150	0.0200	0.37	0.50
G	0.0701	0.0807	1.78	2.04
H	0.0005	0.0040	0.013	0.100
J	0.0034	0.0070	0.085	0.177
K	0.0140	0.0285	0.35	0.69
L	0.0350	0.0401	0.89	1.02
S	0.0830	0.1039	2.10	2.64
V	0.0177	0.0236	0.45	0.60

Note:
PIN 1. Base
PIN 2. Emitter
PIN 3. Collector

Soldering Pad Layout :



Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bipolar Transistors - BJT category](#):

Click to view products by [Lite-On manufacturer](#):

Other Similar products are found below :

[619691C](#) [MCH4017-TL-H](#) [MJ15024/WS](#) [MJ15025/WS](#) [BC546/116](#) [BC556/FSC](#) [BC557/116](#) [BSW67A](#) [HN7G01FU-A\(T5L,F,T](#)
[NJVMJD148T4G](#) [NSVMMBT6520LT1G](#) [NTE187A](#) [NTE195A](#) [NTE2302](#) [NTE2330](#) [NTE2353](#) [NTE316](#) [IMX9T110](#) [NTE63](#) [NTE65](#)
[C4460](#) [SBC846BLT3G](#) [2SA1419T-TD-H](#) [2SA1721-O\(TE85L,F\)](#) [2SA1727TLP](#) [2SA2126-E](#) [2SB1202T-TL-E](#) [2SB1204S-TL-E](#) [2SC5488A-](#)
[TL-H](#) [2SD2150T100R](#) [SP000011176](#) [FMC5AT148](#) [2N2369ADCSM](#) [2SB1202S-TL-E](#) [2SC2412KT146S](#) [2SC4618TLN](#) [2SC5490A-TL-H](#)
[2SD1816S-TL-E](#) [2SD1816T-TL-E](#) [CMXT2207 TR](#) [CPH6501-TL-E](#) [MCH4021-TL-E](#) [BC557B](#) [TTC012\(Q\)](#) [BULD128DT4](#) [JANTX2N3810](#)
[Jantx2N5416](#) [US6T6TR](#) [KSF350](#) [068071B](#)