



MICRO3® Blade Fuses



MICR03[®] Shunt

MICRO3™ Blade Fuses Rated 32V

The MICRO3™ Fuse has 3 terminals and 2 fuse elements with a common center terminal. Its sub-miniature design meets the need for more circuits to be protected while utilizing less space and its ability to cope with high temperatures in adverse environments makes the MICRO3™ Fuse of recommended choice for protection.

Specifications

Voltage Rating: 32 VDC

Interrupting Ratings: 1000A @ 32 VDC
*Recommended Environmental Temperature: -40°C to +125°C
Terminals Material: Silver plated zinc alloy

Housing Material: PA66 (U.L. 94 Flammability rating – V2)

Net Weight Per Fuse: 0.95±10% gr

Complies with: SAE 2741 and ISO 8820-3 in reference to electrical, mechanical and environmental performance requirements



^{*}Silver plating allows up to 150°C at the terminal interface.

Part Number Rating Package Size 0337xxx.PX2S 3 - 15 & SHUNT 2000 0337xxx.LXS 3 - 15 & 50

Ordering Information

Time-Current Characteristics

% of Rating	Opening Time Min / Max (s)
110	360,000 / ∞
135	0.75 / 120
160	0.3 / 50
200	0.15 / 5
350	0.04 / 0.5
600	0.02 / 0.1

Ratings

Part Number	Current Rating (A)	Housing Material Color	Test Cable Size (mm²)		Typ. Voltage	Typ. Cold	Typ. I ² t
			Side Fuse Blades	Center Fuse Blades	Drop (mV)	Resistance (mΩ)	(A ² s)
0337003	3		0.5	1	113	31.7	9
0337005	5		0.5	1	116	17.4	17
033707.5_	7.5		0.75	1.5	106	10.8	47
0337010	10		1	2.5	102	7.8	89
0337015	15		1.5	4	94	4.9	189
0337900	SHUNT		-	-	-	-	-

The typical I²t is an average value calculated from the breaking capacity tests by using the melting time before the arcing occurs.

Time-Current Characteristic Curves

1000.								
100.								
100.								
10.								
1.								
0.1								
0.1								
0.01								
0.01	1 10 100	1000						
Current (A)								

REV11042021


Blade Fuses




MICRO3™ Blade Fuses Rated 32V

Dimensions

Dimensions in mm for reference only. See outline drawing for dimensions and tolerances.



Temperature Rerating Curve



SHUNT Maximum Continuous Load: 15A

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Fuses category:

Click to view products by Littelfuse manufacturer:

Other Similar products are found below:

HBO-10 HBO-100 HBO-150 HBO-40 HBO-50 AFX-150 AT-10 AT-30 AT-5 ATM-10ID ATM-4LP ACL-50 AFX-50 299080 HBO-15 AT-20 AT-3 0287015 142.7010.5502 FMM-15 0MIN015.HXGLO 0695030.PXPS 0695040.PXPS 0297003.WXT 0MIN025.HXGLO 0MIN030.HXGLO 0695025.PXPS 0695015.PXPS 0695050.PXPS 0695060.PXPS MRBF-075 02400106P 0297002.WXT 0297004.WXT 0297010.WXT 0297015.WXT 0297020.WXT 0297025.WXT 0297030.WXT 029707.5WXT 0602925 0602930 0602935 0602940 0602950 0611100 0611125 0611150 0611175 0611225