

MDB SERIES MIDI POWER DISTRIBUTION FUSE HOLDER

200A • 2 or 3 Outputs • Sealed • AssureLatch™



Description

The MDB series is an internally bussed, water-proof and dust-proof fuse holder developed for high current loads, and harsh conditions. The unit is well-suited for near-the-battery applications and can be mounted in exposed locations to fit your design. The MDB series can be configured with 2 or 3 MIDI® fuses and includes the cover seal and M5 thread bolts for a fuse installation. Cable seals (grommets) are optional and fuses are sold separately.

Features and Benefits

- AssureLatch[™] yellow positive-sealing latches keep the cover securely in place while allowing for fast service.
- Included tether connects cover to base preventing misplacement
- The module is internally bussed allowing for high current power distribution
- Innovative cable seals provide a tight seal for power cables in a variety of diameters
- Rugged mounting holes allow secure fastening
- Sealed to IP67 and IP69K for maximum flexibility in mounting location
- Spare fuse location built into cover for easy replacement

Specifications Overview

Voltage:	6 - 58V DC
Max Total Current:	200A
Fuse Torque:	5 Nm
Mounting Torque:	6-8 Nm
Operating Temp:	-40 to +85 °C
Ingress Protection:	IP67, IP69K
Flammability Rating:	UL94-V0
Wire Sizes:	Input: 16 or 25 mm² Output: 6-16 mm²

Dimensions: Applications

- Construction Vehicles
- Agricultural Vehicles
- High amperage loads

Web Resources

Download 2D print, installation guide and technical resources at: **littelfuse.com/MDB**

131x68x38 mm

PART NUMBER	POLES	DESCRIPTION	INCLU	IDED ACCESSORIES
PANT NUIVIDEN	PULES	DESCRIPTION	INPUT	OUTPUT
04980932ZXT	2	Fuse Holder Only	_	_
04980933ZXT	3	Fuse Holder Only	—	—
04980932.X	2	Fuse Holder with Caps and Seals	 1 x 25 mm² cap 1 x 25 mm² seal 	 2 x 6-10 mm² seal 2 x 10-16 mm² seal 1 x 6-16 mm² cap
04980933.X	3	Fuse Holder with Caps and Seals	 1 x 25 mm² cap 1 x 25 mm² seal 	 2 x 6-10 mm² seal 3 x 10-16 mm² seal 1 x 6-16 mm² cap

Ordering Information



Cable Seals and Caps


Input Cable Seal & Cap Options (front)


CABLE SIZE	INPUT CABLE SEAL PART NUMBER	INPUT CABLE CAP PART NUMBER
25 mm² (4 AWG)	0HBF0003ZXS25-GN (Green)	0HBF0003ZXCAP25
16 mm² (5 AWG)	OHBF0003ZXS16-PK (Pink)	0HBF0003ZXCAP16


Output Cable Seal & Cap Options (back)


CABLE SIZE	OUTPUT CABLE SEAL PART NUMBER	OUTPUT CABLE CAP PART NUMBER	NOTES
10-16 mm ² (6-8 AWG)	OHBFA001SEALB (Blue)		
6-10 mm ² (8-10 AWG)	0HBFA001SEALY (Yellow)	OHBFA001CAPB	
None (Cavity plug)	OHBFA001SEALC (Gray)		One hole blocked in 2 way housing


Dimensions in millimeters











131.35

Visit Littelfuse.com for the most up-to-date product information. Littelfuse reserves the right to make product changes, without notice. Material in this document is as accurate as known at the time of publication.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fuse Holder category:

Click to view products by Littelfuse manufacturer:

Other Similar products are found below :

570-290-741P40 570-290-751P40 020417G 020418E 6R30A1B F600A3B 80910030 8601.2020 G15A2SPQ 9-3557-GP REV A HDJ-B R6J30A3S HFH-1 RF30A2B RF30A3SP 15600-08-10 BK/FHN19G BK/HHM BK/HKP-CCHH BK/HKP-JJ BK/HTJ-LES-FUSE HMG-241 HTJ-LES-FUSE C4044-1 2086-1 2193 2602 2650 178.000100 FHN31G1 T30A2B G4PB8 2660 2799 CQ-209V HKP-CCHH R6F30A2S 341001A 345621A CVRMCC 4202 4407 4408 4413 4423 4532 4537 TSD1404-12 BK/FHN31G1 BK/HC-5