# Cartridge Fuses





MCASE+™ Cartridge Fuses

### MCASE+™ Cartridge Fuses Rated 32V

The Unslotted MCASE+™ Fuse is a cartridge style fuse up to 40A with female terminals for 2.8 mm male terminals. The Slotted MCASE+™ Fuse is available in amperages up to 60A and can mate with larger male terminals (e.g., 6.3mm) or even mount directly to onto a busbar. It has a miniaturized footprint for optimal usage of space. It is a time delayed fuse and can handle inrush currents.

#### **Specifications**

Voltage Rating: 32 VDC Interrupting Ratings: 1000A @ 32 VDC Operating Temperature Range: -40°C to +125°C PPA-GF33 Housing Material: Cover Material: PA66

Fuse Insertion Force: 50N (11.2lbf) Typical

**Extraction Force:** 4N Min. (0.9 lb). I 24.5N Max. (5.5 lb)

Conforms to: SAE 2741 and ISO 8820-4 in reference to electrical, mechanical

and environmental performance requirements

#### **Ordering Information**

Part Number	Package Size	
0695xxx.PXPS Slotted	2000	
0695xxx.PXP Unslotted	2000	

#### **Time-Current Characteristics**


% of Rating	Opening Time Min / Max
110	100hrs / —
135	60s / 1800s
200	2s / 60s
350	0.2s / 7s
600	N N4s / 1s

#### Ratings


Part Number	Туре	Current Rating* (A)	Housing Material Color	Max. Voltage Drop (mV)	Cold Resistance $(m\Omega)$	I²t (A²s)
0695015.PXP	Unslotted	15		125	5.1	310
0695020.PXP	Unslotted	20		125	3.4	750
0695025.PXP	Unslotted	25		125	2.5	1300
0695030.PXP	Unslotted	30		120	1.8	970
0695040.PXP	Unslotted	40		120	1	1550
0695015.PXPS	Slotted	15		125	5.1	310
0695020.PXPS	Slotted	20		125	3.4	750
0695025.PXPS	Slotted	25		125	2.5	1300
0695030.PXPS	Slotted	30		120	1.8	970
0695040.PXPS	Slotted	40		120	1.1	1550
0695050.PXPS	Slotted	50		120	0.8	4000
0695060.PXPS	Slotted	60		115	0.6	8500

<sup>\*</sup> The performance of the male terminal is critical to ensuring the fuse will function as designed. The current-carrying capability of the mating terminal must be verified to ensure proper system operation.

#### Temperature Rerating Curve



#### Time-Current Characteristic Curves



Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Automotive Fuses category:

Click to view products by Littelfuse manufacturer:

Other Similar products are found below:

AFX-150 AT-10 AT-30 AT-5 ATM-4LP 299080 AT-20 AT-3 0287015 142.7010.5502 0MIN015.HXGLO 0695030.PXPS 0695040.PXPS 0297003.WXT 0MIN025.HXGLO 0MIN030.HXGLO 0695025.PXPS 0695015.PXPS 0695050.PXPS 0695060.PXPS 0695040.PXPS 0695040.